# 0501 : V 150+ Core Drill and Support Stand



## The + product :

**For wet and dry / raised hand or support stand core drilling.**
3-speed motor with **progressive start**.
**Triple protection** for the motor for long lift and user safety.
**Quick, tool-free** attachment to the support stand.

## Description

**Core drill:**
Hand core drilling facilitated:
1900 W motor with triple protection.
- Electronic (in the event of overload on the motor) with alert light in the trigger,
- Thermal (in the event of overheating),
- Mechanical (axis decoupling if the core bit locks).
3 speeds: 550/1250/2700 tr/min (rotation under load).
Ready to use : the water and dust aspiration end pieces are built-in.
UNC connection 1.1/4", 1/2".
PRCD protection switch.

**Support stand:**
Aluminium column support stand and reinforcement bars to minimise vibration.
Drilling over the full height of the stand (scale in mm); Can be tilted from 0° to 45°.
Adjustable brake; Stop button; easy positioning of the V150+.
Practical: centring indicator and built-in level.
Maximum stability: base with 4 adjustment nuts, can be used fixed by anchor spindle or with vacuum pump
Right/left movement lever, movable without tools.
Dimensions (L x w x H): 350 x 250 x 1110 mm.

## More Information

| | |
|---|---|
| Capacity | Wet drilling for reinforced concrete, abrasive materials, etc.:<br>- Raised hand: Ø max 82 mm,<br>- On support stand: Ø max 152 mm.<br>Dry drilling for brick, breeze block, hollow materials:<br>- Raised hand: Ø max 200 mm (requires the use of the centre bit ref. 050158),<br>- On support stand: Ø max 152 mm. |
| Tips | The use of a water and dust vacuum (ref. 050157) is strongly recommended for dry core drilling. |
| Supplied with | **Core drill:**<br>Side handle,<br>2 flat wrenches (SW 32 and SW 41),<br>Sprinkler mechanism with bearing tap - Dust suction mechanism,<br>Plastic transport case.<br>**Support stand:**<br>Ready to use attachment set (anchor spindle, reusable pegs for attachment in breeze block, non reusable pegs for attachment in concrete).<br>Delivered without core bit. |

## References

| Sku | Description | Power W | kg |
|---|---|---|---|
| **050110** | V 150+ Motor and support stand | 1900 | 19,500 |
| **050111** | V 150+ Support stand | - | 13,000 |
| **050116** | V 150+ Motor | 1900 | 6,500 |
| **990022** | V 150+ Motor and support stand + Core bit Ø 127 mm | 1900 | 23,200 |
| **990023** | V 150+ Motor and support stand + Core bit Ø 127 mm + Manual water pump + Centring bit | 1900 | 30,200 |