

0501: V 250 Core Drill and Support Stand



The + product :

For wet core drilling on support stand.

Powerful 2-speed motor for **frequent use**.

Quadruple protection for the motor for long life and user safety.

1 single support stand for the 2 core drills V 250 and V 350.

Description

Core drill:

2500 W motor with triple protection:

. Electronic (in the event of overload on the motor) with alert light in the trigger,

- Thermal (in the event of overheating),

- Mechanical (axis decoupling if the core bit locks).

Fourth protection for the motor and gears thanks to an oil pumping system that enables permanent lubrication.

2 speeds: 360/850 rpm (rotation under load).

UNC connection 1.1/4".

PRCD protection switch.

Support stand:

Aluminium column support stand and reinforcement bars to minimise vibration.

Drilling over the full height of the stand (scale in mm); Can be tilted from 0° to 45°.

Adjustable brake; Stop button; easy positioning of the V150+.

Practical: centring indicator and built-in level.

Maximum stability: base with 4 adjustment nuts, can be used fixed by anchor spindle or with vacuum pump

Right/left movement lever, movable without tools.

Wheels and handle to facilitate transport.

Dimensions (L x w x H) : 538 x 330 x 1110 mm.

More Information

Capacity	Wet drilling on support stand for reinforced concrete, abrasive materials, bricks, breeze block, etc. up to Ø 250 mm.
Tips	The use of a water and dust vacuum (ref. 050057) is strongly recommended for dry core drilling.
Supplied with	Core drill: 2 flat wrenches (SW 32 and SW 41), Sprinkler mechanism with bearing tap. Support stand: Ready to use attachment set (anchor spindle, reusable pegs for attachment in breeze block, non reusable pegs for attachment in concrete). Delivered without core bit.

References

Sku	Description	Power W	kg
050120	V 250 motor and support stand	2500	32,500
050121	V 250 / V 350 support stand	-	22,000
050126	V 250 motor	2500	10,500

