

0535 : Diamond Core Bit



The + product :

For wet core drilling for reinforced concrete and abrasive materials.

For dry core drilling on breeze block, brick and non-abrasive materials.



Cold segment fusion for **extreme tear strength**.

Description

Segment composition specially optimised both for dry core drilling on abrasive materials and wet core drilling on non-abrasive materials. For fast starting upon the 1st use: tip segments (Ø 25 – 250 mm) or with release sphere (Ø 300 – 350 mm).

Segments welded by cold fusion: extreme tear strength and 100% segment used.

Re-segmentable core bit.



More Information

Capacity	Ø 25 to 350 mm. Useful length 430 mm. Segment height: 10 mm.
Tips	Respecting usage instructions (providing water for abrasive materials, vacuuming dust for non-abrasive materials) will increase the segments' lifetime. Virax can re-segment core bits for increased lifetime.

References

Sku	Ø mm	Connection "	kg
053502	25	1/2	0,420
053504	30	1/2	0,560
053506	40	1/2	0,750
053508	52	1.1/4	1,120
053510	62	1.1/4	1,330
053512	72	1.1/4	2,080
053514	82	1.1/4	2,190
053516	92	1.1/4	2,800
053518	102	1.1/4	2,850
053520	112	1.1/4	3,220
053522	127	1.1/4	3,750
053524	132	1.1/4	3,900
053526	152	1.1/4	4,560
053528	162	1.1/4	5,720
053530	182	1.1/4	6,490
053532	200	1.1/4	7,200
053534	225	1.1/4	9,040
053536	250	1.1/4	9,840
053538	300	1.1/4	13,440
053540	350	1.1/4	22,150

