

2402 : Manual Hydraulic Bender

The + product :

Bending capacity:

Gas pipes: Ø 3/8" to 4" (nfa 49115-en10255).

Locksmith's pipes: Ø 12 à 45 mm.

Multilayer pipes: Ø 40 to 63 mm.

Angle: 0 to 90°.

Description

For medium and heavy series gas pipes.

Manual hydraulic bender for worksites or prefabrication.

Simple action circuit with spring-loaded piston return.

Supplied in a wooden case with the forms and accessories.

To identify the different types of cheeks, see next pages.

Tip:

- Use Virax hydraulic ram oil for best protection.

- All necessary precautions must be taken when filling the ram to avoid foreign matter entering the reservoir as this may impair operation.

- Use horizontally.

Ref. 240233 / 240242 / 240243 / 240249 : Supplied in a wooden chest.

Ref. 240252 : Supplied in two wooden chests.



References

Sku	For pipe	Formers	Ram	Type	kg
240233	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4	Manual - n°1	Sliding cheek	44,500
240242	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	Manual - n°2	Open cheek	77,000
240243	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	Manual - n°2	Sliding cheek	71,00

Sku	For pipe	Formers	Ram	Type	kg
240249	Multilayer	40 - 50 - 63 mm	Manual - n°2	Sliding cheek	54,000
240252	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2 - 2.1/2 - 3"	Manual - n°3	Hinged cheek	170,000

