

2502 : Workbench Manual Bender

Description



Wall thickness: 0.8 to 1.5 mm. Bending angle: 0 to 180°.

Red Universal formers:

Ø 8 to 22 mm.

Grey Universal formers:

Ø 5/16 to 7/8 ".

Wall thickness: 1 to 1.5 mm. Bending angle: 0 to 180°.

Yellow Standard formers

Ø 10 to 22 mm. Short bending radius.

With Loose guide.

Provides a perfect finish as the guide follows the pipe round the bend.

Essential for bending insulated pipes.

With Sliding guide

For quick bendings and vertical works.

Supplied with an assembled body and a rapid feed lever.

Attachment: on a special base (250203), in a parallel vice, in a pipe vice.



References

Sku	Type	Composition	Ø	kg
250271	With loose guide	Universal formers	8 - 10 - 12 - 14 - 16 - 18 - 20 - 22 mm	18,600
250272	With loose guide	Universal formers	10 - 12 - 14 - 16 - 18 - 20 - 22 mm	18,400
250275	With loose guide	Standard formers	10 - 12 - 14 - 16 - 18 - 20 - 22 mm	12,500
250280	With loose guide	Universal formers	5/16 - 3/8 - 1/2 - 5/8 - 3/4 - 7/8"	15,030
250282	With sliding guide	Universal formers	10 - 12 - 14 - 16 - 18 - 20 - 22 mm	16,550
250285	With sliding guide	Standard formers	10 - 12 - 14 - 16 - 18 - 20 - 22 mm	15,000

