

1380 : Phenix Mini Portable Electric Threading Machine



The + product :

Compact, ideal for interventions in confined environment.

Locking vice with anti-torque bar to lock the machine in rotation when threading.

Robust and light, suited to all maintenance work.

Description

Dual rotation direction.

Easy to use, selector to choose rotation direction and trigger to control rotation speed according to pressure applied.

In spite of its small size, this threading machine can thread right- or left-hand BSPT, from 1/4" to 1.1/4".

Feather weight for easy transport and use.

Rotation speed: 20 rpm in both directions.

For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.



More Information

Capacity	Steel: Right-hand BSPT Ø 1/4" to 1.1/4" Left-hand BSPT Ø 1/4" to 1.1/4"
Tips	Virax cutting oil (ref. 110200) should be used for smooth die operation, ensuring a good cut and a perfect thread. For NPT threading use the Phenix III portable automatic threading machine ref. 137562.
Supplied with	- 1 locking vice (ref. 138022). - 4 Right-hand BSPT heads: 1/2" - 3/4" - 1" - 1.1/4".

References

Sku	Description	Voltage V	Power	kg
138021	Mini Phenix + 4 Right-hand BSPT heads: 1/2" - 3/4" - 1" - 1.1/4"	230	800W - 50/60 Hz	230
138020	Threader only - 230 V	230	800W - 50/60 Hz	5,800

