

1380 : Phenix Mini Portable Electric Threading Machine



The + product :

Compact, ideal for interventions in confined environment.

Locking vice with anti-torque bar to lock the machine in rotation when threading.

Robust and light, suited to all maintenance work.

Description

Dual rotation direction.

Easy to use, selector to choose rotation direction and trigger to control rotation speed according to pressure applied.

In spite of its small size, this threading machine can thread right- or left-hand BSPT, from 1/4" to 1.1/4".

Feather weight for easy transport and use.

Rotation speed: 20 rpm in both directions.

For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.



More Information

| | |
|---------------|--|
| Capacity | Steel: Right-hand BSPT Ø 1/4" to 1.1/4" Left-hand BSPT Ø 1/4" to 1.1/4" |
| Tips | Virax cutting oil (ref. 110200) should be used for smooth die operation, ensuring a good cut and a perfect thread. For NPT threading use the Phenix III portable automatic threading machine ref. 137562. |
| Supplied with | - 1 locking vice (ref. 138022). - 4 Right-hand BSPT heads: 1/2" - 3/4" - 1" - 1.1/4". |

References

| Sku | Description | Voltage V | Power | kg |
|--------|--|-----------|-----------------|-------|
| 138021 | Mini Phenix + 4 Right-hand BSPT heads: 1/2" - 3/4" - 1" - 1.1/4" | 230 | 800W - 50/60 Hz | 230 |
| 138020 | Threader only - 230 V | 230 | 800W - 50/60 Hz | 5,800 |

