

# 1375 : Phenix III Portable Electric Threader

## The + product :

For effortless threading up to 2" in all situations.

Holding vice with anti-torque bar to steady the machine during threading operations.

Ideal for working in confined spaces (close to walls, etc.).



## Description

Bidirectional rotation.

Mechanical reverse control ensuring longer motor life.

Adaptor for octagonal heads 1/4" to 1.1/4" with unique locking system for securely holding the head during difficult operations.

Rotation speed: 26 rpm in both directions.

For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.



## More Information

Capacity	<b>Steel:</b> Right BSPT Ø 1/4" to 2" Left BSPT Ø 1/4" to 2" NPT: Ø 1/4" to 2"
Tips	Virax cutting oil (ref. 110200) should be used for smooth die operation, ensuring a good cut and a perfect thread.
Supplied with	- 1 holding vice (ref. 137552) - 1 adaptor for octagonal heads 1/8" to 1 1/4" (ref. 137553).

## References

Sku	Description	Voltage V	Power	kg
137562	Phenix III + 4 Right heads BSPT: 1/2" - 3/4" - 1" - 1.1/4"	230	1100W - 50/60 Hz	18,800
137563	Phenix III + 6 Right heads BSPT: 1/2" - 3/4" - 1" - 1.1/4" - 1.1/2" - 2"	230	1100W - 50/60 Hz	22,800
137550	Threader only - 230 V	230	1100W - 50/60 Hz	7,500

