

1362 - 1363 - 1364 : Drop Head Threaders



The + product :

Lubrication and chip removal assisted by large openings.
Die position markings remain perfectly visible at all times.
Guide hole for self-centring of die-head.

Description

Heads with notched octagonal (or splined) drive for securing within the housing.
Cap for accurate positioning of dies. Also allows them to be turned around to cut threads tight up against walls without risking to be pulled out.
Long-reach centring guide for easy operation.

Compatible with manual interchangeable head threader, Mini Phenix and Phenix III, according to capacity.

To be threaded with the Mini Phenix ref. 138020 /138021, use only steel BSPT heads up to Ø 1.1/4".

For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.

* Retaining pin must be removed when used with the Phenix IIB / Phenix III threading machines (ref 1375).

References

SKU	Type	Type of thread	Ø "	Ø mm	kg
136340	Steel	Right hand BSPT	1/4	8/13	0,460
136341	Steel	Right hand BSPT	3/8	12/17	0,445
136342	Steel	Right hand BSPT	1/2	15/21	0,520
136343	Steel	Right hand BSPT	3/4	20/27	0,570

Sku	Type	Type of thread	Ø "	Ø mm	kg
136344	Steel	Right hand BSPT	1	26/34	0,720
136345	Steel	Right hand BSPT	1.1/4	33/42	0,720
136346	Steel	Right hand BSPT	1.1/2*	40/49	2,000
136347	Steel	Right hand BSPT	2*	50/60	2,150
136241	Steel	Left hand BSPT	1/8	6/10	0,460
136242	Steel	Left hand BSPT	1/4	8/13	0,460
136244	Steel	Left hand BSPT	1/2	15/21	0,510
136246	Steel	Left hand BSPT	1	26/34	0,720
136448	Steel	Left hand BSPT	1.1/2*	40/49	1,980
136449	Steel	Left hand BSPT	2*	50/60	2,150
136350	Steel	NPT	1/4	8/13	0,450
136351	Steel	NPT	3/8	12/17	0,430
136352	Steel	NPT	1/2	15/21	0,520
136353	Steel	NPT	3/4	20/27	0,570
136354	Steel	NPT	1	26/34	0,720
136355	Steel	NPT	1.1/4	33/42	0,730
136356	Steel	NPT	1.1/2*	40/49	2,000
136357	Steel	NPT	2*	50/60	2,160

