

2626 : Filetfix® III



The + product :

Quick polymerisation.

Repositionable after application.

High temperature and pressure resistance.

Consistent with the main European standards for gas, hot water and drinking water.

Description

Sealant for threaded connections in contact with town gas, natural gas, liquid petroleum gas, hot water, drinking water, air and petroleum products.

- Complies with Positive Lists (**CLP**) for contact with drinking water.
- Complies with EN 751-1 Class H / DVGW approval * (sealants for threaded connections in contact with gas and hot water).
- Complies with **WRAS** drinking water certification.

For installation in accordance with the user manual, on a Ø 1" pipe installation and at room temperature of 20°C :

- **Repositionable** for 3 minutes after application
- **Sealing is guaranteed** after 5 minutes and up to 50 bar pressure.
- **Complete polymerization** after 24h (72 h for stainless steel).

Easy to apply, thanks to its transparent precision tip.

Resistant to vibration, corrosion and most solvents.

Not to be used on pure oxygen or steam pipes, or on plastics.

For more information, see our Technical data sheet available at www.virax.com, section Documentation > Technical Sheet.

* excluding installation meeting the TRGI 2018 standard

References

Sku	Description	Packaging	kg
262600	Français	1 bottle of Filetfix® III - 60 ml	0,100
262670	Français - English - Română - Magyar - Slovenščina - Slovenčina - Ελληνικά - Česky - עברית	1 bottle of Filetfix® III - 60 ml	0,100

Sku	Description	Packaging	kg
262672	Français - Italiano - Español - Português - Nederlands - Polski - Deutsch - Türkçe - العربية	1 bottle of Filetfix® III - 60 ml	0,100

