

2931 : Cable segment pipe cleaner VAL 96QC



The + product :

'Quick Change' system: instant swapping of Ø 16 mm and Ø 22 mm cables, without tools.

Easily transportable: easy to store in a chest, cable sections are supplied in independent cages.

Continuous drive shaft: excellent protection against used water flow on the motor, as well as electrical and mechanical parts.

Description

For Ø 50 to 150 mm piping, maximum length 70 m.

Electrical motor 750 W, right / left reversible, 690 rpm, 24 kg, IP44, maintenance-free, delivering high torque for effective pipe cleaning. Timed belt for smooth motor power transmission. High wear resistance. Electrical connection cable with built-in differential circuit breaker (PRCD) providing optimum protection of the pipe cleaner but also the user.

External drive jaws allowing instant cable changing; sealed, life lubricated, maintenance free bearings.

Sheathed grip for clutch and transport.

Manual cable feed for fast and accurate approach of the tool towards the plug.

Guide pipe to prevent waste water projections in the work environment. Fastening pin securing the cable to the pipe cleaner when adding or removing a section (prevents untimely loss of the section engaged in the piping).

Feet with rubber anti-slip protection for better operating stability.

Cable sections with tempering optimized to guarantee flexibility allowing several elbows to be passed.

Metallic cable section storage and transport cage.

Simple and fast section connection / separation, T coupler for secured holding.

According to the model, special cable sections with plastic core, ideal to avoid inner cable fouling, easier to clean.

Cable sections and tools compatible with most cable segment cleaner in the market.

Capacity	Cable section Ø 16 mm / 2.30 m: for Ø 50 - Ø 100 mm piping, max length 40 m. Cable section Ø 22 mm / 4.50 m: for Ø 70 - Ø 150 mm piping, max length 70 m.
Tips	The cable sections and tools are compatible with most pipe cleaners with a cable section Ø 16 mm / Ø 22 mm.
Supplied with	Guide pipe, pair of gloves, user manual. Cable sections according to model: - Ø 16 mm: 5 sections Ø 16 mm / 2.3 m + transport cage. - Ø 16 mm with plastic core: 5 sections Ø 16 mm / 2.3 m + transport cage. - Ø 22 mm: 5 sections Ø 22 mm / 4.5 m + transport cage. - Ø 22 mm with plastic core: 5 sections Ø 22 mm / 4.5 m + transport cage. Tool sets according to model (supplied in a case VIRABOX): - Set of 3 tools for Ø 16 mm sections: straight spiral head Ø 16 mm (293158), bulb spiral head Ø 28 mm (293159), arrow blade head Ø 25 mm (293160), 1 uncoupling wrench Ø 16 mm (293162). - Set of 5 tools for Ø 22 mm sections: straight spiral head Ø 22 mm (293163), bulb spiral head Ø 40 mm (293164), conical spiral head Ø 55 mm (293165), toothed knife head Ø 76 mm (293166), toothed mill head Ø 65 mm 4 blades (293168), 1 uncoupling wrench Ø 22 mm (293169).

References

Sku	Description	Ø 16 mm	Ø 22 mm	Pipe Ø mm	Max. reach m	kg
293140	VAL 96QC machine only	-	-	-	-	29,500
293130	VAL 96QC Ø 16 and Ø 22 mm	5 x 2.30 m - Set of 3 tools	5 x 4.50 m - Set of 5 tools	50 - 150	70	69,400
293133	VAL 96QC Ø 16 and Ø 22 mm with plastic core	5 x 2,30 m with plastic core - Set of 3 tools	5 x 4,50 m with plastic core - Set of 5 tools	50 - 150	70	72,800

