

# 2941: Colour Digital Inspection Mini Camera Visioval®



## The + product :

**Image always horizontal** thanks to the self-levelling head.

**Colour touch screen** for intuitive use.

**Application on Smartphone** or tablet to view / transfer the image.

**Possible head localisation** on the 16-metre cable version.

## Description

### Colour CCD camera head:

Self-levelling image to maintain it horizontal whatever the position of the camera head.

Watertight head IP 68 down to 9 m deep. 4 built-in LEDs (power 100 Lux).

Head Ø 17 mm on 1.2 m semi-rigid cable: for inspections of Ø 20 - 75 mm / 3/4" - 3" in confined areas (ref. 294110).

### 3,5" (9 cm) colour touch screen:

Touch screen with intuitive browsing in the many settings: zoom x2, adjustable brightness, black & white image function, time stamping.

Live viewing during inspection possible on Smartphone and tablet via the Mini Visioval® app (on iOS and Android).

### Power supply / Battery life:

Internal rechargeable lithium battery 3.7 V/ 4.2 Ah, battery life several hours.

### Photo / video / voice recording:

Resolution: Photos 720 x 480 (jpeg) / Videos 640 x 480 (avi)

Built-in microphone to record voice comments on real-time videos or photos.

3 transfer modes: via SD card, USB port (cable supplied), or built-in Wifi transmitter for Smartphone or tablet transfer using the Mini Visioval® app (with synchronisation function), to later add annotations to the image, send by email or SMS.

**Cable 16 m (ref. 294121):** to be used with the Mini Visioval® ref. 294110:

Head Ø 25 mm to inspect the Ø 40 - 100 mm / 1.1/2" - 4" up to 16 metres distance (can negotiate 90° bends in 50 mm internal diameter pipes)

4 built-in LEDs (power 125 Lux).

Head fitted with a 512 Hz transmitter to be detected by the Virax localizer ref. 294130.

Other characteristics of the head equivalent to those of the Mini Visioval® ref. 294110.

Cable in turret open with guide for easy storage and cleaning. Base with anti-slip and anti-scratch rubber pads.

More Information

Capacity	Ref. 294110: Head Ø 17 mm on 1.2 m semi-rigid cable: for inspections of Ø 20 - 75 mm / 3/4" - 3" in confined areas (ref. 294110). Ref. 294121: Head Ø 25 mm to inspect the Ø 40 - 100 mm / 1.1/2" - 4" up to 16 metres distance (can negotiate 90° bends in 50 mm internal diameter pipes).
Supplied with	<p>Ref. 294110:</p> <ul style="list-style-type: none"><li>-1 cable 1.2m.</li><li>-1 USB mini-cable.</li><li>-1 SD card.</li><li>-1 charger for internal battery.</li><li>-In plastic case.</li></ul> <p>Ref. 294121:</p> <ul style="list-style-type: none"><li>-1 cable 16 m.</li><li>-2 AA batteries to supply the 512 Hz transmitter.</li><li>-In plastic case.</li></ul> <p>Ref. 294120:</p> <ul style="list-style-type: none"><li>-1 Mini Visioval camera ref. 294110.</li><li>-1 cable 16 m ref. 294121.</li><li>-In plastic case.</li></ul>

References

SKU	Description	Type head camera	For pipes internal Ø mm	Built-in record function	Possibility of localisation	Autonomy	kg
294110	Mini Visioval® 1,2 m	Fixe auto-nivellante	20 - 75	Yes	No	3-5hrs	2,090
294120	Mini Visioval® kit 1,2 m + cable 16 m	Fixe auto-nivellante	20 - 75 / 40 (50) - 100	Yes	Yes	3-5hrs	12,000
294121	Cable 16 m	Fixe auto-nivellante	40 (50) - 100	Yes	Yes	3-5hrs	9,000

