

2950 : Descaling Pump



The + product :

Faster and more effective action thanks to its **electric** manual flow reverser to remove deposits in the 2 directions.

Easy draining with its lower handle moulded in the tank

Description

Translucent, anti-impact plastic tank **to view the fluid level**.

Balanced and **powerful motor (150 W)** for a 33 l/min flow rate and an elevation height up to 12 metres.

IP54 protected motor for maximum lifetime.

Robust and practical transport handle.

Specific funnel screwed instead of the stopper **for easy filling**.

Max usage temperature: 50°C.

Virax additives must be added to optimise the action of the descaling pump. These additives are specific to the cleaning to be carried out. Their objective is to re-establish the ideal circulation in the installation for better effectiveness.

More Information

Tips

Choose the descaling fluid to use according to the material of the boiler heating element:

- **Steel and copper:** descaling fluid ref. 295010 to associate with a neutralizer 295015 to preserve the boiler, descaling pump, and environment.

- **All materials including aluminium:** multi-material descaling fluid ref. 295011 and 295012 not requiring any neutralisation phase.

Supplied with

Two 2 m long transparent pipes and 1 set of 8 connectors included to adapt to all configurations.

References

Sku	Description	Pump flowrate l/min	Motor rating kW	Tank capacity L	Elevation height m	Use	kg
295000	Descaling pump	33	0,150	15	12	Boiler	9,200

