

2950 : VIRAFILL heating water demineralization cartridge



The + product :

Environmentally-friendly for chemical-free use, thanks to its two-component resin.

Quick, easy installation: standard 3/4" screw thread.

Instant visualization of cartridge usage with color indicator.

Description

Water demineralization cartridge for **optimum protection** of the heating network (radiators or underfloor heating) thanks to its two-component resin that filters out the **minerals responsible for network degradation** (sludge, corrosion, limescale).

Suitable for total or top-up filling of a heating network.

Non-harmful to people and the environment, **with no added chemicals**, thanks to its two-component filter resin.

Maintains heating system **efficiency** over time, resulting in **energy savings**.

Quick and easy to install directly on the heating network.

Visual indicator lets you know when to replace the cartridge, as **the resin changes from blue to beige** when the cartridge is no longer filtering. As long as there is blue resin, filtration quality is still 100%, so the cartridge can be used for another installation.

Complies with current standards for filling heating circuits in countries subject to regulations*.

3 proof-of-intervention labels included to indicate that the heating system has been filled with demineralized water.

*SICC BT 102-01 (CH), VDI 2035 (DE), Ö - NORM H 5195-1 (AT), UNI 8065 (IT).

More Information

Tips

Rinse the inside of the cartridge before use to remove any impurities (drain off 3 liters of water).
To store the cartridge after opening, it is advisable to fill it 3/4 full of water, so that the resin remains moist.
When the cartridge has become completely beige (0%), replace it with a new one, even during filling.
The VIRAFILL cartridge completes the mechanical action of the VIRAFAL by being used after the sludge removal operation.

Features

Cartridge water filtration capacity at 10°FH: 400 liters*.
Maximum cartridge water flow rate: 4-5 l/minutes.
Maximum cartridge water pressure: 4 bar.

Maximum cartridge water temperature: 60°C.
Cartridge shelf life after opening: 3 years.
Cartridge installation by immediate standard 3/4" connection.

*depending on water hardness, region and temperature.

Supplied with

- 3 proof-of-intervention labels

References

SKU	Description	Size mm	kg
295040	VIRAFILL heating water demineralization cartridge	440 x 80 x 80	1,800

