

2942: Thermo Visioval® Thermal camera

The + product :



Fast, accurate diagnostics: high-resolution 256 x 192 pixel thermal sensor.

Detailed view: 3.5" 320 x 240 pixel screen.

Detection of the smallest temperature variations: high thermal sensitivity.



Description

Thermal sensor:

Measure malfunctions with an accuracy of $\pm 2^{\circ}\text{C}$ or $\pm 2\%$ thanks to **the high-resolution infrared thermal sensor** (256 x 192 pixels), with a temperature range from **-10°C to 400°C** .

Visualize the details of your thermal images on **the 3.5" widescreen display** with **320 x 240 pixel** resolution.

Quickly scan large areas with **the $50^{\circ} \times 37^{\circ}$ wide-angle lens**.



Features / settings :

Easily differentiate temperature differences according to the environment, thanks to **5 color palettes**.

Locate and compare maximum, minimum and central temperatures simultaneously with **the pointer display**.

Navigate the screen **intuitively** thanks to **black, non-slip Soft Touch buttons** for use even with wet hands.

IP 54 protection for indoor and outdoor use; **shock-resistant** thanks to **Soft Touch protective shell**.

Photo recording, with transfer via USB-C cable (included) or 4 GB micro-SD card (included).

Up to **4 hours' autonomy** thanks to its **3.7 V Li-ion battery**; **2-hour** recharge time via USB-C cable (included).

Compact (designed to fit in a pocket) and **lightweight** (only 210g).

More Information

Supplied with

USB-C cable → for universal connectivity
4GB micro-SD card → for a capacity of +17,000 photos
Textile cover → for easy transport

References

Sku	Description	Size mm	kg
294205	Thermal camera THERMO VISIOVAL®	130 x 30 x 90	0,210

