

The **MAPP**[®] torch,
a must in your toolbox!



For faster soldering work.

 **virax**



Trigger lock for continuous use.

- Standard MAPP® Pro MAPP®



Easy head changing without tools.

- Standard MAPP® Pro MAPP®



Can be used in **all positions** (360°).

- Standard MAPP® Pro MAPP®



Standard MAPP®
Ref. 521715
Ref. 521710

Standard tip head



Pro MAPP®
Ref. 521735
Ref. 521720

Extra-wide turbojet head
(delivered in standard).

Trigger lock
for easier work.

Easy replaceable
head without tools,
with a range of 6 different
heads.

Standard equipment:

- **Powerful:** the MAPP® torch heats up to 2400 °C, faster than a standard butane/propane mix.
- **Long operating** time up to 2h30.
- **Very broad range of** operating temperatures: -20° to 50 °C.
- **Can be used in any position and lightweight** for a lower stress index.
- **Piezo lighting** and accurate flame adjustment.
- **Non rechargeable** cartridge, 1" UNEF thread.
- **Safety valve** to remove the cartridge even when not empty.



Specifications

Description	Blowpipe and head	Cartridge	Soft soldering	Brazing	Ref.
Standard MAPP® kit	Delivered with	Delivered with	Ø 18 mm	-	521715
Standard MAPP® blowpipe	Delivered with	-			521710
Pro MAPP® kit	Delivered with	Delivered with	Up to Ø 54 mm	Up to Ø 18 mm	521735
Pro MAPP® blowpipe	Delivered with	-			521720
MAPP®	-	Delivered with	-	-	521700



Heads (for MAPP® Pro only)

Description	Soft soldering	Brazing	Use	Ref.
Superslim tip head	Ø 10 mm	-	Accurate and stable flame.	521721
Standard tip head	Ø 18 mm	-	Accurate, stable and strong flame.	521722
Turbojet head	Ø 40 mm	Ø 18 mm	Cyclone effect for even and fast heating.	521723
Extra-wide turbojet head	Ø 54 mm	Ø 18 mm	Cyclone effect for even and fast heating.	521724
Hot air burner head	-	-	Stripping and shrinking work, powerful hot air flow, wind-proof, to heat roofs.	521725
Soft flame burner head	Ø 22 mm	-	Shrinking and heating work, soft and powerful wind-proof flame. Wiring, heat-shrinking work.	521726



www.virax.com

VIRAX France : client.fr@virax.com
Tel. : +33 (0)3 26 59 56 78 - Fax : +33 (0)3 26 59 56 20

VIRAX International : export@virax.com
Tel. : +33 (0)3 26 59 56 97 - Fax : +33 (0)3 26 59 56 70

