

1

.

000



Powerful, compact portable threading machine



FRANCE

Bidirectional rotation

NEW Generation

Phenix III bidired Portable threading machin For effortless threading up to 2" in all situations

Cutting capacities:

Steel pipes: Right-hand BSPT/ Left-hand BSPT / NPT: Ø 1/8" to 2" Stainless steel pipes: Right-hand BSPT: Ø 3/8" to 1.1/4"

Specifications:

Weight: 7.5 kg (machine only) Rated power: 1100 W Rotation speed: 26 rpm in both directions Dimensions: 591 x 167 x 102 mm



Bidirectional operation allows cutting of right-hand or left-hand BSPT threads without changing the machine position.



Holding vise with antitorque bar to steady the machine during threading operations.

WHEDX

Bidirectional rotation for threading in both directions and reversal without changing positions

Characteristics

DESCRIPTION	Ref.
Phenix III + 4 RH BSPT heads: 1/2" - 3/4" - 1" - 1.1/4"	137562
Phenix III + 6 RH BSPT heads: 1/2" - 3/4" - 1" - 1.1/4" - 1.1/2" - 2"	137563

Accessories

DESCRIPTION	Ref.
230 V Phenix III without attachments	137550
Holding vise	137552
Adaptor for octagonal heads 1/8" to 1.1/4"	137553
Vise jaws for stainless steel pipes	137507

ctional

e

Mechanical reverse control ensuring longer motor life Replaceable carbon brushes



Ideal for working in confined spaces (close to walls, etc.)



Adaptor for octagonal heads 1/8" to 1 1/4" with unique locking system for securely holding the head during difficult operations.





Unlocked



Ergonomically designed handle for greater comfort of use.



Powerful 1100W motor for threading up to 2".



Phenix III threading machine sets come in a plastic case containing:

evirax

- 1 Holding vise (ref. 137552)
- 1 adaptor for octagonal heads 1/8" to 1 1/4" (ref. 137553)
- 1 spare set of carbon brushes (ref. 753291)



High standard, high performance Virax threading heads.

Thread type


ø"

- Large openings for easy lubrication and shaving removal.
- Markings for accurate positioning of dies.
- Long-reach self-centring pipe guide.
- Heads compatible with Virax manual threaders.

ourax -	Right-hand BSPT steel
Co Corres	Left-hand BSPT steel
	Right-hand BSPT stainless steel
CO vrav	NPT steel

Right-hand BSPT	1/8	6/10	-	136231
	1/4	8/13	-	136232
	3/8	12/17	137043	136233
	1/2	15/21	137044	136234
	3/4	20/27	137045	136235
	1	26/34	137046	136236
	1.1/4	33/42	137047	136237
	1.1/2	40/49	-	136438
	2	50/60	-	136439
	1/8	6/10	-	136241
	1/4	8/13	-	136242
	3/8	12/17	-	136243
	1/2	15/21		136244
	3/4	20/27		136245
BSP1 -	1	26/34		136246
	1.1/4	33/42	-	136247
	1.1/2	40/49	-	136448
	2	50/60	-	136449
	1/8	6/10	-	136251
	1/4	8/13	-	136252
	3/8	12/17	-	136253
	1/2	15/21		136254
NPT	3/4	20/27		136255
	1	26/34		136256
	1.1/4	33/42	-	136257
	1.1/2	40/49	-	136458
	2	50/60	-	136459

Ømm



Packaging	Ref.
1L bottle	110101
5L bottle	110105
20L bottle	110120
Spray can	110200
5L bottle	110505
5L bottle	110605
	1L bottle 5L bottle 20L bottle Spray can 5L bottle



39, quai de Marne - BP 197 - F 51206 Epernay Cedex **www.virax.com**

Service client France - Tel.: +33 (0)3 26 59 56 78 - Fax: +33 (0)3 26 59 56 20 - client.fr@virax.com International Customer Service - Tel.: +33 (0)3 26 59 56 97 - Fax: +33 (0)3 26 59 56 70 - export@virax.com Ref.

Steel

Stainless steel