

MAKE THE MOST OF YOUR TALENT

MAKES THE OF YOUR **TALENT**

At Virax, we are convinced that your talent needs quality solutions so you can fully develop your abilities. This is why our teams work with discipline and passion each day to boost quality; not only for our products, but also for our services.

We have been manufacturing our products in France, in Epernay, for almost a century now. This is no accident: we truly believe that our commitments are synonymous with quality and therefore loyalty.

We listen to our customers, both in France and abroad, and abroad, to improve our ranges each and every day, while our R&D team innovates to enhance our products in order to make your operations more effective, simple and qualitative.

Our commitments to boost your operations!



CONTENTS





VIRAX was created with the famous "Virax threader" that "turns around the Axis".

> Conquering foreign markets thanks to VIRAX threaders. VIRAX operates in over 42 countries.

> > Relocation to Epernay (51), in the French region of La Marne.

VIRAX launches its new soldering / waterproofing / roofing range.

ISO 9001 certification was obtained.

Visioval Digital inspection camera ® & M20+ Electro-mechanical Pressing fitting machine launched.

> Environmental certification obtained: ISO 14001.





MADE IN FRANCE AND PROMOTED WORLDWIDE.

VIRAX has established its reputation as a reference tool manufacturer for pipe maintenance and installation professionals. Both in fluid and gas applications, for almost a century!

With more than 2,500 products in its catalogue and over 10,000 references produced, VIRAX is currently the leader in France and number 4 in the European market.

The Quality policy implemented by VIRAX has been repeatedly praised and rewarded by the most demanding certifications over more than 20 years:

- ISO 9001 since 1997.
- ISO 14001 since 2008.
- OHSAS 18001 since 2008.







PRODUCTION AFTER-SALES SERVICE WARRANTY

Over 70% of our product range is industrialised in our 20,000 m² plant in Champagne region. As our tools are often used in harsh conditions, we build them to last using premium materials and the best industrial solutions available. On this basis, we are comfortable to offer a 2 year warranty on all Virax products.

Thanks to our investments in our hardware and software capacities, we are now able to adapt in real time our production. This enables to boost our deliveries and improve our service, satisfying further market demands.

Our commitment to the quality and the excellence of VIRAX products relies on an after sales service reaching equivalent standards. Based on this principle, the VIRAX after sales team is listening and available, but also offers tools on an extranet to simplify customer requests 24/7.

RESEARCH & DEVELOPMENT

As well as monitoring technical and technological innovations in the markets and listening carefully to our customers, we are convinced that only a strict process can lead to the promotion of a quality solution.


From the basic idea to the day the product is available on the shelves, the complete company is involved in the research and development process for a VIRAX product. Several prototypes may be required to meet both our requirements and the customer's needs

New products and upgrades at our R&D unit in Epernay are systematically based on a deep-rooted drive:

- The drive to satisfy and plan ahead for the needs of our most demanding customers.
- The drive to create innovative tools, which are able to boost the quality and productivity of our professional customers
- The drive to surprise the market thanks to ingenious developments of our products made by our engineers.

All of the resources invested in our R&D department feed one simple ambition: establish our position as the benchmark for innovation, performance and reliability in the world of pipe tools.







quality control

the 1st prototype

the approved product

MAKE THE MOST OF OUR USERS


VIRAX tools are by your side throughout your projects: What could you tell us?

Working since 1995, I'm the 4th generation of heating and plumbing experts in my family. In our company, VIRAX tools are passed on from father to son, sharing our professional history and expertise. Despite their age, they are still operational and active. My favourite is a copper bender, which we've had for around 45 years, and which I still take with me on jobs."

How would you describe VIRAX and its tools?

"These tools are innovative, effective and robust. VIRAX helps companies such as ours to move forward. Every VIRAX innovation is good news for plumbers."





VIRAX tools were by your side during your apprenticeship and the Worldskills France tests: How did these tools help to ensure your success?

"VIRAX is THE brand in this market. Participating in Worldskills France tests with VIRAX tools is highly reassuring as quality is on the agenda."

How would you summarise the VIRAX brand in just 3 words?

"Quality - French - Top-of-the-range."

VIRAX tools are by your side throughout your projects: What could you tell us?

"I have been using VIRAX tools for all of my plumbing and heating jobs since 1986. I work extensively with Sibéria, the test pump, Phénix, bending pliers, P25, the pipe cutter, etc. ... To cut a long story short, I practically own the entire catalogue."

How would you describe VIRAX and its tools?

"They are great tools, the best you can get for professionals. They are profitable as they are long-lasting and will not let you down in the middle of a job."





PIPE WRENCH	14	SANICROM WRENCH 25
RACK-TYPE WRENCH	16	PLUG WRENCH 27
TWIN SLIP-JOINT	16	CARPENTERS PENCIL / CHALK LINE 27
STRAP WRENCH	18	LEVEL 27
STILLSON WRENCH	19	HEXAGON SOCKET SCREW KEY SET 29
VIGRAGRIP WRENCH	19	REDUCING PLIERS 29
CHAIN WRENCH	20	SCREWDRIVER 30
ADJUSTABLE WRENCH	21	SQUARE 31
RADIATOR WRENCH	23	MEASURING TAPE 32
RATCHET WRENCH	24	FITTING BAR 32
UNIVERSAL WRENCH	24	

PIPE WRENCH

0100 : Swedish key - 90°

90° head angle. Narrow parallel, tapered jaws for effective nut gripping. Easily grips thin materials. Non-pinch handles.





Α"	A mm	A max.	L"	L mm	E mm	Kg	Ref.
1	34	47	12.1/2	305	15	0,765	010011
1.1/2	49	63	16.3/4	420	18	1,410	010012
2	60	82	22	535	22	2,500	010013

0100 : Swedish - 45° Pipe Wrench

45° head angle. Parallel jaws for effective nut gripping. Teeth fully surround the pipe so it cannot escape.

Special notch for nut corner. Non-pinch handles.





Α"	A mm	A max.	L"	L mm	E mm	Kg	Ref.
1	34	45	12.1/2	315	10	0,725	010041
1.1/2	49	61	16.3/4	445	12	1,380	010042
2	60	82	22	560	14	2,600	010043


0104: Swedish Pipe Wrench

Teeth fully surround the pipe. No risk of slippage. Pipe gripped at three points. Non-pinch handles.





Α"	A mm	A max.	L"	L mm	E mm	Kg	Ref.
1	34	48	12	320	14	0,860	010434
1.1/2	49	55	16.1/4	440	19	1,580	010449
2	60	68	22	550	21	2,830	010460



0105 : Swedish - 45° Pipe Wrench

45° head angle. Parallel jaws for effective nut gripping. **Easily grips thin materials.** Non-pinch handles.





Α"	A mm	A max.	L"	L mm	E mm	Kg	Ref.
1/2	21	29	9.1/2	240	15	0,465	010521
1	34	45	12.1/2	315	17	0,800	010534
1.1/2	49	59	16.3/4	440	20	1,450	010549
2	60	76	22	560	23	2,700	010560
3	90	102	27.3/4	705	28	4,160	010590

0106: Chain Wrench

Forged, heat-treated jaws for a powerful grip. Heat-treated nickle-chrome pin. Fast opening. Heavy-duty tool for securely tightening pipes in difficult-to-reach locations (water and gas pipes in trenches, pipelines, etc.).





Α"	A mm	C mm	L"	L mm	E max. mm	E1 mm	Kg	Ref.
1/8 - 1	10 - 34	275	14	350	52	16	1,175	010610
1/8 - 3	10 - 90	470	27	680	64	20	4,100	010611
1/4 - 6	13 - 165	690	36	930	90	32	7,650	010613

0107: Chain Wrench

Reversible jaws double the lifespan of the wrench.

Very heavy-duty wrench for tightening the large diameter pipes used in the chemical and petroleum industries, shipyards, etc.





Α"	A mm	C mm	L"	L mm	E max. mm	E1 mm	Kg	Ref.
1/4 - 2.1/2	13 - 76	415	22	550	55	22	3,200	010731
3/4 - 4	27 - 114	560	35	900	60	20	5,900	010732
1 - 6	34 - 165	690	42	1065	80	32	8,720	010733
1.1/2 - 8	48 - 219	1090	50	1285	82	32	14,500	010734
2 - 12	60 - 320	1440	64	1600	100	40	24,000	010735



100% guarantee for 2 years

Virax guarantees all its products for 2 years at 100%, excluding consumables and batteries, and excluding abuse or product modified.

RACK-TYPE WRENCH

0108 : Adjustable Wrench

Sturdy, wide-opening wrench. Easy to adjust. Made in hardened steel. Ground and chrome finish.





A max. mm	A hex. nut	L"	L mm	E mm	Kg	Ref.
60	39 mm - 1.1/2"	9	230	17	0,480	010823
70	45 mm - 1.3/4"	11	280	20	0,780	010828
80	52 mm - 2.1/16"	15	375	22	1,580	010838

TWIN SLIP-JOINT

0109: Twin Slip-Joint Pliers

Excellent grip on all shapes. 7 position rack, for high precision adjustment. Non-pinch interlocking handles.





A mm	L mm	P mm	E mm	Kg	Ref.
17	175	18,5	6	0,160	010917
30	240	27	7	0,310	010924
36	300	35	10,5	0,485	010930

0112 : Insulated Slip-Joint Pliers - Straight Jaws

Grooved ratchet system prevents slippage for effective tightening. Plastic handle grips. Chrome-vanadium steel body. Straight jaws: very large capacity.





A mm	L mm	P mm	E mm	Kg	Ref.
100	400	75	14	1,065	011240

0182: Extra-Wide Opening Multigrip Pliers

Advantages

Practical: wide opening to substitute for several pliers. **Ergonomic** with very large handles for a better grip.

Avoids slipping with self-clamping inward curved teeth.

Extra-wide opening, between 28 and 70% wider than typical pliers: one set of pliers instead of several (saves weight and space in the toolbox).


Available with classical or non-slip handles for a better grip.

Extra-wide handles for a better grip and lesser effort.

Chrome vanadium pliers, forged for a very high strength tool with double thermal treatment.







A mm	L mm	P mm	E mm	E1 mm	Sheathed grips	Kg	Ref.
35	180	32	6	13	no	0,240	018202
56	250	45	8	15	no	0,420	018208
35	180	32	6	13	yes	0,245	018212
56	250	45	8	15	yes	0,425	018218

0182 : Extra-Wide Multigrip Pliers with Fast Locking Button

Advantages

Practical: wide opening to substitute for several sets of pliers.

Ergonomic with very large handles for a better grip

Fast with a fast locking button for accurate adjusting.

Extra-wide opening, up to 30% wider than typical pliers: one set of pliers instead of several (saves weight and space in the toolbox).


Fast locking button for easier and more accurate adjusting, 18 locking positions Non-slip handles for a better grip.

Extra-wide handles for a better grip and lesser effort.

Chrome vanadium pliers, forged for a very high strength tool with double thermal treatment.







A mm	L mm	P mm	E mm	E1 mm	Sheathed grips	Kg	Ref.
45	180	32	6	18	yes	0,240	018222
52	250	45	8	20	yes	0,425	018228

0182: Display for Extra-Wide Opening Multigrip Pliers

Counter display box containing 4 x 180 mm extra-wide opening multigrip pliers with non-slip handles (018212), 4 x 250 mm extra-wide opening multigrip pliers with non-slip handles (018218), 4 x 180 mm extra-wide multigrip pliers with fast locking button (018222), 4 x 250 mm extra-wide multigrip pliers with fast locking button (018228).

Kg	Ref.
5,600	018230





0113: Large-Capacity Plumbing Wrench

Ideal for tightening and loosening large nuts in difficult-to-reach locations. Rounded jaws suitable for sanitary installations (traps, couplers, etc.). 3 settings. Supplied with plastic jaws.





A mm	L mm	P mm	E mm	Kg	Ref.
60	240	42	10	0,310	011324

STRAP WRENCH

0116: Strap Wrench

For use where the surface of the parts to be tightened must remain unmarked, such as chrome pipes, connectors or tap fittings, as well as components made from stainless steel or plastic, etc. Very high strength replaceable nylon strap.

High-strength light alloy handle. End of handle shaped to allow strap to be self-tightening.





Α"	A mm	L"	L mm	E mm	C mm	E1 mm	Kg	Ref.
2	60	12	315	42	450	30	0,320	011600
4	114	12	315	42	750	30	0,355	011610
14	350	12	315	42	1500	30	0,360	011620



Virax and the environment

Virax is committed to environmental protection and sustainable development, as demonstrated by our ISO certification 14001: 2015 for our environmental management system.

Compliance with the REACH Directive no.1907/2006.

Low energy consumption.

Dematerialisation of documentary flows and printing control.

Waste control and reclaiming.

Packaging materials recycled in a partnership with Eco Emballage.

Anticipation of pollution risks.

STILLSON WRENCH

0125: Stillson Wrench

Springs housed inside the casing provide an instant grip on the pipe and efficient self-tightening and ratchet-like action.

Special heat-treated steel handle and jaws.





Α"	A mm	L"	L mm	E mm	Kg	Ref.
3/4	27	8	200	12	0,280	012520
1	34	10	250	16	0,600	012525
1.1/2	49	14	350	20	1,130	012535
2	60	18	450	23	1,845	012545
2.1/2	76	24	600	26	3,100	012560
3.1/2	102	36	900	28	5,975	012590

VIGRAGRIP WRENCH

0136 : Light Alloy Offset Viragrip® Pipe Wrench

Perfect for working in difficult-to-reach places: along walls and floors, between pipes next to ceilings, etc. Replaceable lower jaw.





Α"	A mm	L"	L mm	E mm	Kg	Ref.
1.1/2	49	14	350	34	0,900	013614
2	60	18	450	39	1,460	013618
2.1/2	76	24	600	47	2,485	013624

0137 : Light Alloy Viragrip® Pipe Wrench

The upper jaw is forged in heat-treated steel, equipped with 2 springs ensuring efficient self-tightening on the pipe and allowing ratchet-like action. Double high-frequency hardened teeth.

Lightweight, very easy to handle. Replaceable lower jaw.





Α"	A mm	L"	L mm	E mm	Kg	Ref.
2	60	14	350	23	0,985	013735
2.1/2	76	18	450	27	1,675	013745
3	90	24	600	30	2,650	013760
5	140	36	900	32	5,210	013790

0138 : Viragrip® in Heavy Duty Cast Iron

Advantages

High effort resistance: reinforced model.

Efficient: self-clamping on pipe. Fast: moving jaw ratchet effect.

Viragrip® pipe wrench, 6" to 48", for tubes of Ø 3/4" to 6".

Reinforced handle and head for use in extreme tightening conditions.


Moving jaw made from treated forged steel, with 2 springs allowing effective self-tightening of the tube and providing clamping force identical to that of a ratchet. High-frequency double hardening for gear teeth.

In accordance with standard US/GGG-W-651-E.

HEAVY DUTY: + 30% more strength.







Α"	A mm	L"	L mm	E mm	Kg	Ref.
3/4	27	6	150	15	0,240	013806
1	34	8	200	15	0,400	013808
1.3/4	55	10	250	20	0,770	013810
2	60	12	300	25	1,110	013812
2	60	14	350	25	1,610	013814
2.1/2	76	18	450	30	2,580	013818
3.1/2	102	24	600	30	3,740	013824
5	140	36	900	40	7,750	013836
6	168	48	1200	52	14,100	013848

CHAIN WRENCH

0141: Chain Wrench

Forged, hardened chrome vanadium steel jaws and handles made of one piece. Double set of teeth allow direction to be reversed with the wrench in position. Easy to handle tool for use in confined spaces.





	Tightening A	Tightening A mm	Pre-tigntenin g A "	Pre-tightenin g A mm	C mm	L"	L mm	E mm	Kg	Ref.
Ī	2	60	4	114	460	14	360	20	1,040	014100

0142: Chain Wrench

Reversible jaw with two sets of teeth in hardened chrome vanadium steel. Chain secured to handle at two points. Easy to handle, designed for use in confined spaces.



Tightening A"	Tightening A mm	Pre-tigntenin g A "	Pre-tightenin g A mm	C mm	L"	L mm	E mm	Kg	Ref.
2	60	4	114	475	14	350	21	1,150	014200
3	90	5	140	515	24	600	30	3,740	014210

ADJUSTABLE WRENCH

0170: Extra-Wide Opening Adjustable Wrench

Advantages

Practical:

One wrench instead of several, saves weight and space.

For confined spaces:

Thin noses and flush moving jaw when open.

2 additional extra-wide opening versions:

Classical or with thin jaws for confined locations.

Extra-wide opening, sheathed adjustable wrench, ideal for working on copper and brass in plumbing, air-conditioning, refrigeration, maintenance and heating applications. With it's wide-opening jaw and torsional strength, it replaces 3 wrenches (6"-8"-10" for ref. 017045/017047, 8"-10"-12" for ref. 017050/017052). Non-slip sheathed handle for a better grip.

Extra-wide opening adjustable wrench with extra-thin jaws (ref. 017047 and 017052) adapted to the thinnest nuts.

Ideal for assembly and disassembly of locknut systems.

Maximum access thanks to nose 50% slimmer than standard wrenches with similar opening, and even thickness over the entire nose length.

Complies with ISO 6787:2001 and ASME B107.100-2010 standards.







Accross flats A mm	Accross flats A"	E mm	E1 mm	L mm	L"	Kg	Ref.
34	1.1/4"	6	14	175	6	0,210	017045
34	1.1/4"	4	14	175	6	0,210	017047
39	1.1/2"	6	14	215	8	0,350	017050
39	1.1/2"	4	14	215	8	0,350	017052



Safety, one of the top concerns of Virax

Safety throughout the site is at the heart of Virax's concerns:

Emergency situations, incidents and accidents are avoided through a prevention process. The target is zero accident.

Mitigate, and whenever possible eliminate, nuisances and risks in terms of occupational health and safety for all staff and interveners.

Focus on safety equipment.

0170: Adjustable wrench with reversible jaw

Advantages

Reversible jaw: 1 side for pipes, 1 side for nuts.

Wide opening: the jaw opens wider than wrenches with

equivalent length.

For confined spaces: thin nose tips.

The two-in-one tool: High quality reversible jaw, with one serrated side for tightening and loosening pipes and damaged nuts, and one smooth side for usual work.

With its wide opening jaw it replaces two wrenches (6"-8" for reference 017030, 8"-10" for reference 017031, etc.)

Triple coating of nickel and chrome provides high corrosion resistance.

Ergonomic handle with anti-slip coating for better grip.

Fixed jaw graded in mm and inch for adjustment before use.

Complies with ISO 6787:2001 and ASME B107.100-2010 standards.







Accross flats A mm	Accross flats A"	E mm	E1 mm	L mm	L"	Kg	Ref.
27	1.1/16"	5,3	10,8	162	6	0,160	017030
34	1.5/16"	7,2	14,0	209	8	0,320	017031
40	1.9/16"	7,7	15,5	261	10	0,510	017032
45	1.3/4"	9,5	19,0	313	12	0,835	017033

0170 : Display Box of Extra-Wide Opening Adjustable Wrenches

Display box containing 6 x 6" extra-wide opening adjustable wrenches(017045) and 6 x 8" extra-wide opening adjustable wrenches(017050).

Kg	Ref.
4,100	017093







Much more than just quality, here's the Virax commitment!

Virax commits to total, permanent and durable satisfaction of users and therefore applies a process based on:

A proactive product plan.

A constant innovation process.

A focus on permanent improvement.

Improved customer services.

An assurance of optimum availability rate.

Customer satisfaction, the heart of our commitments.

0170 : Adjustable Wrench

Triple coating of nickel and chrome provides high corrosion resistance. Very tough. The moving jaw of 6, 8, 10 and 12" long wrenches do not protrude when open, making them suitable for use in confined spaces.





Accross flats A mm	Accross flats A"	E mm	E1 mm	L mm	L"	Kg	Ref.
19	3/4	6	10	150	6	0,120	017006
24	15/16	7	12	200	8	0,230	017008
29	1.1/8	8	14	250	10	0,390	017010
33	1.1/4	11	19	300	12	0,670	017012
45	1.3/4	18	25	380	15	1,230	017015
53	2.1/16	19	28	455	18	2,105	017018

RADIATOR WRENCH

2204 : Radiator Key Wrench With Ratchet

For fitting the captive nuts connecting the regulating valve to the radiator. Short wrench for working on ribbed nuts and internal hexagonal nuts in confined spaces.

Description	Kg	Ref.
Wrench : 3/8" - 1/2" - 3/4" - 1" + 1/2" female ratchet	0,545	220425
Wrench: 8 sizes including 3/8" - 1/2" - 3/4" - 1"+ 1/2" female ratchet	0,560	220435
1/2" female ratchet	0,420	220410
Wrench : Ø 3/8" - 1/2" - 3/4" - 1"	0,130	220420
Wrench: 8 sizes. including 3/8" - 1/2" - 3/4" - 1"	0,140	220430



2204: Radiator Key Wrench

For fitting the captive nuts connecting the regulating valve to the radiator. 18 mm square drive. Forged steel.

Description	Kg	Ref.
Wrench : Ø 3/8" - 1/2" - 3/4"	0,175	220460
Wrench: Ø 3/8" - 1/2" - 3/4" - 1" - 1.1/4"	0,315	220465





www.virax.com

Simple, quick and easy to use. Browse and download our online catalogue, Discover the new products, Find a point of sale, Subscribe to our newsletter, Ask for an appointment, In just a few clicks!

RATCHET WRENCH

3103: Flexible Head Ratchet Wrench 8-17 mm

Advantages

Accessibility:

180° flexible head and 15° angle fork

Ratchet wrench with a 5° recovery angle.

Comfort:

12-sided profile eye: easy positioning on the nut

Wrench ideal for tightening operations in difficult to access locations.

The set contains the most frequently used dimensions: 8, 9, 10, 11, 12, 13 and 17 mm. Delivered in a storage case.

Dimensions indicated on the case enabling quick selection and easy storage.







Number of wrenches	A mm	Size mm	Kg	Ref.
7	8, 9, 10, 11, 12, 13, 17	190 x 82 x 35	0,630	310325

UNIVERSAL WRENCH

2205: Universal wrench for toilet lid

Advantages

Central articulation for easier tightening/loosening. Small footprint for use in tight spaces.

Universal tool for butterfly nut for installing and removing toilet lids with most fixing systems. Optimised handle for a good grip.

Very easy to use, fast and efficient.



Size mm	Kg	Ref.
200 x 30 x 30	0,070	220510



2615: Universal Key Wrench

Advantages

Made in **zinc moulded** under pressure for **high strength and light weight**.

Multiple pattern four-way wrench, with optimized size and ergonomics.

Minimum dimension for a maximum solution.

The indispensable tool for your projects, 3 models, 3 solutions, suited for maintenance, repairs and installation work.

Electrical universal key wrench with 6 bits: electrical cabinets, sanitary installations, A/C, radiator bleeding.

Construction universal key wrench with 6 bits: service shafts, inspection hatches, radiator bleeds, sanitary installations, buildings (door and window handles).

Universal multifunction key wrench with 12 patterns: service shafts, gas and electricity meters, A/C, buildings (door and window handles), radiator bleeds. Wrench fitted with a square bit, fastened to the spring hook by a magnet system.

Description	Composition	Kg	Ref.
Electrical universal key wrench	Plat 1X7mm, PH2 , hexagonale 1/4" , carré 5 à 8mm, triangle 9 mm, pic 3-5 mm.	0,880	261502
Construction adjustable key wrench	Plat 1X7mm, PH2 , hexagonale 1/4" , carré 5 à 8 mm, triangle 9 mm, étagé 6 à 9 mm.	0,880	261501
Multifunction universal key wrench ^r	Carré 5 à 10 mm, triangle 7 à 9 mm, hexagonale 1/4", pic 3-5 mm, demi-lune 6 mm, étagé 6 à 10 mm.	0,255	261500







SANICROM WRENCH

2614: Sanicrom® Basin Wrench

Basin wrench for nuts and connections on washbasins, bathtubs, sinks or bidets. 2 interchangeable jaws.

Designed for tightening and loosening in difficult-to-reach locations. Self-tightening jaw design.





Composition	Nut size across flats " (A)	Nut size across flats mm (A)	L mm	Kg	Ref.
with small jaw	1.1/2	38	210	0,570	261400
with 2 different jaws fitting onto the same wrench	1.1/2 - 2	38 - 50	210	0,715	261410



Virax encourages WorldSkills France

As an official supplier of the national finals of Plumbing, Heating and Metallic Roofing professionals, our objective is to support apprenticeship and professional training of young adults before the age of 23. Apprentices are able to express all their talent and invest in their future while promoting their trade.

2614: Reversible Sanicrom® Basin Wrench

For nuts and connections on washbasins, bathtubs, sinks or bidets.

Direction of rotation reversed by pivoting the jaw without removing it from the tool.

Designed for tightening and loosening in difficult-to-reach locations.





Nut size across flats " (A)	Nut size across flats mm (A)	L mm	Kg Ref.
1.1/2	38	240	0,565 261420

2614 : Telescopic Sanicrom® Basin Wrench

Basin wrench with 4-position telescopic handle for nuts and connections on washbasins, bathtubs, sinks or bidets.

Min length: 280 mm, - L1: 340 mm, - L2: 400 mm, - L3: 460 mm.

180° pivoting fixed and moving jaw assembly mounted on the end of the handle.

Return spring holds the jaw in place.

Nut size across flats " (A)	Nut size across flats mm (A)	Kg	Ref.
3/8 - 1.3/8	10 - 36	0,795	261450
1.3/8 - 2.1/2	36 - 65	0,955	261460



2614: Basin Wrench

Advantages

Manoeuvrable:

Compact design for reaching awkward nuts.

Fits most taps.

Practical:

Hollow arms and end fittings to avoid obstruction by threaded rods.

For tightening and loosening tap nuts. Hollow arms, 25 cm long. Hollow end fittings for 13 mm hexagonal nuts.

Removable jaw, adjustable up to 32 mm - 1.1 / 4, for screws or fittings sinks, bathtubs, sinks

Removable jaw, adjustable up to \varnothing 32 mm - 1.1 / 4, for screws or fittings sinks, bathtubs, sinks or bidets.

Other end fittings provided: 9, 10, 11, 12, 14, 17 mm.

Description	Nut size across flats mm (A)	Kg	Ref.
Basin wrench + 7 end fittings + jaw	9 - 10 - 11 - 12 - 13 - 14 - 17 - 32	0,400	261470









Virax is on Facebook!

@viraxofficial

PLUG WRENCH

2616: Plug Wrench

Advantages

Detachable head:

Fits most drainage plugs.

M8 and M10 threads for fitting studs.

Essential accessory for our basin wrenches (2614), to hold the drain plug in place while tightening or loosening the nut.

Wrench: M8 and M10 threads for fitting double-end studs.









CARPENTERS PENCIL / CHALK LINE

2627: Carpenter's Pencil

Professional quality pencil with a very hard lead, suitable for writing on all materials.

Contents	Kg	Ref.
12 carpenters pencils	0,155	262700



LEVEL

2631 : Compact Tubular Level

Shock-resistant mini-level with ABS casing and shock-proof grips.

Magnetized surface for easier work on metallic materials.

V-shaped sole plate to adapt to tubes.

Accuracy: 0.8 mm/m.

Length: 23 cm.







L mm	H mm	E mm	Kg	Ref.
230	38	18	0,085	263125

2631 : Tubular Vial Level / Trapezoid Level

Advantages

Easy vertical levelling: front or side "double view" reading. High quality: lifetime guarantee, UV protected, one-piece vials (shock resistant).

Optimum 0.5 mm/m accuracy.

Easy front level reading with the "dual view" system and its 45° mirror.

Magnetized surface for easier work on metallic materials.

Optimum 0.5 mm/m accuracy thanks to top range one-piece vials (shock resistant), lifetime guaranteed with inside permanent engraved level line.

The vials are treated against UV radiation to prevent fading by sunlight.

Tubular vial level:

High quality in aluminium profiles with 2 machined sole plates.

Grips with shock-proof coating for protection in case of fall.


Trapezoid level:

High quality trapezoid-shaped in cast aluminium.

Shock absorbing pads allow to adjust the level with a hammer without risk of damaging the







Description	L mm	H mm	E mm	Kg	Ref.
Tubular vial level	500	60	25	0,530	263120
Trapezoid level	500	46	20	0,440	263122



2631: Level with 2 in 1 centre distance

Advantages

Special plumbing: designed for accurate alignment of

wall-mounted fixtures.

2-in-1: 3 vials for classical use as a spirit level.

Handy: supplied in reusable storage bag.

Standardized centre distance level, for accurate horizontal and vertical levelling of wall-mounted fixtures.

2 removable calibres, with vials, double thread 3/8" and 1/2".

Standardized **dimensions**: 90 - 110 - 120 - 140 - 150 - 160 - 180 - 200 - 220 mm.

Can be used as a classical level with its $\bf 3$ vials (horizontal, vertical, $\bf 45^{\circ}$). Length 50 cm

 $\label{lem:continuous} \textbf{Optimum 0.5} \ \text{mm/m} \ \textbf{accuracy} \ \text{thanks to top range shock resistant, } \ \textbf{lifetime guaranteed vials}, \ \text{with inside permanent engraved level line}.$

The vials are treated against UV radiation to prevent fading by sunlight.

Reinforced shock resistant end pieces, 2 fastening holes.


High quality aluminium profile.

Supplied with:

- 2 removable calibres.
- Storage pouch.







Description	L mm	H mm	E mm	Kg	Ref.
Level with 2 in 1 centre distance	500	50	23	0,580	263150

HEXAGON SOCKET SCREW KEY SET

3114: Set of Hexagonal Keys

Ring set of hexagonal keys.

For hexagonal socket head screws.

Number of keys	A mm	Kg	Ref.
8	1,5 - 2 - 2,5 - 3 - 4 - 5 - 6 - 8	0,150	311458



REDUCING PLIERS

3350 : Reducing Pliers

The blades inter-penetrate to form a fold on the periphery of the pipe, reducing its diameter, and allowing consistent slotted joints to be easily formed in all types of pipe (smoke and gas, extraction, ventilation, dust extraction, rainwater downpipes, etc.).

Accurate adjustment is obtained by varying the pressure on the handles.

Insulating polypropylene grips. Case-hardened blades and pins.





Туре	Capacity mm	L mm	Kg	Ref.
Short model	35	245	0,490	335000
Long Model	52	265	0,750	335010

SCREWDRIVER

3418: Magnetic screwdrivers

Advantages

Magnetic tip securing the screw, for comfortable and fast

Graded shank, handy for quick measuring.

Shank in silicon carbon steel for greater torsional strength.

quick rotation between thumb and index.

non-slip with high resistance to cold, impact, abrasion, solvents, and hydrocarbons. sliding thrust zone.

Integral grip moulded directly onto the shank with dual opposite flats.

Hexagon nut for easier unlocking of jammed screws using a wrench (not supplied). ribbed for better locking in the screw head.

Complies with the ISO 8764, ISO 2380 and EN 60900 standards (ref. 341806 1000V insulated screwdriver) guaranteeing secured use.

Supplied in reusable textile pouch (set of 8 screwdrivers, ref. 341820).

Description	Kg	Ref.
Set of 8 magnetic screwdrivers (341801 to 341808) in textile pouch	0,900	341820
Magnetic screwdriver PZ2 x 38 - 106 mm	0,063	341801
Magnetic screwdriver 5.5 X 38 - 106 mm	0,058	341802
Magnetic screwdriver PZ1 X 100 - 209 mm	0,083	341803
Magnetic screwdriver 5.5 X 100 - 209 mm	0,078	341804
Magnetic screwdriver 6.5 X 150 - 259 mm	0,108	341805
1000V insulated screwdriver 3 X 80 - 170 mm	0,043	341806
Magnetic screwdriver PZ2 X 100 - 209 mm	0,096	341807
Magnetic screwdriver 8 X 150 - 269 mm	0,155	341808
Fabric pouch for small tools	0,200	382652







3425 : Seven-Bit Screwdriver

All the bits are stored in the handle for safe-keeping and immediate availability. Very compact. Long bit-holder for difficult-to-reach screws. Fully machined tips. Magnetic bit holder. Large diameter handle: Very efficient tightening and loosening action. Excellent grip. Impact and

torsion-resistant. Total length: 185 mm. Bits length: 35 mm.

Bit	Kg	Ref.
0.8 x 5; 1 x 7; 2.5 x 8; PZ1; PZ2; PH1; PH2	0,210	342501
Torx T10; T15; T20; T25; T27; T30; T40	0,202	342511









Virax has been certified ISO 9001 since 1997

And in 2016 our Quality Management System was acknowledged through certification in its new 2015 version.

3425 : Display of Seven-Bit Screwdrivers.

Ref. 342500:

Display containing 25 seven-bit screwdrivers (342501).

Ref. 342510:

Display containing 15 Torx seven-bit screwdrivers (342511).

Kg	Ref.
6,06	0 342500
3.85	0 342510





3425: Mini Six-Bit Screwdriver

All the bits are stored in the handle for safe-keeping and immediate availability. Very compact.

Magnetic bit holder. Total length: 95 mm. Bits length: 15 mm.

E	Bit Kg	Ref.
0,8 x 5; 1 x 7; PZ	Z1; PZ2; PH1; PH2 0,092	342521



3425 : Display of Six-Bit Mini Screwdrivers

Display containing 16 six-bit mini screwdrivers (342521).

Kg	Ref.
2,880	342520



SQUARE

2206 : Square

Ref. 220610/220620:

For measuring the squareness of pipe flanges prior to welding.

Ref. 220630:

Used to copy angles.





Туре	A mm	B mm	C mm	D mm	Kg	Ref.
Flange square	380	250	90	60	1,000	220610
Flange square	530	460	170	110	1,660	220620
Bevel square	500	500	-	-	0,950	220630
Right-angle square	500	290	-	-	1,090	220640



MEASURING TAPE

3717 : Measuring Tape

New range of sturdy tape measures with bi-material stainless steel / rubber casing for optimum resistance to shock and easy grip.

Precision class: II.

Graduation front / back. Anti-reflective tape.

Hook fastened by 3 rivets on 16 mm wide tape and 4 rivets on the 25 mm tape, for heavy use. Very sturdy. Shock resistant thanks to its bi-material chrome/rubber casing. Excellent handling. Locking button for maximum comfort of use.

Built-in belt clip.

L tape m	w tape mm	Kg	Ref.
3	16	0,150	371741
5	25	0,290	371742





3717: Display of Measuring Tapes

Counter display.

Display of :	Tape dimensions	Kg	Ref.
20	3 m x 16 mm	3,070	371744
10	5 m x 25 mm	3,110	371745



FITTING BAR

2203: Fitting Bar

For tightening nipples on cast iron radiators from inside. 18 mm square drive. Flat for engaging with the internal tabs of the nipple.

Centring guide (1.1/4") . Can be used with ratchet.


For nipples	L mm	Kg	Ref.
1" - 26 x 34 mm	500	0,810	220305
1" - 26 x 34 mm	800	1,215	220308
1" - 26 x 34 mm	1000	1,500	220310
1.1/4" - 33 x 42 mm	500	1,400	220315
1.1/4" - 33 x 42 mm	800	2,120	220318
1.1/4" - 33 x 42 mm	1000	2,850	220320





Virax supports future professionals

Virax helps teachers promote the industry to students. Every year, Virax and teachers create a competition to test the skills of future graduates in a fun way. The best students win prizes to help them get started in their new profession.



Functional and hard-wearing. Your companion on every site!





2 CUTTING / SAWING / CORE DRILLING / REAMING / GAUGING

HACKSAW FRAME	36	PLASTIC-COMPOSITE PIPE CUTTER	51
SAW BLADE	36	GUILLOTINE PIPE CUTTER	56
RECIPROCATING SAW	37	SHEATH-CUTTER	57
RECIPROCATING SAW BLADE	38	HOLE SAW	58
CORE DRILL	39	SCREW-PUNCH	60
CORE DRILL ACCESSORIES	42	REAMER	60
STEEL AND CAST IRON PIPE CUTTER	44	CALIBRATION TOOL	62
STAINLESS STEEL TUBE CUTTER	46	CHAMFERING TOOL	62
COPPER TUBE CUTTER	48		

CUTTING / SAWING / CORE DRILLING / REAMING / GAUGING

HACKSAW FRAME

0490: Hacksaw frame

For 300 mm blades.

Hacksaw Frame (049000): 4 blade positions. Supplied with HSS bi-metal blade (12 teeth/cm).

Hacksaw Frame With Finger-Protecting Closed Grip (049050): 3 blade positions.

Spare blade storage in the upper frame.

Supplied with HSS bi-metal blade (12 teeth/cm).

Mini Hacksaw Frame(049070): Special grip for use where standard hacksaw cannot reach. Supplied without blades.



Description	Size mm	Kg	Ref.
Hacksaw frame	500 x 125	0,590	049000
Hacksaw Frame With Finger-Protecting Closed Grip	425 x 130	0,630	049050
Mini Hacksaw Frame	105 x 80	0,050	049070

SAW BLADE

0430: HSS Saw Blade

New High speed and precise HSS bi-metal saw blade:

- 18 teeth or 24 teeth per inch : blade perfect for steels, but also aluminium, stainless steel, PCV or wood, high thickness (18 TPI) or medium thickness (24 TPI)
- 32 teeth per inch : blade perfect for copper, but also aluminium and stainless steel, small thickness.

Overheating resistance: high longevity.

Flexible blade to be able to cut in difficult to access locations.







Use	Number of teeth per "	Number of teeth per cm	Recommended thickness mm	L mm	Packaging	Kg	Ref.
Steel	18	8	6-25	300	100	1,740	043008
Steel	24	10	3-6	300	10	0,174	043004
Steel	24	10	3-6	300	100	1,740	043010
Copper	32	12	1-3	300	10	0,174	043006
Copper	32	12	1-3	300	100	1,740	043012



Virax, a French story

Nearly a century ago, in 1920, two Frenchmen established Virax by launching its famous "Virax threader", the threader that "Turns around the Axis". Nowadays, it is still from Epernay, at the heart of the Marne and Champagne country, that Virax manufactures and distributes its professional product ranges in more than 40 countries.

RECIPROCATING SAW

0450: Reciprocating Saw

Advantages

Powerful and versatile:

The Virax reciprocating saw is the ideal tool for all intensive or occasional cutting tasks.

Electronic control:

Soft starting for better tube cutting action.

Electrical overload protection (current and temperature). **Constant electronic system** ensures constant speed under varying load.

2" Clamping vice for a perpendicular cut.

1300 W rated power for reliability.

Replaceable carbon brushes.

Fixed shoe for stability during freehand cutting.

Ergonomic rubberised casing for maximum safety and optimum grip.

Ergonomic non-slip handle for a secure grip when cutting.

Universal 12.7 and 20 mm blade holder with secure fastening screw.

Orbital movement for better removal of shavings and a faster cut.

Safety switch to avoid accidental operation.

Cutting capacities:

Steel pipe: up to 6" (168.3 mm).

Steel sections, nail-embedded wood, pallets: up to 250 mm.

Steel sheet: up to 6.3 mm thick.

Supplied with:

- 1 2" clamping vice (ref.045003),
- 1 hexagonal wrench,
- In a case.







Motor	Voltage V	Power W	Size mm	Speed cut/minute	Stroke mm	Kg	Ref.
Universal single-phase	230 V – 50/60 Hz	1300	520 x 100 x 100	2200	30	4,200	045001

0450: Reciprocating Saw Vice

Fits all shapes.

For making square-cuts in pipes and sections.





Description	Capacity "	Size mm	Kg	Ref.
Clamping vice	2	140 x 125 x 95	1,190	045003



Virax, French manufacturer

In its Production Centre extending over more than 25,000 m² situated in Epernay, France, Virax manufactures tools and machines designed by its R&D Center to meet the requirements of professionals. Plasturgy, machining, milling, grinding, assembly and painting, all these activities are performed on site for manufacturing control and quality.

RECIPROCATING SAW BLADE

0460 : Pack of 5 HSS Bi-Metal Reciprocating Saw Blades

High-performance blades suitable for bevel cuts. Blades fit the majority of sabre saws currently available on the market. 12,7 mm shank.







Use	Length x width x thckness, mm	Length x width x thickness, "	Number of teeth per inch	Number of teeth per cm	Kg	Ref.
Nail-embedded wood, metal 3-10 mm, PCV	150 x 19 x 0,9	6 x 3/4 x 0,035	10	4	0,090	046002
Metal 3-10 mm, stainless steel 2-4 mm, Aluminium 3-10 mm	150 x 19 x 0,9	6 x 3/4 x 0,035	14	6	0,092	046004
Metal 1,5-4 mm, stainless steel 1,5-4 mm	150 x 19 x 0,9	6 x 3/4 x 0,035	18	7	0,092	046005
Nail-embedded wood, metal 4-10 mm, stainless steel 4-10 mm	225 x 25 x 1,6	9 x 1 x 0,063	6-10	2/4	0,360	046010
Metal 3-10 mm, PCV, pallet	200 x 19 x 0,9	8 x 3/4 x 0,035	10	4	0,588	046011
Metal 4-25 mm	100 x 19 x 0,9	4 x 3/4 x 0,035	14	6	0,090	046013
Metal, nail-embedded wood, Aluminium, PCV 6-63 mm	300 x 19 x 1,3	12 x 3/4 x 0,050	6-10	2/4	0,280	046014



CORE DRILL

0501: V 150+ Core Drill and Support Stand

Advantages

For wet and dry / raised hand or support stand core drilling. 3-speed motor with progressive start.

Triple protection for the motor for long lift and user safety. **Quick, tool-free** attachment to the support stand.

Core drill:

Hand core drilling facilitated:

1900 W motor with triple protection.

- Electronic (in the event of overload on the motor) with alert light in the trigger,
- Thermal (in the event of overheating),
- Mechanical (axis decoupling if the core bit locks).

3 speeds: 550/1250/2700 tr/min (rotation under load).

Ready to use: the water and dust aspiration end pieces are built-in.

UNC connection 1.1/4", 1/2".

PRCD protection switch.

Support stand:

Aluminium column support stand and reinforcement bars to minimise vibration.

Drilling over the full height of the stand (scale in mm); Can be tilted from 0° to 45° .

Adjustable brake; Stop button; easy positioning of the V150+.

Practical: centring indicator and built-in level.

Maximum stability: base with 4 adjustment nuts, can be used fixed by anchor spindle or with vacuum pump

Right/left movement lever, movable without tools.

Dimensions (L x w x H): 350 x 250 x 1110 mm.

Description	Power W	Kg	Ref.
V 150+ Motor and support stand	1900	19,500	050110
V 150+ Support stand	-	13,000	050111
V 150+ Motor	1900	6,500	050116







Capacities

Wet drilling for reinforced concrete, abrasive materials, etc.:

- Raised hand: Ø max 82 mm,
- On support stand: Ø max 152 mm.

Dry drilling for brick, breeze block, hollow materials:

- Raised hand: Ø max 200 mm (requires the use of the centre bit ref. 050158),
- On support stand: Ø max 152 mm.

Delivered with

Core drill:

Side handle,

2 flat wrenches (SW 32 and SW 41),

Sprinkler mechanism with bearing tap - Dust suction mechanism,

Plastic transport case.

Support stand:

Ready to use attachment set (anchor spindle, reusable pegs for attachment in breeze block, non reusable pegs for attachment in concrete). Delivered without core bit.

Tips

The use of a water and dust vacuum (ref. 050157) is strongly recommended for dry core drilling.

0501: V 250 Core Drill and Support Stand

Advantages

For wet core drilling on support stand.

Powerful 2-speed motor for frequent use.

Quadruple protection for the motor for long lift and user safety.

1 single support stand for the 2 core drills V 250 and V 350.

Core drill:

2500 W motor with triple protection:

- . Electronic (in the event of overload on the motor) with alert light in the trigger,
- Thermal (in the event of overheating),
- Mechanical (axis decoupling if the core bit locks).

Fourth protection for the motor and gears thanks to an oil pumping system that enables permanent lubrication.

2 speeds: 360/850 rpm (rotation under load).

UNC connection 1.1/4".

PRCD protection switch.

Support stand:

Aluminium column support stand and reinforcement bars to minimise vibration.

Drilling over the full height of the stand (scale in mm); Can be tilted from 0° to 45°.

Adjustable brake; Stop button; easy positioning of the V150+.

Practical: centring indicator and built-in level.

Maximum stability: base with 4 adjustment nuts, can be used fixed by anchor spindle or with

vacuum pump

Right/left movement lever, movable without tools.

Wheels and handle to facilitate transport.

Dimensions (L x w x H): 538 x 330 x 1110 mm.

Description	Power W	Kg	Ref.
V 250 motor and support stand	2500	32,500	050120
V 250 / V 350 support stand	-	22,000	050121
V 250 motor	2500	10,500	050126







Wet drilling on support stand for reinforced concrete, abrasive materials, bricks, breeze block, etc. up to Ø 250 mm.

Delivered with

Core drill:

2 flat wrenches (SW 32 and SW 41),

Sprinkler mechanism with bearing tap.

Support stand:

Ready to use attachment set (anchor spindle, reusable pegs for attachment in breeze block, non reusable pegs for attachment in concrete). Delivered without core bit.

The use of a water and dust vacuum (ref. 050057) is strongly recommended for dry core drilling.



Virax, French manufacturing

Located in Epernay, the Capital of the Champagne region, the Virax company was formed about a century ago with the famous "Virax threader" that « Turns around the Axis ». The production centre now extends over more than 25 000 sqm.

0501: V 350 Core Drill and Support Stand

Advantages

For wet core drilling on support stand.

Powerful 3-speed motor for intensive use.

Quadruple protection for the motor for long lift and user safety. **1 single support stand** for the 2 core drills V 250 and V 350.

Core drill:

3000 W motor with triple protection:

- Electronic (in the event of overload on the motor) with alert light in the trigger,
- Thermal (in the event of overheating),
- Mechanical (axis decoupling if the core bit locks).

Fourth protection for the motor and gears thanks to an oil pumping system that enables permanent lubrication.

3 speeds: 230/500/1030 rpm (rotation under load).

Additional handle for easy transport and assembly.

UNC connection 1.1/".

PRCD protection switch.

Support stand:

Aluminium column support stand and reinforcement bars to minimise vibration.

Drilling over the full height of the stand (scale in mm); Can be tilted from 0° to 45°.

Adjustable brake; Stop button; easy positioning of the V150+.

Practical: centring indicator and built-in level.

Maximum stability: base with 4 adjustment nuts, can be used fixed by anchor spindle or with

vacuum pump

Right/left movement lever, movable without tools.

Wheels and handle to facilitate transport.

Dimensions (L x w x H): 538 x 330 x 1110 mm.

Description	Power W	Kg	Ref.
V 350 motor and support stand	3000	33,700	050130
V 250 / V350 support stand	-	22,000	050121
V 350 motor	3000	11,700	050136







Capacities

Wet drilling on support stand for reinforced concrete, abrasive materials, bricks, breeze block, etc. up to \varnothing 350 mm.

Delivered with

Core drill:

2 flat wrenches (SW 32 and SW 41),

Sprinkler mechanism with bearing tap,

Additional handle for transport and assembly

Support stand:

Ready to use attachment set (anchor spindle, reusable pegs for attachment in breeze block, non reusable pegs for attachment in concrete). Delivered without core bit.

Tips

All wet core drilling accessories are available in the Virax range.



Virax committed to WEEE management

As a producer, Virax has implemented a process for collecting Waste from Electrical and Electronic Equipment (WEEE) in compliance with the European Directive 2012/19/UE. In compliance with its environmental commitment, Virax organizes the management and recycling of WEEE at end of life.

CORE DRILL ACCESSORIES

0535: Diamond Core Bit

Advantages

For wet core drilling for reinforced concrete and abrasive

For dry core drilling on breeze block, brick and non-abrasive materials.

Cold segment fusion for extreme tear strength.


Segment composition specially optimised both for dry core drilling on abrasive materials and wet core drilling on non-abrasive materials.

For fast starting upon the 1st use: tip segments (Ø 25 – 250 mm) or with release sphere (Ø 300 - 350 mm).

Segments welded by cold fusion: extreme tear strength and 100% segment used. Re-segmentable core bit.







Ø mm	Connection "	Kg	Ref.
25	1/2	0,420	053502
30	1/2	0,560	053504
40	1/2	0,750	053506
52	1.1/4	1,120	053508
62	1.1/4	1,330	053510
72	1.1/4	2,080	053512
82	1.1/4	2,190	053514
92	1.1/4	2,800	053516
102	1.1/4	2,850	053518
112	1.1/4	3,220	053520

Ø mm	Connection "	Kg	Ref.
127	1.1/4	3,750	053522
132	1.1/4	3,900	053524
152	1.1/4	4,560	053526
162	1.1/4	5,720	053528
182	1.1/4	6,490	053530
200	1.1/4	7,200	053532
225	1.1/4	9,040	053534
250	1.1/4	9,840	053536
300	1.1/4	13,440	053538
350	1.1/4	22,150	053540

Capacities

Ø 25 to 350 mm. Useful length 430 mm. Segment height: 10 mm.

Tips

Respecting usage instructions (providing water for abrasive materials, vacuuming dust for non-abrasive materials) will increase the segments' lifetime.

Virax can re-segment core bits for increased lifetime.



Go to www.virax.com

To find a product sheet, a safety data sheet or exploded views, Go to our web site.

0500 : Vacuum Pump for Core Drill

For core drills:

V 150 + / V 250 / V 350 / V 130 / V 200 / V 300.

For quickly clamping Virax core drills without damage to the floor or wall. "Suction" effect allows drill to be secured without anchor bolts, thus avoiding damage to the support (wall, ceiling, tiling,

Supplied without slot cap + gasket (ref. 050114).

Kg	Ref.
14,300	050043



0501: Core Drill Accessories

For V 150+ / V 250 / V 350 core drills and support stands.

A complete range of accessories for different core drilling situations:

- . Wet core drilling with vacuum, water retriever and water pump (manual or electric),
- . Dry core drilling with vacuum,
- . Raised hand core drilling with centring bit (from Ø 51 mm),
- . Core drilling with vacuum pump.

Adaptors and extensions for core bits. Adaptors for Hilti® core drills.

Wheels to move the support stand.

Sharpening stone to optimise bits' cutting performance and increase their lifetime.







Description	Ø max. mm	V 150+	V 250	V 350	Kg	Ref.
Water retriever + 2 seals	152	ok	-	-	2,000	050112
Seal for water retriever	152	ok	-	-	0,150	050113
Water retriever + 2 seals	250	-	ok	-	4,000	050122
Seal for water retriever	250	-	ok	-	0,300	050123
Water retriever + 2 seals	350	-	-	ok	5,000	050132
Seal for water retriever	350	-	-	ok	0,600	050133
Support stand cover plate + seal		ok	-	-	0,500	050114
Vacuum base seal		ok	-	-	0,150	050115
Support stand cover plate + seal		-	ok	ok	0,600	050124
Vacuum base seal		-	ok	ok	0,200	050125
Wheels for support stand		ok	*	*	1,000	050119
10 anti-lock washers		ok	ok	ok	0,050	050139
Anchor spindle		ok	ok	ok	1,100	050141
Adaptor F/F 1.1/4?-1/2?		ok	ok	ok	0,650	050145
Adaptor M/M 1.1/4"-1/2"		-	-	-	0,530	050144
Extension 1/2? x 200 mm		ok	ok	ok	0,900	050146
Extension 1.1/4? x 300 mm		ok	ok	ok	3,000	050147
Hilti® adaptor DD100-DD130 SDS 1/2"-1.1/4"		ok	ok	ok	0,420	050155
Water and dust vacuum cleaner	-	ok	ok	ok	10,000	050157
Centring bit		ok	-	-	1,000	050158
Hilti® adaptor DD160-DD250 1/2"-1.1/4"	-	ok	ok	ok	0,950	050160
Steel transport case		-	ok	ok		050174

^{*}Delivered as standard

Description	Ø max. mm	V 150+	V 250	V 350	Kg	Ref.
Sharpening stone	-	ok	ok	ok	2,000	050175

0500 : Manual Water Pump

For Core Drills:

V 150+ / V 250 / V 350 / V 130 / V 200 / V 300.

Capacity: 10 L.

Max service pressure 6 bar, with safety valve.

Steel tank with polyester coating.

Kg	Ref.
6,000	050049



0500 : Electrical Water Pump

For core drills:

V 150+ / V 250 / V 350 / V 130 / V 200 / V 300.

Easy, convenient and economical system, to supply the core drill with water. It is the ideal product to solve the damaging of the core bits due to insufficient water-suppling. Warning: Always keep the pump horizontally.

Max lifting height: 1.8m.

Size mm	Voltage V	Kg	Ref.
340 x 190 x 280	220	1,640	050055



STEEL AND CAST IRON PIPE CUTTER

2101: Steel Pipe Cutter

Max thickness: 5 mm.

For quickly cutting steel pipes (gas- API-etc...) cleanly and squarely. Also cuts stainless steel pipes (> 2 mm thick) with cutting wheels 210123 and grey cast iron with cutting wheels 210122.





A pipe "	A pipe mm	L mm	H mm	E maxi mm	Kg	Ref.
1/8 - 1.1/4	10 - 42	310	118	5	1,740	210110
1/2 - 2	21 - 60	400	150	5	3,020	210120
3/4 - 3	27 - 90	460	177	5	4,220	210130

Virax a daily player in environmental protection

CITEO

As a member of Citeo, an eco-organization funding the collection and sorting of paper, Virax is committed to preserving natural resources, by using recycled paper within the company and for all its advertising media, and participating in this funding via the eco-contribution.

2101: Steel Pipe Cutter

Max thickness: 7 mm.

Designed for cutting large diameter pipes, it is fitted with a second handle on the side opposite the feed screw allowing it to be operated by 1 or 2 people. For quickly cutting steel pipes (gas, API, etc.) cleanly and squarely. Removable auxiliary handle attaches to adjusting handle to assist operation. Also works on grey cast iron pipes with special cutting wheels fitted (Ref. 210142).





A pipe "	A pipe mm	L mm	H mm	E maxi mm	Kg	Ref.
2 - 4	60 - 114	1030	235	7	9,000	210145
4 - 6	114 - 165	1110	260	7	10,300	210165

2102 : Grey Cast Iron Pipe Cutter

Max thickness: 7 mm (210210). Max thickness: 8 mm (210220).

Hardened chrome-tungsten steel cutting wheels mounted in separate sections that can be added or removed to adapt the maximum and minimum diameters to the pipe to be cut. Can also be fitted with cutting wheels for ductile cast iron.





A pipe "	A pipe mm	L mm	H mm	E max. mm	No. of wheels	Kg	Ref.
2.1/2 - 6	76 - 150	600	200	7	8	6,550	210210
5 - 12	125 - 300	1000	260	8	9	16,390	210220

2102 : Grey Cast Iron Pipe Cutter for grey cast iron

Max thickness: 5 mm.

Hardened chrome-tungsten steel cutting wheels mounted in separate sections that can be added or removed to adapt the maximum and minimum diameters to the pipe to be cut.





A pipe "	A pipe mm	L mm	H mm	E max. mm	No. of wheels	Kg	Ref.
2.1/2 - 6	76 - 150	530	235	5	9	3,800	210250

2102 : Ductile Cast Iron Pipe Cutter

Max thickness: 7 mm (210260). Max thickness: 8 mm (210265).


Can also be fitted with cutting wheels for grey cast iron.





A pipe "	A pipe mm	L mm	H mm	E max. mm	No. of wheels	Kg	Ref.
2.1/2 - 6	76 - 150	600	175	7	8	6,850	210260
5 - 12	125 - 300	1000	260	8	9	16,500	210265

2101: Cutting Wheel - Steel and Cast Iron Pipe Cutter



For pipe cutter	Description	A mm	A1 mm	E mm	Packaging	Kg	Ref.
210110 - 210120 - 210130	Steel	32	9	19	5	0,170	210121
210110 - 210120 - 210130	Grey cast iron	30	9	18,75	5	0,170	210122
210145 - 210165	Steel	41	9,55	28	5	0,435	210141
210145 - 210165	Grey cast iron	34	9,55	28	5	0,435	210142
210210	Grey cast iron	42	9,6	8	5	0,285	210211
210220	Grey cast iron	47	11,1	9,5	5	0,390	210221
210210	Ductile cast iron	45	9,6	8	5	0,300	210261
210220	Ductile cast iron	50	11,1	9,5	5	0,375	210266
210250	Construction-type grey cast iron	32	9	19	5	0,170	210251
210260	Ductile cast iron	45	9,6	8	5	0,300	210261
210265	Ductile cast iron	50	11,1	9,5	5	0,375	210266
210260	Grey cast iron	42	9,6	8	5	0,285	210211
210265	Grey cast iron	47	11,1	9,5	5	0,390	210221

STAINLESS STEEL TUBE CUTTER

2104 : Stainless Steel Pipe Cutter 6-28 mm

Max thickness: 3.2 mm.

Soft Touch® non-slip knob: good hold in hand. Quick and tool-less wheel change. Fold-away reamer blade.







A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
6 - 28	1/4 - 1.1/8	142	55	3,2	0,385	210469



Virax in France, is also...

The Virax head office, located in Epernay, France, groups all activities: R&D department, Production Centre, Quality pole, Customer service, Purchasing department, After-Sales Service... up to the Storage and Distribution center.

2104: ZR 35 Stainless Steel Tube Cutter 3-35 mm

Advantages

Soft Touch® non-slip knob, fast action adjustment.

Quick, tool-less wheel change.

4 guide rollers to prevent wheel tracking.

Max thickness: 3.2 mm.

Precise cutting from Ø 3 to Ø 35 mm according to the type of tube.


1 spare wheel.

Retractable rotating reamer with interchangeable blades.

Colour-coded end cap according to the material to be cut.







A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
3 - 35	1/8 - 1.3/8	165	64	3,2	0,450	210471

2104: Fast Stainless Steel Tube Cutter 6-67 mm

Max thickness: 2,5 mm.

Notched telescopic slide and release button for fast forward and reverse wheel adjustment.

Removable rotary hole deburrer with interchangeable blade.

Cutting wheel with 4 rollers for increased cutting precision.

Spare cutting wheel incorporated within the knob.

Soft Touch® anti-slip knob.

Colour-coded end cap according to the material to be cut.







A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
6 - 67	1/4 - 2.5/8	230	100	2,5	0,820	210483

2101 : Stainless Steel Pipe Cutter 10-90 mm

Max. thickness: 5 mm.

Excellent weight distribution giving improved inertia and providing high stiffness. Thrust ball bearing prevents slider wear and reduces the turning torque of the screw.

Ref. 210125: Also works on steel pipes with cutting wheels 210121 fitted.

Ref. 210110 - 210130 : Steel pipe cutter (supplied with a steel cutting wheel). Also works on stainless steel pipes with cutting wheels 210123 fitted.





A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
10 - 42	1/8 - 1.1/4	310	118	5	1,740	210110
21 - 60	1/2 - 2	400	155	5	3,010	210125
27 - 90	3/4 - 3	460	177	5	4,220	210130

2104 : Stainless Steel Pipe Cutter 14-54 mm

Max thickness: 3.2 mm.

Soft Touch® non-slip knob: good hold in hand. Quick and tool-less wheel change.






A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
14 - 54	1/2 - 2.1/8	185	79	3,2	0,555	210475

2104 : Cutting Wheel - Deburring Spare Blade - Stainless Steel **Tube Cutter**







For pipe cutter	Description	A mm	A1 mm	E mm	Packaging	Kg	Ref.
210110 - 210125 - 210130	Cutting Wheel	32	9	19	5	0,168	210123
210392	Cutting Wheel	18,5	4,77	3,15	10	0,038	210360
210469 - 210471 - 210475	Cutting Wheel	18,5	4,77	3,15	10	0,038	210360
210479	Cutting Wheel	24,8	4,85	6,20	1	0,010	210481
210483	Cutting Wheel	24,8	4,80	5,95	1	0,007	210482
210471 - 210483	Deburring Spare Blade	-	-	-	5	0,200	221266

COPPER TUBE CUTTER

2104: Mini Copper Tube Cutter 3-28 mm

Max thickness: 2 mm.

Very compact tube cutter. Compact swing radius allows to cut in tight spaces: under washbasin, between 2 tubes, along a wall.

Oval knob: good hold in hand ans optimum tightening.

Quick and tool-less wheel change.







A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
3 - 16	1/8 - 5/8	53	39	2	0,125	210437
6 - 28	1/4 - 1.1/8	74	51	2	0,220	210439

2104 : Copper Tube Cutter 6-28 mm

Max thickness: 2 mm.

Soft Touch® non-slip knob : good hold in hand.

Quick and tool-less wheel change. Equipped with a fold-away reamer blade.

Grooved rollers for cutting tight up against flanges.





A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
6 - 28	1/4 - 1.1/8	142	55	2	0,385	210441

2104 : ZR 35 Copper Tube Cutter 3-35 mm

Advantages

Soft Touch® non-slip knob, fast action adjustment.

Quick, tool-less wheel change.

4 guide rollers to prevent wheel tracking.

Max thickness: 2 mm.

Precise cutting from Ø 3 to Ø 35 mm according to the type of tube.

1 spare wheel.


Retractable rotating reamer with interchangeable blades.

Grooved rollers for cutting tight up against flanges.

Colour-coded end cap according to the materialto be cut.







A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
3 - 35	1/8 - 1.3/8	165	64	2	0,450	210443

2104 : Display Box of Copper Tube Cutters ZR 35

12-pieces ZR 35 Copper tube cutter - display (210443).

Kg	Ref.
5.500	210444







Virax certified ISO 14001 and OHSAS 18001 since 2009

And in 2016 our Environmental Management System was acknowledged through certification in its new version ISO 14001: 2015.

2104 : ZR 42 Copper Tube Cutter 6-42 mm

Advantages

Soft Touch® non-slip knob, fast action adjustment. Quick, tool-less wheel change.

4 guide rollers to prevent wheel tracking.

Max thickness: 2 mm.

Precise cutting from Ø 6 to Ø 42 mm according to the type of tube.

1 spare wheel.


Retractable rotating reamer with interchangeable blades.

Grooved rollers for cutting tight up against flanges.

Colour-coded end cap according to the material to be cut.







A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
6 - 42	1/4 - 1.5/8	187	76	2	0,515	210445

2104 : Fast Copper Tube Cutter 6-67 mm

Max thickness: 2 mm.

Notched telescopic slide and release button for fast forward and reverse wheel adjustment.

Removable rotary hole deburrer with interchangeable blade.

Cutting wheel with 4 rollers for increased cutting precision.

Spare cutting wheel incorporated within the knob.

Soft Touch® anti-slip knob.

Colour-coded end capaccording to the materialto be cut.







A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
6 - 67	1/4 - 2.5/8	230	100	2	0,820	210455

2104: Copper Tube Cutter 14-54 mm

Max thickness: 2 mm.

Slider-mounted cutting wheel.

Phosphate-coated cutting wheel and rollers.

Knob provides excellent grip.






A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
14 - 54	1/2 - 2.1/8	183	79	2	0,555	210447

2104 : Cutting Wheel - Deburring Spare Blade - Copper Tube Cutter







For pipe cutter	Description	A mm	A1 mm	E mm	Packaging	Kg	Ref.
210300 - 210310 - 210312 - 210320 - 210335 - 210390	Cutting Wheel	18,5	4,77	3,15	10	0,030	210350
210437 - 210439 - 210441 - 210443 - 210445 - 210447	Cutting Wheel	18,5	4,77	3,15	10	0,030	210350
210437 - 210439 - 210441 - 210443 - 210445 - 210447	Cutting Wheel	18,5	4,77	3,15	1	0,010	210352
210451	Cutting Wheel	19	4,85	6,20	1	0,010	210453
210455	Cutting Wheel	18,50	4,80	5,95	1	0,005	210454
210443 - 210445 - 210455	Deburring Spare Blade	-	-	-	5	0,200	221265

PLASTIC-COMPOSITE PIPE CUTTER

2104 : Fast feed 6-65 mm plastic pipe cutter

Max thickness: 8 mm.

For pipes in plastic, composite materials and multilayer.

Notched telescopic slide and release button for fast forward and reverse wheel adjustment.

Removable rotary hole deburrer with interchangeable blade.

Cutting wheel with 4 rollers for increased cutting precision.

Soft Touch® anti-slip knob.

Colour-coded end capaccording to the material to be cut.







A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
6 - 65	1/4 - 2.9/16	230	100	8	0,820	210497

2106 : Plastic pipe cutter 50 -110 mm plastic pipe cutter

Max thickness: 8 mm.

For pipes in plastic, composite materials and multilayer.

Releasable nut for quick fast forward and reverse wheel adjustement.

Fitted with 3 rollers to avoid crushing the pipe.





A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
50 - 110	2 - 4	295	125	8	1,230	210630

2104: ZR 35 Plastic Tube Cutter 3-32 mm

Advantages

Soft Touch® non-slip knob, fast action adjustment. Quick, tool-less wheel change. 4 guide rollers to prevent wheel tracking.


Max thickness: 3 mm.

For pipes in plastic, composite materials and multilayer. Precise cutting from \emptyset 3 to \emptyset 32 mm according to the type of tube. 1 spare wheel.

Retractable rotating reamer with interchangeable blades. Colour-coded end cap according to the material to be cut.







A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
3 - 32	1/8 - 1.1/4	165	64	3	0,450	210487

2104 : ZR 42 6-40 mm plastic pipe cutter

Advantages

Soft Touch® non-slip knob, fast action adjustment. Quick, tool-less wheel change. 4 guide rollers to prevent wheel tracking.


Max thickness: 4 mm.

For pipes in plastic, composite materials and multilayer. Precise cutting from Ø 6 to Ø 40 mm according to the type of tube.

Retractable rotating reamer with interchangeable blades. Grooved rollers for cutting tight up against flanges.








A mm	A " OD	L mm	H mm	E maxi mm	Kg	Ref.
6 - 40	1/4 - 1.1/2	187	76	4	0,520	210489

2104 : Cutting Wheel - Deburring Spare Blade - Plastic-composite **Tube Cutter**







For pipe cutter	Description	A mm	A1 mm	E mm	Packaging	Kg	Ref.
210487 - 210489	Cutting Wheel	26	4,77	3	10	0,030	210488
210493	Cutting Wheel	26	4,85	6,20	1	0,010	210495
210610	Cutting Wheel	22	4,77	3	5	0,070	210611
210630	Cutting Wheel	31	8	11	5	0,070	210621
210497	Cutting Wheel	28,70	4,80	5,95	1	0,005	210496
210487 - 210489 - 210497	Deburring Spare Blade	-	-	-	5	0,200	221265

2114 : Plastic pipe cutter 35 - 40 - 63 mm

Used for quickly cutting PVC, PP, PE, PER, ABS and HDPE pipes. Ref. 211464: also for multilayer pipes.

Effort-reducing rack system.

Locking catch.

Ref. 211440: non-slip sheathed handle for a better grip.







A mm	A " OD	L mm	H mm	Kg	Ref.
35	1.3/8	198	72	0,260	211435
40	1.1/2	250	135	0,355	211440
63	2.1/2	428	133	1,110	211464



Customer Service

For information on our products, promotions, stocks, record your orders or follow a delivery? From 8.00 am to 12.15 pm and from 1.45 pm to 5.30 pm, Monday to Friday (5 pm):

FRANCE

Phone: 03.26.59.56.78 Fax: 03.26.59.56.20 Email: client.fr@virax.com

EXPORT

Phone: +33 3.26.59.56.57 Fax: +33 3 26.59.56.70 Email: export@virax.com

Exploded views and manuals: www.virax.com, Documentation section.

2150 : PC 32 Plastic Tube Cutter up to 32 mm

Advantages

Accuracy: "V" shape blade to enable easy, perpendicular cutting and reduced imprint on the pipe.

Practical: automatic opening: a spring keeps the lower handle

open. The pipe cutter is always ready to cut.


Soft Touch® handle: non-slip grip for firm control.

Materials cut: PVC, PE, PER, PEX, flexible plastic pipes (Tricoclair®), sprinkler hoses, irrigation hoses, multilayer.

Locking catch: keeps the lower handle closed: easy storage. No risk of injury. Ergonomy: the lower handle's special shape is suitable for all hand sizes.







A mm	A " OD	L mm	H mm	Kg	Ref.
32	1.1/4"	198	90	0,195	215032

2150 : Display Box of PC 32 Pipe Cutters

Display containing 12 pipe cutters (215032).

Kg	Ref.
2,870	215035





Benefit of VIRAX Soft Touch®



In addition to visually emphasize the hand's position on the tool, the Soft Touch® coating provides you with the best grip. On tools such as the PC42, it makes the tool easier to hold in the palm of your hand, and prevents cutting fatigue. On the ZR35, it enables to increase the torque applied to the slide, reducing fatigue and providing more accuracy when used. Pre-qualification and endurance tests have been carried out to determine the best combination between nuance hardness - grain for the Soft Touch®.

2150 : PC 42 Plastic Tube Cutter up to 42 mm

Advantages

Patented ratchet mechanism:

Quick cutting with little cutting effort, no return of the blade during cutting.

Accurate:

The V-shaped blade enables easy, perpendicular cutting.

Integral chamfering tool:

For PVC tubes before pasting.

Material cut: PVC, PP, PE, PER, PEX, ABS, PEHD, CPVC, PPR, PB, multilayer.

Practical: quick, tool-free blade change.

Soft Touch ® handle: non-slip for perfect control.

The shape of the upper arm perfectly guides the blade during cutting. Integral wire-cutter: max \emptyset : 12 mm, max cross section: 4 x 2.5 mm².

Chamfer angle: 15°.







A mm	A " OD	L mm	H mm	Kg	Ref.
42	1.5/8	238	113	0,530	215042

2150 : Display Box of PC 42 Plastic Tube Cutters

Displays containing 6 tube cutters (215042).

	Kg	Ref.
Γ	3,820	215060





2114 - 2140 : Blade - Plastic-composite Tube Cutter



Description	For pipe cutter	Packaging	Kg	Ref.
Blade and rack	211435	1	0,050	211404
Blade and rack	211442	1	0,075	211402
Blade	211463	1	0,200	211403
Blade and rack and springs	211464	1	0,370	211406
Blade	215042	1	0,100	214041
Blade and rack	211426	1	0,070	211401
Blade	211440	1	0,060	211405

GUILLOTINE PIPE CUTTER

2115 : Guillotine Pipe Cutter

Advantages

Practical: Fast opening.

Heavy-duty: Quadruple ground stainless steel blade. Blade holder: Holds the blade perpendicular to the pipe

centerline.

Max thickness: 18 mm.

Material cut: PEHD.

Square drive 14 mm (models 1 and 2) or 17 mm (model 3) across flats. A wrench or extension can be used for cutting pipes in deep trenches.

Releasing the catch on the hinged lower V-shaped jaw allows the cutter to be positioned

anywhere along the pipe. Stainless steel blade.



Model	Ø ext. tube "	Pipe O.D. mm	SDR	Max. thickness mm	C mm	Kg	Ref.
1	4	125	11	11,4	125	7,470	211512
2	8	225	11,5	18	225	17,000	211522
3	12	315	17	18	323,8	34,000	211532

2115 : Blade - Guillotine Pipe Cutter

Stainless steel blade.

For pipe cutter	Packaging	Kg	Ref.
211512	1	0,290	211501
211522	1	0,720	211502
211532	1	2,090	211503





Customer Service

For information on our products, promotions, stocks, record your orders or follow a delivery? From 8.00 am to 12.15 pm and from 1.45 pm to 5.30 pm, Monday to Friday (5 pm):

FRANCE

Phone: 03.26.59.56.78 Fax: 03.26.59.56.20 Email: client.fr@virax.com

EXPORT

Phone: +33 3.26.59.56.57 Fax: +33 3 26.59.56.70 Email: export@virax.com

Exploded views and manuals: www.virax.com, Documentation section.

SHEATH-CUTTER

2116 : Corrugated Conduit Cutter Ø 45 mm

Advantages

Cuts corrugated conduits without damaging the pipe inside the sheath, and without risk for the user.

No risk of injury, as blades are in the middle of guides.

Ensures a straight, clean cut.

Very compact cutter, for use in confined spaces.

Cuts PE protective pipe sheaths and most electric cable sheaths up to \varnothing 45 mm.

Cuts the corugation at the top of the grove leaving the pipe inside the sheath intact and free from scratches.

Ultra-resistant body and blade guides.

Very strong, removable, interchangeable stainless steel blades.

2 models / 2 colours to suit all available corrugated conduits on the market.

Cut quickly. 1/2 turn is enough.







For corrugations	L mm	H mm	Kg	Ref.
At 2,7 mm centres	85	53	0,290	211627
At 4 mm centres	85	53	0,290	211640

2116: Blade - Corrugated Conduit Cutter

	For Corrugated Conduit	Packaging	Kg	Ref.
Ī	211627 - 211640	2	0,008	752653





Virax Experts

Would you like technical assistance?

Our team of experts is at your disposal to provide you with tips and recommendations on how to get the most out of your Virax products.

From 8.00 am to 12.15 pm and from 1.45 pm to 5.00 pm, Monday to Friday (4.30 pm): +33 (0) 3.26.59.56.82

Exploded views and manuals: www.virax.com, Documentation section.

HOLE SAW

2209: Hole Saw Set

Advantages

Virax bi-metal hole saws, with their varying tooth height and gullet size guarantee:

A fast, regular cut. Low vibration during cutting. Easy removal of the blank. Increased durability. Low pressing force.

For drilling holes in gas pipes to form T-flanges or in partitions made of wood, plasterboard or similar materials for the passage of mild steel, semi-hard steel, stainless steel, lightweight alloy or plastic pipes.







Description	Ø mm	Supplied with	Kg	Ref.
Complete kit - 12-piece hole saw set	16-19-22-25-29-32-35-38-44-51-64-76	2 arbors with Ø 6 mm.pilot drill, 3 spare pilot drills	1,910	220906
Plumbers and electricians kit - 9-piece hole saw set	19-22-29-35-38-44-51-57-64	2 arbors with Ø 6 mm pilot drill, 1 adaptor, 1 spare pilot drill	1,590	220907
Basic kit - 5-piece hole saw set	22-25-29-32-39	1 arbor with Ø 6 mm pilot drill, 1 adaptor	0,590	220908



2209: Individual Hole Saws

Advantages

Virax bi-metal hole saws, with their varying tooth height and gullet size guarantee:

A fast, regular cut. Low vibration during cutting. Easy removal of the blank. Increased durability. Low pressing force.

For accurate drilling of various materials and in particular gas pipes to form welded connections. - HSS bi-metal saw. - HSS teeth of varying height and gullet size.







Ø mm	ø"	H mm	Kg	Ref.
15,9	5/8	50	0,025	220910
17,4	11/16	50	0,030	220911
19	3/4	50	0,030	220912
22,2	7/8	50	0,045	220914
25,4	1	50	0,060	220916
27	1.1/16	50	0,070	220917
28,6	1.1/8	50	0,080	220918
31,7	1.1/4	45	0,085	220920
33,3	1.5/16	45	0,090	220921
34,9	1.3/8	45	0,090	220922
38,1	1.1/2	45	0,090	220924
41,3	1.5/8	45	0,100	220926
44,4	1.3/4	45	0,085	220928
47,6	1.7/8	45	0,130	220930

Ø mm	ø"	H mm	Kg	Ref.
50,8	2	45	0,140	220932
54	2.1/8	45	0,120	220934
57,1	2.1/4	45	0,130	220936
60,3	2.3/8	45	0,135	220938
63,5	2.1/2	45	0,210	220940
66,7	2.5/8	45	0,160	220942
76,2	3	45	0,205	220948
82,6	3.1/4	45	0,195	220952
88,9	3.1/2	45	0,365	220956
101,6	4	45	0,285	220964
104,8	4.1/8	45	0,500	220966
114,3	4.1/2	45	0,540	220972
127	5	45	0,650	220980

2209: Accessories for Hole Saws

Description	Kg	Ref.
Arbor and pilot drill for saws Ø 14 a 130 mm	0,065	220900
Arbor and pilot drill for saws Ø 32 a 152 mm	0,220	220901
Pilot drill	0,020	220903









Virax is on Twitter!

@ViraxOfficial

SCREW-PUNCH

2211: Knockout Punch

For cutting stainless steel sinks or mild steel plates 2 mm thick. Special 4-tooth design prevents the blank from sticking.

It is important to grease the screw and the back of the head.



Ø mm	Electrical conduit no.	Screw hole	Kg	Ref.
22,50	16	10	0,150	221123
28,30	21	10	0,220	221128
31,75	-	10	0,260	221132
35	-	12	0,310	221135
37	29	12	0,330	221137

REAMER

2212 : Ratchet Reamer

For steel pipe \emptyset 1/8" to 2".

Ratchet handle with 18 mm square drive. 5 hardened forged steel cutting blades.

Kg	Ref.
2,250	221220



2212: Standard Reamer

For copper, HDPE and PVC pipes.

Reamer with non-replaceable blade. For deburring the inside of copper or other pipes, sheet metal edges, etc. Pocket clip.

Packaging	Kg	Ref.
2	0,064	221242



2212 : Internal-External Reamer

For HDPE pipes: **reaming** inner / outer Ø 6 to 40 mm.

For copper pipes: reaming inner Ø 6 to 42 mm - reaming outer Ø 6 to 40 mm.

Impact and cold resistant polypropylene housing.

Packaging	Kg	Ref.
1	0,115	221250





2212 : Multi-Material Internal/External Reamer

Advantages

Reaming of all types of tubes (copper, stainless steel, aluminium, steel, hard plastics, multi-layer).

Internal and external reaming of the tube.

Precise reaming (due to its large number of small steel blades).

Ergonomic (easy handling, aluminium finish).

For copper, stainless steel, aluminium, steel, hard plastics and multi-layer tubes: Ø 8 to 35 mm/ 5/16" to 1.3/8" for 221251, Ø 10 to 56 mm/ 1/2" to 2" for 221252.







A mm	A " OD	L mm	H mm	Kg	Ref.
8 - 35	5/16 - 1.3/8	48	60	0,210	221251
12 - 54	1/2 - 2	70	85	0,450	221252

2212 : Pencil Reamer with Interchangeable Blade

Advantages

Possibility of changing the blade when it is worn. Receptacle to store the spare blades. Choice of blade according to the tube type.

For internal reaming of copper, PVC, PEHD and stainless steel tubes. Supplied with 3 blades copper, PVC and PEHD.



Description	Kg	Ref.
Pencil reamer with 3 blades for Cu, PVC and PEHD	0,500	221261
Pack of 5 blades for Cu, PVC and PEHD (black color)	0,200	221265
Pack of 5 blades for stainless steel (golden color)	0,200	221266





Discover our YouTube channel

and its product demonstration videos! /VIRAX

CALIBRATION TOOL

2212: Calibration Tool 16-63 mm

Advantages



5 models to calibrate a maximum of tube makes. **Dual function**: calibration and interior reamer.

Several diameters per product to calibrate the most frequently used dimensions.

Two vital functions to crimp multi-layer tubes.

- 1- Recalibrate the tube after cutting operations.
- 2- Ream the inside of the tube to avoid damaging the connector's o-ring.

Strong product, burnished steel body, hardness 95 HrB.

Practical plastic handle.

221280 - 221281 (Ø 40 - 50 - 63 mm): ease of use and speed thanks to an integrated ratchet.

Ext. Ø x Thickness mm	Kg	Ref.
16x2 - 20x2 - 25x2.5 - 26x3 - 32x3	0,260	221276
16x2 - 20x2.5 - 25x2.5 - 26x3 - 32x3	0,260	221277
16x2.25 - 20x2.5 - 25x2.5 - 26x3 - 32x3	0,260	221278
40X3,5 - 50X4 - 63X4,5	0,450	221280
40X4 - 50X4,5 - 63X6	0,450	221281







CHAMFERING TOOL

2215: Chamfering Tool For Plastic Pipes

Recommended by plastic pipe manufacturers.

Releasable grips.

Capacity: Ø 32 to 250 mm pipe. Thickness: up to 12 mm. Chamfering angle: 15° on plastic pipes. Pivoting counter-blade adjustment.

Kg	Ref.
0,785	221500






2215: Blade and Counter-Blade

For	Packaging	Kg	Ref.
221500	1	0,026	221501







Tools for manual cutting and reaming of plastic tubes and pipes up to \emptyset 315 mm.



MAKE THE MOST OF YOUR TALENT AS PER ANTHONY


VIRAX is the benchmark brand in the trade:
Quality, French,

Top-of-the-range.

WITAX

Gold medallist from Worldskills

■ BENDING



BENDING

MANUAL HYDRAULIC BENDER

2402 : Manual Hydraulic Bender

Advantages

Bending capacity:

Gas pipes: Ø 3/8" to 4" (nfa 49115-en10255).

Locksmith's pipes: Ø 12 à 45 mm. Multilayer pipes: Ø 40 to 63 mm.

Angle: 0 to 90°.

For medium and heavy series gas pipes.

Manual hydraulic bender for worksites or prefabrication. Simple action circuit with spring-loaded piston return. Supplied in a wooden case with the forms and accessories. To identify the different types of cheeks, see next pages.

- Use Virax hydraulic ram oil for best protection.
- All necessary precautions must be taken when filling the ram to avoid foreign matter entering the reservoir as this may impair operation.
- Use horizontally.

Ref. 240233 / 240242 / 240243 / 240249 : Supplied in a wooden chest.

Ref. 240252: Supplied in two wooden chests.







For pipe	Formers	Ram	Туре	Kg	Ref.
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4	Manual - n°1	Sliding cheek	44,500	240233
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	Manual - n°2	Open cheek	77,000	240242
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	Manual - n°2	Sliding cheek	71,00	240243
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2 - 2.1/2 - 3"	Manual - n°3	Hinged cheek	170,000	240252
Multiplayer	40 - 50 - 63 mm	Manual - n°2	Sliding cheek	54,000	240249

2402: Manual Hydraulic Bender for Locksmith's Pipe

For locksmith's pipes and electrical conduit. (Supplied without formers)

Capacity mm	Ram	Туре	Kg	Ref.
Ø 12 to 45	Manual - no.2	Sliding Cheeks	58,000	240279



Safety, one of the top concerns of Virax

Safety throughout the site is at the heart of Virax's concerns:

Emergency situations, incidents and accidents are avoided through a prevention process. The target is zero accident.

Mitigate, and whenever possible eliminate, nuisances and risks in terms of occupational health and safety for all staff and interveners.

Focus on safety equipment.

POWERED HYDRAULIC BENDER

2408: Powered Hydraulic Bender

Advantages

Bending capacity:

Gas pipes: Ø 3/8" to 4" (nfa 49115 - en 10255).

Locksmith's pipes: Ø 12 à 45 mm.

Bending angle: 0° to 90°.

For medium and heavy series gas pipes.

Electrical hydraulic bender for worksites or prefabrication.

Simple action circuit with spring-loaded piston return.

Supplied in a wooden case with the forms and accessories.

Less effort required for large batches.

Limit switch (option - ref. 240811) to reproduce identical bends.

To identify the different types of cheeks, see next pages.

Tip:

- Use Virax hydraulic ram oil for best protection.
- All necessary precautions must be taken when filling the ram to avoid foreign matter entering the reservoir as this may impair operation.
- Use horizontally.

Ref. 240851, Ref. 240852 delivered in two wooden chests







For pipe	Formers	Ram	Туре	Kg	Ref.
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	230 V - n° 2	Open Cheeks	93,000	240842
Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	230 V - n° 2	Sliding Cheeks	87,000	240843
Steel	□3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2 - 2.1/2 - 3"	□230 V - n° 3	Hinged Cheeks	□188,0 00	240852
Steel	□3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2 - 2.1/2 - 3 - 3.1/2 - 4"	□230 V - n° 3	Hinged Cheeks	□303,0 00	240851

2408: Limit Switch

 $230\ V$ single phase limit switch for electric ram 2. This device allows the same bend to be reproduced repeatedly on electric powered benders.

For ram	Kg	Ref.
no.2	0,710	240811





ACCESSORIES FOR HYDRAULIC BENDER

2402 - 2408 : Hydraulic Ram Oil

Highly refined mineral oil, essential for the proper operation of Virax hydraulic benders (ref. 2402/2408). Very high lubrication, prevents oxidation, corrosion and wear. Density at 20°C: 0.87 to 0.89. Viscosity at 40°C: 22 mm2/s. Flow point: - 42°C.

Description	Kg	Ref.
1-litre container	0,910	240101
Box of 12 containers of 1 L	11,600	240102



BENDING

2402 - 2408 : Tripod

Range of tripods adaptable on Virax benders to avoid stooping, as well as for forming bends at the ends of pipes or working in confined spaces.

Cheek	For ram	Kg	Ref.
Open	Manual and electric no.1 and 2	5,500	240103
Sliding	Manual and electric no.2	9,350	240105
Hinged 3"	Manual no.3 e eléctrico no.3	11,700	240106
Open	Electrical no.2	10,000	240107



2402 - 2408 : Open Cheeks

For medium and heavy series gas pipes.



Description	Ø"	For ram	Kg	Ref.
Open cheek	3/8 - 1.1/2	n°1	10,750	240210
Dolly OC (x1)	3/8 - 1.1/2	n°1	1,830	240110
Open cheek	3/8 - 2	n°2	20,200	240216
Dolly OC (x1)	3/8 - 2	n°2	2,225	240114

2402 - 2408 : Sliding Cheeks

For medium and heavy series gas pipes.



Description	ø"	For ram	Kg	Ref.
Sliding cheeks	3/8 - 1.1/4	n°1	7,200	240211
Dolly SC (x1)	3/8 - 1.1/4	n°1	1,730	240111
Sliding cheeks	3/8 - 2	n°2	15,120	240217
Dolly SC (x1)	3/8 - 2	n°2	2,200	240115



Virax encourages WorldSkills France

As an official supplier of the national finals of Plumbing, Heating and Metallic Roofing professionals, our objective is to support apprenticeship and professional training of young adults before the age of 23. Apprentices are able to express all their talent and invest in their future while promoting their trade.

2402 - 2408 : Cheeks 2.1/2"

For medium and heavy series gas pipes.



Description	ø"	For ram	Kg	Ref.
Upper cheek	3/8 - 2.1/2	n°2	20,000	240221
Lower cheek	3/8 - 2.1/2	n°2	24,000	240220
Dolly (x1)	3/8 - 2.1/2	n°2	1,410	240116

2402 - 2408 : Hinged cheek 3"

For medium and heavy series gas pipes.



Description	ø"	For ram	Kg	Ref.
Hinged cheek	3/8 - 3	n°3	33,000	240228
Dolly for hinged cheek (x1)	3/8 - 3	n°3	3,970	240120

2402 - 2408 : Cheeks 4"

For medium and heavy series gas pipes.



Description	ø"	For ram	Kg	Ref.
Upper cheek	2.1/2 - 4	n°2 - n°3*	30,000	240223
Lower cheek	2.1/2 - 4	n°2 - n°3*	37,000	240222
Dolly for 2.1/2 to 4" hinged cheek (x1)	2.1/2 - 4	n°2 - n°3*	4,560	240117

www.virax.com

Simple, quick and easy to use. Browse and download our online catalogue, Discover the new products, Find a point of sale, Subscribe to our newsletter, Ask for an appointment, In just a few clicks!

^{*} Requires adaptor (Ref. 240206+240207+20408).

3 BENDING

2402-2408 : Sliding Cheeks - Locksmith's Conduit

For Locksmith's conduit.



Description	Ø mm	For ram	Kg	Ref.
Dolly SC (x1)	12-50	n°2	2,000	240119
Sliding cheeks	12-50	n°2	17,000	240226

2402 - 2408 : Former for Gas Pipes Medium and Heavy Series (nfa49-115)



Pipe "	Pipe mm	Radius mm	Kg	Ref.
3/8	12/17	40	0,845	240141
1/2	15/21	50	0,875	240142
3/4	20/27	65	1,190	240143
1	26/34	100	1,950	240144
1.1/4	33/42	135	3,300	240145
1.1/2	40/49	160	4,650	240146
2	50/60	210	7,050	240147

Pipe "	Pipe mm	Radius mm	Kg	Ref.
2.1/2*	66/76	350	19,480	240148
3*	80/90	400	27,900	240149
2.1/2**	66,76	350	22,000	240122
3***	80/90	420	30,200	240123
3.1/2***	90/102	mini 1800	9,025	240124
4***	102/114	mini 2000	9,320	240125

2402 - 2408 : Former for Light Series Pipes



Pipe "	Pipe mm	Radius mm	Kg	Ref.
3/8	12/17	70	0,920	240151
1/2	15/21	85	1,000	240152
3/4	20/27	110	1,375	240153
1	26/34	135	2,160	240154
1.1/4	33/42	170	3,510	240155
1.1/2	40/49	200	4,790	240156

 $^{^{\}ast}$ with hinged cheek (240228) .

^{**} with 2 1/2 to 4" cheeks (240222 - 240223) or 2 1/2" cheek (240220 - 240221).

^{***} only with 2 1/2" to 4" cheeks (240222 - 240223).

2402 - 2408 : Former for Locksmith's Pipes



Pipe O.D. mm	Bending radius	Kg	Ref.
12	50	0,850	240160
13	50	0,830	240161
14	60	0,900	240162
15	60	0,860	240163
16	70	0,920	240164
18	70	0,890	240165
20	105	0,900	240166
22	130	1,335	240167

Pipe O.D. mm	Bending radius	Kg	Ref.
25	130	1,330	240168
28	160	1,640	240169
30	165	2,000	240170
32	165	2,030	240171
35	220	4,220	240172
38	220	3,700	240173
40	220	3,300	240174
45	275	5,700	240175

2402 - 2408 : Former for PEX/AL/PEX Pipe



Description	Pipe O.D. mm	Bending radius	Kg	Ref.
Former	40	160	0,980	240177
Former	50	200	1,170	240178
Former	63	252	1,590	240179
Pair of dollies SC (HR)	-	-	2,500	240185

2402 - 2408 : Bending 2.1/2-4" Option for Ram No. 2

For medium and heavy series gas pipes (nfa 49115 - en 10255). Upper and lower cheeks. Dollies. 2 1/2" and 3" formers. 3 1/2" and 4" section formers. Ram adaptor. Piston extension.

Description	Kg	Ref.
2.1/2 to 4"	178,000	240248



Virax supports future professionals

Virax helps teachers promote the industry to students. Every year, Virax and teachers create a competition to test the skills of future graduates in a fun way. The best students win prizes to help them get started in their new profession.

BENDING

2402: Manual Ram

Mechanical safety ensured by an end-of-travel stop and high pressure seals at the back of the piston, which remain effective even in the event of impact on the piston. Automatic piston return. Virax rams are individually tested and inspected.

Ram No.	Capacity	Kg	Ref.
1	1.1/4" (42,4 mm)	13,900	240201
2	2" (60,3 mm) or 4" with accessories	17,200	240202
3	3" (90 mm) or 4" with accessories	31,000	240203



2402: Accessories

Description	Kg	Ref.
Pump handle	0,810	240200

2408 : Electric Ram

Mechanical safety ensured by an end-of-travel stop and high pressure seals at the back of the piston, which remain effective even in the event of impact on the piston. Automatic piston return.

Virax rams are individually tested and inspected.



Ram No.	Voltage	Capacity	Kg	Ref.
2	230 V single phase	2" (60,3 mm) to 4" with accessories	29,000	240802
3	230 V single phase	3" (90 mm) to 4" with accessories	39,000	240803



Customer Service

For information on our products, promotions, stocks, record your orders or follow a delivery? From 8.00 am to 12.15 pm and from 1.45 pm to 5.30 pm, Monday to Friday (5 pm):

FRANCE

Phone: 03.26.59.56.78 Fax: 03.26.59.56.20 Email: client.fr@virax.com

EXPORT

Phone: +33 3.26.59.56.57 Fax: +33 3 26.59.56.70 Email: export@virax.com

Exploded views and manuals: www.virax.com, Documentation section.

CROSSBOW BENDER

2503: Crossbow Bender

Advantages

Optimum force / actuation ratio for easy and fast bending.

Powerful: bends stainless steel tubes p to Ø 15 mm.

Optimised high quality materials for **maximum strength**.

Perfect bending of annealed copper tubes, in compliance with the recommendations of the EN 1057 standard up to Ø 22 mm, multilayer pipes up to Ø 32 mm, stainless steel and zinc-platedtubes up to Ø 15 mm.

Optimizes the force to apply with respect to the number of grip presses for easy and fast bending.

Ideal for use in work sites or workshops.

To produce 90° elbows, crank shapes, bayonets, etc.

Lightweight and handy, only 1.3 kg (bare machine) for user comfort.

Body in high quality aluminium, mobile handle in treated drop-forged steel.

High strength steelrack and mechanism.

Adaptable use: 1 hand for fast bending on most diameters, 2 hands for high strengthon the most demanding materials and diameters.

Release lever for fast removal of the bending former.

Non-slip Soft Touch® handle for perfect control.

Time gain against soldering, lower costs of elbow procurement and storage, secured installations thanks to fewer assemblies.


New formers in high strength glass fibre charged plastic, guaranteeing ideal maintaining of the tube in the former.


Patented system for easy viewing of the dimension markings on the tube.

High strength glass fibre charged plastic cheeks and counter formers. Patented system facilitating elbow-in-elbow bending. Easy fitting / removal of bending formers and cheeks without tools.

Size: 350 x 60 x 65 mm.

Supplied in a plastic VIRABOX case.





Capacities

Annealed copper pipes: Ø 10 to 22 mm, Ø 3/8 to 7/8"

Multilayer pipes: Ø 14 to 32 mm. Stainless steel pipes: Ø 12 to 15 mm Zinc-plated pipes: Ø 12 to 15 mm Bending angle: up to 95°

Tips

Tip: For blow torch annealed copper pipe, only anneal the bent part to avoid weakening the tube at the counter-form. Do not anneal the tube at the counter-formers: risk of warping.







BENDING

2500 : Former for 2500 / 2503 Crossbow Bender

Formers in high strength glass fibre charged plastic, guaranteeing ideal maintaining of the tube in the former. For perfect bending of annealed copper tubes, in compliance with the recommendations of the EN 1057 standard, or multilayer tubes.

To facilitate bending: patented system for easy viewing of the dimension markings on the tube. Clear and visible marking of the diameter and bending radius directly on the formers.







Pipe O.D. mm	Ø ext. tube "	Bending radius mm	Kg	Ref.
10	3/8	40	0,063	250010
12	-	45	0,065	250012
14	-	50	0,087	250014
15	-	50	0,081	250015
16	5/8	54	0,082	250016
18	-	70	0,150	250018

Pipe O.D. mm	Ø ext. tube "	Bending radius mm	Kg	Ref.
20	-	80	0,167	250020
22	7/8	88	0,159	250022
26	-	95	0,128	250026
32	-	114	0,162	250032
-	1/2	45	0,062	250051
-	3/4	70	0,140	250053

2500 : Cheek and Counter Former for 2500 / 2503 Crossbow **Bender**

Cheeks with high strength glass fibre charged plastic counter formers. Patented system facilitating elbow-in-elbow bending: counter formers with 1 for regular bending and 1 special face dedicated to elbow-in-elbow.

Pipe O.D. "	Pipe O.D. mm	Kg	Ref.
3/8 - 1/2 - 5/8	10 - 16	0,470	250001
3/4 - 7/8	18 - 22	0,600	250002
-	26 - 32	0,700	250003





2501: Former for 2501 Crossbow Bender

High strength lightweight alloy formers.



Pipe O.D. mm	Ø ext. tube "	Bending radius mm	Kg	Ref.
10	-	30	0,090	250160
12	-	35	0,100	250161
14	-	40	0,120	250162
15	-	50	0,140	250159
16	-	50	0,140	250163
18	-	70	0,190	250164
20	-	80	0,200	250165
22	-	90	0,200	250166

Pipe O.D. mm	Ø ext. tube "	Bending radius mm	Kg	Ref.
24	-	90	0,200	250167
26	-	95	0,240	250168
-	3/8	30	0,080	250170
-	1/2	40	0,140	250171
-	5/8	50	0,150	250172
-	3/4	80	0,190	250173
-	7/8	90	0,210	250174

2501: Cheeks and Counter-Former for 2501 Crossbow Bender

Pipe O.D. "	Pipe O.D. mm	Kg	Ref.
3/8 - 1/2 - 5/8	10 - 16	0,500	250130
3/4 - 7/8	18 - 22	0,460	250131
-	26	0,380	250132



BENDING SPRING

2510 : Bending Spring - For Copper Pipe

Outside bending spring.

Hardened, burnished steel wire. End bending rings.

Wall thickness: 0,8 to 1,2 mm.

Ø mm	L mm	Kg	Ref.
10	240	0,170	251010
12	240	0,240	251012
14	255	0,280	251014
15	275	0,320	251015
16	285	0,350	251016
18	295	0,470	251018
20	325	0,580	251020
22	340	0,650	251022



2510 : Internal Bending Spring for PEX & Multilayers Pipes

These springs slip inside pipes (multi-layers, PEX) in order to bend pipes without folding or flattening them.

With 1100 mm length, these springs can be used easily and in every situations. Springs in pre-zinc steel.





L mm	Ø mm	For PEX-pipe Ø mm	For Multilayer-pipe Ø mm	Kg	Ref.
1100	9	12 x 1,1	12 x 1,1 - 14 x 2 - 16 x 2,7	0,280	251042
1100	11	16 x 1,5	16 x 2 - 16 x 2,2	0,370	251044
1100	13	-	18 x 2 - 20 x 2,8 - 20 x 3	0,460	251046
1100	15	20 x 1,9	20 x 1,9 - 20 x 2 - 20 x 2,25	0,560	251048
1100	17	-	25 x 3,5	0,650	251050
1100	19	25 x 2,3	25 x 2,5 - 26 x 3	0,780	251052



Virax, a French story

Nearly a century ago, in 1920, two Frenchmen established Virax by launching its famous "Virax threader", the threader that "Turns around the Axis". Nowadays, it is still from Epernay, at the heart of the Marne and Champagne country, that Virax manufactures and distributes its professional product ranges in more than 40 countries.

BENDING

BENDING PLIERS

2511: Bending Pliers

For hardened and annealed copper pipes: Ø 6 to 18 mm and Ø 1/4" to 5/8" O.D. / wall thickness 1 to 1.2 mm.

Bending radius: 2 to 3.5 D.

For forming very short radius bends and counter-bends.

Bending angle: up to 180°.

0 to 180° graduations.

Steel handle and body. Machined groove.





Pipe O.D.	Bending radius mm	Kg	Ref.
6	11	0,310	251106
8	14	0,355	251108
10	23	0,850	251110
12	30	1,000	251112
14	42	2,100	251114
15	42	2,100	251115
16	54	2,740	251116

Pipe O.D.	Bending radius mm	Kg	Ref.
18	55	3,000	251118
1/4	15	0,355	251121
5/16	25	0,500	251122
3/8	35	1,015	251123
1/2	45	2,100	251124
5/8	54	2,700	251125

2514: Bending pliers

For hardened and annealed copper pipes: Ø 8 to 16 mm / wall thickness: 1 to 1.2 mm. Bending radius: approx. 3.85 D.

Lightweight alloy body.

Rounded shape, can rest on the knee.

180° bending angle.

Handles designed for clamping in a parallel vice.

Pipe O.D. mm	Bending radius mm	Kg	Ref.
8	35	0,490	251408
10	40	0,925	251410
12	45	0,850	251412
14	50	1,340	251414
15	55	1,385	251415
16	60	1,730	251416







Much more than just quality, here's the Virax commitment!

Virax commits to total, permanent and durable satisfaction of users and therefore applies a process based on:

A proactive product plan.

A constant innovation process.

A focus on permanent improvement.

Improved customer services.

An assurance of optimum availability rate.

Customer satisfaction, the heart of our commitments.

ATTACHABLE MANUAL BENDER

2502: Workbench Manual Bender

Wall thickness: 0.8 to 1.5 mm. Bending angle: 0 to 180°.

Red Universal formers:

Ø 8 to 22 mm.

Grey Universal formers:

Ø 5/16 to 7/8 ".

Wall thickness: 1 to 1.5 mm. Bending angle: 0 to 180 $^{\circ}.$

Yellow Standard formers

Ø 10 to 22 mm. Short bending radius.

With Loose guide.

Provides a perfect finish as the guide follows the pipe round the bend. Essential for bending insulated pipes.

With Sliding guide

For quick bendings and vertical works.

With sliding guide

Supplied with an assembled body and a rapid feed lever.







Туре	Composition	Ø	Kg	Ref.
With loose guide	Universal formers	8 - 10 - 12 - 14 - 16 - 18 - 20 - 22 mm	18,600	250271
With loose guide	Universal formers	10 - 12 - 14 - 16 - 18 - 20 - 22 mm	18,400	250272
With loose guide	Universal formers	12 - 15 - 18 - 22 mm	15,000	250273
With loose guide	Standard formers	10 - 12 - 14 - 16 - 18 - 20 - 22 mm	12,500	250275
With loose guide	Universal formers	5/16 - 3/8 - 1/2 - 5/8 - 3/4 - 7/8"	15,030	250280
With sliding guide	Universal formers	10 - 12 - 14 - 16 - 18 - 20 - 22 mm	16,550	250282
With sliding guide	Universal formers	12 - 15 - 18 - 22 mm	14,500	250283
With sliding guide	Standard formers	10 - 12 - 14 - 16 - 18 - 20 - 22 mm	15,000	250285

Standard formers

2502: Workbench Manual Bender Accessories

Support Base for workbench-mounted bender: space-saving arrangement allowing bender to be used in both horizontal and vertical positions. Fits inside the bender's storage case.



12 - 15 - 18 - 22 mm






12,360

250286

Description	Pipe O.D.	Kg	Ref.
Assembly body	-	3,540	250200
Rapid speed lever	-	1,900	250201
Support Base	-	1,250	250203
Stitch barrel	-	0,045	250208
Assembly body + rapid feed lever	-	10,400	250270
Lever extension	-	0,810	240200
Loose Guide	8 - 10 - 20 - 22 mm	1,160	250210
Loose Guide	12 - 14 - 16 - 18 mm	1,180	250212

Description	Pipe O.D.	Kg	Ref.
Loose Guide	12 - 15 - 18 - 22 mm	0,935	250214
Loose Guide	5/16 - 3/8 - 7/8"	1,260	250216
Loose Guide	1/2 - 5/8 - 3/4"	1,120	250218
Sliding Guide + Pin	8 - 10 - 20 - 22 mm	0,290	250211
Sliding Guide + Pin	12 - 14 - 16 - 18 mm	0,290	250213
Sliding Guide + Pin	12 - 15 - 18 - 22 mm	0,270	250215
Sliding Guide + Pin	5/16 - 3/8 - 7/8"	0,280	250217
Sliding Guide + Pin	1/2 - 5/8 - 3/4"	0,290	250219



BENDING

2502 : Former





Description	Pipe O.D. "	Pipe O.D. mm	Bending radius mm	Kg	Ref.
Universal	-	8	30	0,275	250221
Universal	-	10	42	0,430	250222
Universal	-	12	50	0,545	250223
Universal	-	14	60	0,700	250224
Universal	-	15	71	0,830	250225
Universal	-	16	71	0,925	250226
Universal	-	18	80	1,135	250227
Universal	-	20	90	1,370	250228
Universal	-	22	100	1,500	250229
Standard	-	10	35	0,335	250232
Standard	-	12	42	0,420	250233
Standard	-	14	50	0,525	250234
Standard	-	15	60	0,700	250235
Standard	-	16	60	0,680	250236
Standard	-	18	70	0,915	250237
Standard	-	20	80	1,100	250238
Standard	-	22	90	1,270	250239
Universal	5/16	-	30	0,270	250241
Universal	3/8	-	42	0,420	250242
Universal	1/2	-	60	0,715	250243
Universal	5/8	-	70	0,850	250244
Universal	3/4	-	90	1,350	250245
Universal	7/8	-	100	1,490	250246



Virax and the environment

Virax is committed to environmental protection and sustainable development, as demonstrated by our ISO certification 14001: 2015 for our environmental management system.

Compliance with the REACH Directive no.1907/2006.

Low energy consumption.

Dematerialisation of documentary flows and printing control.

Waste control and reclaiming.

Packaging materials recycled in a partnership with Eco Emballage.

Anticipation of pollution risks.

PORTABLE ELECTRIC BENDING MACHINE

2518: Portable Battery-Powered Bender Eurostem® II

Advantages

For small and medium-sized series in the workshop or on site...

Self-contained:2 batteries (supplied) provide sufficient power for several hundred bends.

Accurate bends ensured by speed-reducer.

Handy mobile hook for easy pipe installation and removal.

Bending radius in accordance with European standard EN 1057. Bends up to 180 $^\circ$. **Motor drive**: - 14.4 V - 2,4 Ah Li-lon battery. - Bending speed: 0 to 4 rpm.

Ref. 251806: For PEX/AL/PEX pipes

Formers Ø	Counter former Ø	Kg	Ref.
12 - 14 - 16 - 18 - 22 mm	12/15 - 14/16 - 18/22 mm	16,400	251800
12 - 15 - 18 - 22 mm	12/15 - 18/22 mm	15,000	251805
16 - 20 - 26 - 32 mm	14/16 - 20 - 26 - 32 mm	15,000	251806
15 - 22 - 28 mm	12/15 - 18/22 - 28 mm	15,000	251845
15 - 18 - 22 mm	12/15 - 18/22 mm	14,000	251846
14 - 16 - 18 - 22 - 28 mm	14/16 - 18/22 - 28 mm	17,800	251854
1/2 - 5/8 - 3/4 - 7/8"	1/2 - 5/8 - 3/4 - 7/8"	14,000	251850







Capacities

Maximum capacity:

- Hard copper, locksmith and hydraulic pipes: Ø 10 to 28 mm, wall thickness 1 to 1.5 mm.
- Stainless steel: Ø 10 to 22 mm, wall thickness 1 mm, Ø 28 mm, wall thickness 1.2 mm.
- PEX/AI/PEX: Ø 14 à 32 mm.

Delivered with

- 2 Li-Ion batteries 14.4 V 2.4 Ah.
- 1 fast 45 min. charger.
- in a case.



Customer Service

For information on our products, promotions, stocks, record your orders or follow a delivery? From 8.00 am to 12.15 pm and from 1.45 pm to 5.30 pm, Monday to Friday (5 pm):

FRANCE

Phone: 03.26.59.56.78 Fax: 03.26.59.56.20 Email: client.fr@virax.com

EXPORT

Phone: +33 3.26.59.56.57 Fax: +33 3 26.59.56.70 Email: export@virax.com

Exploded views and manuals: www.virax.com, Documentation section.

BENDING

2518: Portable Power Bender Eurostem® II

Advantages

For small and medium-sized series in the workshop or on

Accurate bends ensured by speed-reducer.

Handy mobile hook for easy pipe installation and removal.

Bending radius in accordance with French standard EN 1057. Bends up to 180°. Motor drive: 230 V - 50/60 Hz - 550 W. - Bending speed: 0 to 3 rpm.

Ref. 251808: For PEX/AL/PEX pipes

Formers Ø	Counter former Ø	Kg	Ref.
12 - 14 - 16 - 18 - 22 mm	12/15 - 14/16 - 18/22 mm	14,170	251802
12 - 15 - 18 - 22 mm	12/15 - 18/22 mm	14,000	251807
16 - 20 - 26 - 32 mm	14/16 - 20 - 26 - 32 mm	15,000	251808
15 - 22 - 28 mm	12/15 - 18/22 - 28 mm	15,000	251847
15 - 18 - 22 mm	12/15 - 18/22 mm	14,000	251848
14 - 16 - 18 - 22 - 28 mm	14/16 - 18/22 - 28 mm	16,000	251856
1/2 - 5/8 - 3/4 - 7/8"	1/2 - 5/8 - 3/4 - 7/8"	14,000	251852





Capacities

Maximum capacity:

- Hard copper, locksmith and hydraulic pipes: Ø 10 to 28 mm, wall thickness 1 to 1.5 mm.
- Stainless steel: Ø 10 to 22 mm, wall thickness 1 mm, Ø 28 mm, wall thickness 1.2 mm.
- PEX/AI/PEX: Ø 14 à 32 mm.

Delivered with

- in a case.

2518: Former and Counter-Former for Eurostem® II

Ref. 251826/251831 : For PEX/AL/PEX pipes. Ref. 251829 : For stainless steel pipes Ø 28 x 1.2 mm.








Туре	Pipe O.D. mm	Pipe O.D. "	Bending radius	Kg	Ref.
Formers and counter-former	10	-	40	0,260	251810
Former	12	-	45	0,220	251812
Former	14	-	50	0,290	251814
Former	15	-	55	0,325	251815
Former	16	-	60	0,380	251816
Former	18	-	70	0,590	251818
Formers and counter-former	20	-	77	0,930	251820

Туре	Pipe O.D. mm	Pipe O.D. "	Bending radius	Kg	Ref.
Former	22	-	77	0,710	251822
Formers and counter-former	25	-	98	1,720	251825
Formers and counter-former	26	-	98	1,700	251826
Formers and counter-former	28	-	98	1,560	251828
Formers and counter-former	28	-	112	□1,820	251829
Formers and counter-former	32	-	□112	□1,620	251831
Formers and counter-former	-	3/8	40	0,270	251860
Former	-	1/2	45	0,240	251863
Former	-	5/8	55	0,320	251866
Former	-	3/4	70	0,600	251869
Formers and counter-former	-	1.1/8	98	1,600	251879
Former	-	7/8	77	0,690	251872
Counter-former	12/15	-	-	0,055	251832
Counter-former	14/16	-	-	0,065	251833
Counter-former	18/22	-	-	0,085	251834
Counter-former	-	1/2 - 5/8	-	0,050	251882
Counter-former	-	3/4 - 7/8	-	0,080	251883

2518: Concentric Radius Former for Eurostem® II

Former with special bending radius for parallel working on double collars.

Ø mm	Bending radius	Kg	Ref.
12	75	0,410	251835
14	80	0,580	251836
16	90	0,780	251837
18	105	0,960	251838
22	120	1,380	251839



2518: Accessories for Eurostem® II

Description	Kg	Ref.
Tripod	6,400	251809
Battery 14,4 V - 2,4 Ah Li-Ion	0,645	253244
230 V Charger - for 14,4 V battery - 2,4 Ah Li-lon	0,740	251844
Mains adaptor 230V - 14,4V	0,980	252938









Virax Experts

Would you like technical assistance?

Our team of experts is at your disposal to provide you with tips and recommendations on how to get the most out of your Virax products.

From 8.00 am to 12.15 pm and from 1.45 pm to 5.00 pm, Monday to Friday (4.30 pm): +33 (0) 3.26.59.56.82

Exploded views and manuals: www.virax.com, Documentation section.



	CUTTING OIL	84		FRIGOR - FLARING TOOL	99
	ADJUSTABLE MANUAL THREADER	85		FLARING PLIERS	100
o coc	MANUAL THREADER WITH INTERCHANGEABLE HEADS	86		EXPANSION PLIERS	101
	PORTABLE ELECTRIC THREADING MACHINE	88	3.111	T-FLANGE	102
	COMPLETE HEADS & DIES	90		TOOLS FOR LEAD TUBE	103
	THREADING MACHINE	92	NITE OF THE PROPERTY OF THE PR	SEALANT	104
	ACCESSORIES FOR 2" AND 4" THREADING MACHINE	94	ESSME	AXIAL CRIMPING	105
	GROOVER	97		RADIAL CRIMPING	107
	PERCUSSION FLANGING TOOL	98			

CUTTING OIL

1101 - 1102 - 1105 : Mineral Cutting Oil

Specially designed for manual and powered threading. With its very high lubricating ability, Virax cutting oil ensures better quality threads and lengthens the service life of both dies and machines.

Water emulsifiable. Odourless.

WARNING: It is essential to rinse off the oil with detergent when used on drinking water circuits.

L	Packaging	Kg	Ref.
1 L	Container	0,985	110101
5 L	Container	4,860	110105
1 L	Box of 12 containers	12,430	110112
500 ml	Spray can	0,620	110200
500 ml	Box of 12 spray cans	6,900	110202
5 L - Special Stainless steel	Container	4,600	110505







1106: Synthetic Threading Oil

Advantages

Special threading on drinking water circuits.

Odourless: For a better user comfort.

High technical performances: Threading couple and tools

durability are improved.

Acceptable for fresh water: specially done to thread drinkable water pipings, all the oil is eliminated by rinsing it out.

DVGW W 521 Certification Nr. DW-0201BR5779.

Dynamic viscosity at -10°C: < 250 mPa s.

Use it without diluting.

L	Packaging	Kg	Ref.
5 L	Container	5,720	110605





Virax, French manufacturer

In its Production Centre extending over more than 25,000 m² situated in Epernay, France, Virax manufactures tools and machines designed by its R&D Center to meet the requirements of professionals. Plasturgy, machining, milling, grinding, assembly and painting, all these activities are performed on site for manufacturing control and quality.

ADJUSTABLE MANUAL THREADER

1265 - 1275 : Adjustable Manual Threader

Forged, heat-treated steel, reversible without removal, for right and left-hand threads. Two removable tubular steel handles, can be screwed end to end.

Adjustable rear guides for centring the threader on the pipe.

Opening lever disengages the dies from the pipe when threading completed for trimming metal shavings and removing the threader from the pipe.



Description	Pipe O.D. "	Pipe O.D. mm	Dies	Kg	Ref.
Single ratchet 1" to 3"	1.1/2 - 2, 2.1/2 - 3	40/49 - 50/60, 66/76 - 80/90	Right BSPT	19,100	126500
Single ratchet 1" to 3"	1 - 1.1/4, 1.1/2 - 2, 2.1/2 - 3	26/34 - 33/42, 40/49 - 50/60, 66/76 - 80/90	Right BSPT	20,000	126520
Single ratchet 2.1/2" to 4"	2.1/2 - 3, 3.1/2 - 4	66/76 - 80/90, 90/102 - 102/114	Right BSPT	25,200	127500
Single ratchet housing only	1 - 3	-	-	18,600	126599
Single ratchet housing only	2.1/2 - 4	-	-	23,150	127599

1245 - 1265 - 1275 : Set of Dies



Description	Pipe O.D. "	Pipe O.D. mm	For adjustable threader	Kg	Ref.
Right BSPT	1/4 - 3/8	3/8 - 12/17	1240 - 1245	0,575	124501
Right BSPT	1/2 - 3/4	15/21 - 21/27	1240 - 1245	0,560	124502
Right BSPT	1 - 1.1/4	26/34 - 33/42	1240 - 1245	0,530	124503
Right BSPT	1.1/2 - 2	40/49 - 50/60	1240 - 1245	0,470	124504
Right BSPT	1 - 1.1/4	26/34 - 33/42	1265	0,980	126503
Right BSPT	1.1/2 - 2	40/49 - 50/60	1265	0,900	126504
Right BSPT	2.1/2 - 3	66/76 - 80/90	1265	0,810	126505
Left BSPT	1 - 1.1/4	26/34 - 33/42	1265	0,980	126513
Left BSPT	1.1/2 - 2	40/49 - 50/60	1265	0,910	126514
Right BSPT	2.1/2 - 3	66/76 - 80/90	1275	1,250	127505
Right BSPT	3.1/2 - 4	90/102 - 102/114	1275	1,990	127506



Virax has been certified ISO 9001 since 1997

And in 2016 our Quality Management System was acknowledged through certification in its new 2015 version.

MANUAL THREADER WITH INTERCHANGEABLE HEADS

1362 - 1363 : Threading Set 3/8" - 1 1/4" - Plastic case -Metal case

Advantages

Reversible ratchet for increased manœuvrability. Ergonomic grip.

Capacity:

Steel:

Right BSPT: Ø 1/8" to 1.1/4" Left BSPT: Ø 1/8" to 1.1/4" NPT: Ø 1/8" to 1.1/4" Stainless steel:

Right BSPT: Ø 3/8" to 1.1/4". Tubular steel handles.

Heads can also be used on Mini Phenix / Phenix III B portable electric threader. For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.

Description	Case	Kg	Ref.
Single ratchet housing + handle - BSPT right and left : 3/8 - 1/2 - 3/4 - 1 - 1.1/4	Metal - Double (670 x 140 x 150 mm)	12,200	136267
Single ratchet housing + handle right BSPT: 1/2 - 3/4 - 1 - 1.1/4	Metal - Single (670 x 115 x 150 mm)	7,650	136270
Single ratchet housing with 2 part handle - Right BSPT : 3/8 - 1/2 - 3/4 - 1 - 1.1/4	Plastic (429 x 240 x 125 mm)	6,060	136301
Single ratchet housing with 2 part handle - Right BSPT : 1/2 - 3/4 - 1 - 1.1/4	Plastic (429 x 240 x 125 mm)	5,615	136311
Single ratchet housing with 2 part handle - NPT : 3/8 - 1/2 - 3/4 - 1 - 1.1/4	Plastic (429 x 240 x 125 mm)	6,100	136361





Customer Service

For information on our products, promotions, stocks, record your orders or follow a delivery? From 8.00 am to 12.15 pm and from 1.45 pm to 5.30 pm, Monday to Friday (5 pm):

FRANCE

Phone: 03.26.59.56.78 Fax: 03.26.59.56.20 Email: client.fr@virax.com

EXPORT

Phone: +33 3.26.59.56.57 Fax: +33 3 26.59.56.70 Email: export@virax.com

Exploded views and manuals: www.virax.com, Documentation section.

1362 - 1364 : Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case

Advantages

Reversible ratchet for increased manœuvrability. Ergonomic grip. Easy head installation and removal.

Capacity:


Steel

Right BSPT: Ø 1/8" to 2" Left BSPT: Ø 1/8" to 2" NPT: Ø 1/8" to 2". Stainless steel

Right BSPT: Ø 3/8" to 1.1/4".

Tubular steel handles.

Heads can also be used on Mini Phenix / Phenix III portable electric threading machine. For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.









1362 - 1363 - 1364 : Ratchet Housing for Manual Threader with Interchangeable Heads

Description	Capacity "	Kg	Ref.
1 ratchet 1 housing	1/8 - 1.1/4	1,130	136294
1 handle + 1 ratchet 1 housing	1/8 - 1.1/4	1,990	136290
2-part handle + 1 ratchet 1 housing	1/8 - 1.1/4	2,050	136295
1 handle + 2 ratchets 1 housing	1/8 - 1.1/4	2,100	136292
3-part handle + 1 ratchet 1 housing	1.1/2 - 2	2,565	136495
1 ratchet 1 housing	1.1/2 - 2	1,130	136494
2-part handle + 1 ratchet 1 housing	1.1/2 - 2	2,480	136490
2-part handle + 2 ratchets 1 housing	1/8 - 1.1/4	2,260	136095





PORTABLE ELECTRIC THREADING MACHINE

1380 : Phenix Mini Portable Electric Threading **Machine**

Advantages

Compact, ideal for interventions in confined environment. Locking vice with anti-torque bar to lock the machine in rotation when threading.

Robust and light, suited to all maintenance work.

Dual rotation direction.

Easy to use, selector to choose rotation direction and trigger to control rotation speed according to pressure applied.

In spite of its small size, this threading machine can thread right- or left-hand BSPT, from 1/8" to 1.1/4".

Feather weight for easy transport and use.

Rotation speed: 20 rpm in both directions.

For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.







Description	Voltage V	Power	Kg	Ref.
Mini Phenix + 4 Right-hand BSPT heads: 1/2" - 3/4" - 1" - 1.1/4"	230	800W - 50/60 Hz	11,000	138021

Capacities

Steel:

Right-hand BSPT Ø 1/8" to 1.1/4" Left-hand BSPT Ø 1/8" to 1.1/4"

Delivered with

- 1 locking vice (ref. 138022).
- 4 Right-hand BSPT heads: 1/2" 3/4" 1" 1.1/4".

Tips

Virax cutting oil (ref. 110200) should be used for smooth die operation, ensuring a good cut and a perfect thread. For NPT or steel threading, use the Phenix III portable automatic threading machine ref. 137562.



Virax, French manufacturing

Located in Epernay, the Capital of the Champagne region, the Virax company was formed about a century ago with the famous "Virax threader" that « Turns around the Axis ». The production centre now extends over more than 25 000 sqm.

1375: Phenix III Portable Electric Threader

Advantages

For effortless threading up to 2" in all situations.

Holding vice with anti-torque bar to steady the machine during threading operations.

Ideal for working in confined spaces (close to walls, etc.).

Bidirectional rotation.

Mechanical reverse control ensuring longer motor life.

Adaptor for octagonal heads 1/8 " to 1 1/4 " with unique locking system for securely holding the head during difficult operations.

Rotation speed: 26 rpm in both directions.

For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.







Description	Voltage V	Power	Kg	Ref.
Phenix III + 4 Right heads BSPT: 1/2" - 3/4" - 1" - 1.1/4"	230	1100W - 50/60 Hz	18,800	137562
Phenix III + 6 Right heads BSPT: 1/2" - 3/4" - 1" - 1.1/4" - 1.1/2" - 2"	230	1100W - 50/60 Hz	22,800	137563

Capacities

Steel:

Right BSPT Ø 1/8 to 2" Left BSPT Ø 1/8 to 2" NPT: Ø 1/8 to 2"

Stainless steel:

Right BSPT: Ø 1/8 to 2".

Delivered with

- 1 holding vice (ref. 137552)
- 1 adaptor for octagonal heads 1/8" to 1 1/4" (ref. 137553).

Tins

Virax cutting oil (ref. 110200) should be used for smooth die operation, ensuring a good cut and a perfect thread.



Virax committed to WEEE management

As a producer, Virax has implemented a process for collecting Waste from Electrical and Electronic Equipment (WEEE) in compliance with the European Directive 2012/19/UE. In compliance with its environmental commitment, Virax organizes the management and recycling of WEEE at end of life.

1375 - 1380 : Accessories - Portable Electric Threader

Holding vice: safety pipe-threading accessory. Anti-torque bar steadies the machine while

Phenix III: vice jaws can be adapted for threading stainless steel pipes (137507).

Description	For	Kg	Ref.
Threader only - 230 V	Phenix III	7,500	137550
Holding vice	Phenix III	3,000	137552
Reducer for octagonal heads 1/8" to 1.1/4"	Phenix III	1,400	137553
Vice jaw inserts for stainless steel pipes (for mounting on blocking vice)	Phenix III	0,200	137507
Threader only - 230 V	Mini Phenix	5,800	138020
Holding vice	Mini Phenix	1,500	138022







COMPLETE HEADS & DIES

1362 - 1364 - 1370 : Drop Head Threaders

Advantages

Lubrification and chip removal assisted by large openings. Die position markings remain perfectly visible at all times. Guide hole for self-centring of die-head.

Heads with notched octagonal (or splined) drive for securing within the housing. Cap for accurate positioning of dies. Also allows them to be turned around to cut threads tight up against walls without risking to be pulled out. Long-reach centring guide for easy operation.

Compatible with manual interchangeable head threader, Mini Phenix and Phenix III, according to capacity.

To be threaded with the Mini Phenix ref. 138020 /138021, use only steel BSPT heads up to

For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.

* Retaining pin must be removed when used with the Phenix IIB / Phenix III threading machines (ref 1375).







Туре	Type of thread	Ø"	Ø mm	Kg	Ref.
Steel	Right hand BSPT	1/8	6/10	0,445	136231
Steel	Right hand BSPT	1/4	8/13	0,460	136232
Steel	Right hand BSPT	3/8	12/17	0,445	136341
Steel	Right hand BSPT	1/2	15/21	0,520	136342
Steel	Right hand BSPT	3/4	20/27	0,570	136343
Steel	Right hand BSPT	1	26/34	0,720	136236
Steel	Right hand BSPT	1.1/4	33/42	0,720	136345
Steel	Right hand BSPT	1.1/2*	40/49	2,000	136438
Steel	Right hand BSPT	2*	50/60	2,150	136439
Steel	Left hand BSPT	1/8	6/10	0,460	136241

Туре	Type of thread	ø"	Ø mm	Kg	Ref.
Steel	Left hand BSPT	1/4	8/13	0,460	136242
Steel	Left hand BSPT	3/8	12/17	0,440	136243
Steel	Left hand BSPT	1/2	15/21	0,510	136244
Steel	Left hand BSPT	3/4	20/27	0,575	136245
Steel	Left hand BSPT	1	26/34	0,720	136246
Steel	Left hand BSPT	1.1/4	33/42	0,725	136247
Steel	Left hand BSPT	1.1/2*	40/49	1,980	136448
Steel	Left hand BSPT	2*	50/60	2,150	136449
Steel	NPT	1/8	6/10	0,460	136251
Steel	NPT	1/4	8/13	0,450	136252
Steel	NPT	3/8	12/17	0,430	136253
Steel	NPT	1/2	15/21	0,520	136254
Steel	NPT	3/4	20/27	0,570	136255
Steel	NPT	1	26/34	0,720	136256
Steel	NPT	1.1/4	33/42	0,730	136257
Steel	NPT	1.1/2*	40/49	2,000	136458
Steel	NPT	2*	50/60	2,160	136459
Stainless steel	Right hand BSPT	3/8	12/17	0,460	137043
Stainless steel	Right hand BSPT	1/2	15/21	0,532	137044
Stainless steel	Right hand BSPT	3/4	20/27	0,596	137045
Stainless steel	Right hand BSPT	1	26/34	0,720	137046
Stainless steel	Right hand BSPT	1.1/4	33/42	0,730	137047

1362 - 1364 - 1370 : Set of Dies

Advantages

Precision machined from a special alloy steel guaranteeing a high cutting performance, excellent resilience and hardness. **Cutting profile** with a clearance angle to reduce friction.

Compatible with manual interchangeable head threader, Mini Phenix and Phenix III, according to capacity.

For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.



Virax cutting oil must be used for lubrication in all threading operations.

Туре	Type of thread	ø"	Ø mm	Kg	Ref.
Steel	Right hand BSPT	1/8	6/10	0,060	136201
Steel	Right hand BSPT	1/4	8/13	0,055	136202
Steel	Right hand BSPT	3/8	12/17	0,055	136203
Steel	Right hand BSPT	1/2	15/21	0,060	136204
Steel	Right hand BSPT	3/4	20/27	0,070	136205
Steel	Right hand BSPT	1	26/34	0,115	136206
Steel	Right hand BSPT	1.1/4	33/42	0,115	136207
Steel	Right hand BSPT	1.1/2 - 2	40/49 - 50/60	0,150	136408
Steel	Left hand BSPT	1/8	6/10	0,060	136211
Steel	Left hand BSPT	1/4	8/13	0,055	136212
Steel	Left hand BSPT	3/8	12/17	0,055	136213
Steel	Left hand BSPT	1/2	15/21	0,055	136214

Туре	Type of thread	Ø"	Ø mm	Kg	Ref.
Steel	Left hand BSPT	3/4	20/27	0,070	136215
Steel	Left hand BSPT	1	26/34	0,115	136216
Steel	Left hand BSPT	1.1/4	33/42	0,115	136217
Steel	Left hand BSPT	1.1/2 - 2	40/49 - 50/60	0,150	136418
Steel	NPT	1/8	6/10	0,060	136221
Steel	NPT	1/4	8/13	0,060	136222
Steel	NPT	3/8	12/17	0,055	136223
Steel	NPT	1/2	15/21	0,060	136224
Steel	NPT	3/4	20/27	0,070	136225
Steel	NPT	1	26/34	0,115	136226
Steel	NPT	1.1/4	33/42	0,120	136227
Steel	NPT	1.1/2 - 2	40/49 - 50/60	0,150	136428
Stainless steel	Right hand BSPT	3/8	12/17	0,055	137003
Stainless steel	Right hand BSPT	1/2	15/21	0,065	137004
Stainless steel	Right hand BSPT	3/4	20/27	0,072	137005
Stainless steel	Right hand BSPT	1	26/34	0,120	137006
Stainless steel	Right hand BSPT	1.1/4	33/42	0,120	137007

THREADING MACHINE

1621: Threading Machine 2"

Advantages

Automatic opening or manually operated threading head.

Quick, simple thread size adjustment.

Hammer-type chuck and long jaws to rapidly, firmly and safely secure the pipe.

Safety switch avoids accidental operation.

Universal motor designed for harsh condition. Can withstand voltage drops of up to 80 V.

Machine producing "gas" threads with sealing as per NFE 03.004 compliant with ISO/7. For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.

Heavy-duty dies of HSS or standard grade steel.

Five-blade reamer for a clean, accurate result.

Body 330 mm long for threading short lengths of pipe. The body is angled at 2.2° to drain the oil from the pipe.

Safety pedal for starting and stopping the machine.

Self-priming gear-style oil pump.

Raised strainer avoids oil contamination by iron filings.

Variable oil flow control.









Capacities

Steel: BSPT, NPT Ø 1/4" - 2". BSPP Ø 1/2" - 2". Stainless steel: BSPT, NPT Ø 1/4" - 2".

Delivered with

- 1 automatic 1/2" to 2" BSPT and NPT threading head,
- 1 set of right-hand BSPT dies 1/2" 3/4",
- 1 set of right-hand BSPT dies 1" 2",
- 1 set of carbon brushes,
- 1 steel pipe cutting wheel,
- 5 L container of oil (Ref. 110605),
- 4 support legs,
- 1 safety pedal.

Tips

Use specially-designed dies and cutting wheels when working with zinc-coated and stainless steel.

1621: Threading Machine 4"

Advantages

Automatic opening threading head.

Quick, simple thread size adjustment.

Hammer-type chuck and long jaws to rapidly, firmly and safely secure the pipe.

Machine producing "gas" threads with sealing as per NFE 03.004 compliant with ISO/7. For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.

Self-priming gear-style oil pump.

Raised strainer avoids oil contamination by iron filings.

Variable oil flow control.

Heavy-duty dies available in HSS and standard grade steel.

Slotted dies for quick and easy replacement without removing the head.

3 gears for optimum cutting and threading of each pipe diameter.

Safety pedal for starting and stopping the machine.


Three-blade reamer for a precision result.

Special storage compartment.

A machine of proven endurance, designed for high-volume applications.







Motor	Power W	Composition	Dies	Speed rpm	Size mm	Kg	Ref.
Single-phase induction 230 V motor	1600	Ø": 1/2 - 3/4, 1 - 2, 2.1/2 - 4. Ø mm: 8/13 - 12/17, 26/34 - 50/60, 66/76 - 102/114	Right-hand BSPT	36/20/11	1200 x 870 x 1200	142,200	162140

Capacities

Steel: BSPT, NPT Ø 1/4" - 4". BSPP Ø 1/2" - 2". Stainless steel: BSPT, NPT Ø 1/4"- 4".

Delivered with

- 1 automatic 1/2" to 2" BSPT threading head,
- 1 automatic 2.1/2" to 4" BSPT threading head,
- 1 set of right-hand BSPT dies 1/2" 3/4",
- 1 set of right-hand BSPT dies 1" 2",
- 1 set of right-hand BSPT dies 2.1/2" 4",
- 1 steel pipe cutting wheel,
- $2 \times 5 L$ synthetic threading oil (ref. 110605),
- 4 support legs,
- 1 safety pedal.

Tips

Use specially-designed dies and cutting wheels when working with zinc-coated and stainless steel.

ACCESSORIES FOR 2" AND 4" THREADING MACHINE

1611: Roller Stand

The feet can be formed from 3/4" tubes (20/27).

Feet not included.

Description	Kg	Ref.
Stand (without feet)	4,100	161100





1621: Die Head for 2" – 4" Threading Machine

Machine producing "gas" threads with sealing as per NFE 03.004 compliant with ISO/7. For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.

* Supplied without set of dies.



Description	Capacity "	For machine	Opening	Kg	Ref.
Right hand BSPT - NPT *	1/4 - 3/8	162120/40	Manual	3,700	162150
Right hand BSPT - NPT *	1/2 - 2	162120/40	Auto	6,000	162151
Right hand BSPT *	2.1/2 - 4	162140	Auto	10,000	162152
Right hand NPT *	2.1/2 - 4	162140	Auto	10,000	162153

1622 : Dies for 2 " - 4 " Threading Machine Die Heads

Standard: steel.

HSS: Zinc coated and stainless steel.

Machine producing "gas" threads with sealing as per NFE 03.004 compliant with ISO/7. For tubes complying with the EN 10255 S and EN 10255 W standards (former NFA 49115 and NFA 49145 standard medium and heavy duty series); only light series tubes are not recommended.



Description	Pipe O.D. "	Pipe O.D. mm	For threader	Kg	Ref.
Right hand BSPT	1/4 - 3/8	8/13 - 12/17	Steel - 1621	0,500	162201
Right hand BSPT	1/2 - 3/4	15/21 - 20/27	Steel - 1621	0,600	162202
Right hand BSPT	1 - 2	26/34 - 50/60	Steel - 1621	0,600	162203
Right hand BSPT	2.1/2 - 4	66/76 - 102/114	Steel - 1621	0,800	162204
Right hand NPT	1/4 - 3/8	8/13 - 12/17	Steel - 1621	0,500	162205
Right hand NPT	1/2 - 3/4	15/21 - 20/27	Steel - 1621	0,600	162207
Right hand NPT	1 - 2	26/34 - 50/60	Steel - 1621	0,600	162208
Right hand NPT	2.1/2 - 4	66/76 - 102/114	Steel - 1621	0,800	162209
HSS Right hand BSPT	1/4 - 3/8	8/13 - 12/17	Stainless steel - 1621	0,500	162301
HSS Right hand BSPT	1/2 - 3/4	15/21 - 20/27	Stainless steel - 1621	0,600	162302
HSS Right hand BSPT	1 - 2	26/34 - 50/60	Stainless steel - 1621	0,600	162303
HSS Right hand BSPT	2.1/2 - 4	66/76 - 102/114	Stainless steel - 1621	0,800	162304
HSS Right hand NPT	1/4 - 3/8	8/13 - 12/17	Stainless steel - 1621	0,500	162305
HSS Right hand NPT	1/2 - 3/4	15/21 - 20/27	Stainless steel - 1621	0,600	162307
HSS Right hand NPT	1 - 2	26/34 - 50/60	Stainless steel - 1621	0,600	162308
HSS Right hand NPT	2.1/2 - 4	66/76 - 102/114	Stainless steel - 1621	0,800	162309
Right hand BSPP	1/2 - 3/4	15/21 - 20/27	Steel - 1621	0,600	162220
Right hand BSPP	1 - 2	26/34 - 50/60	Steel - 1621	0,600	162221

1621 : Spare parts for 2" - 4" Threading Machine

Description	Kg	Ref.
Cutting wheel for steel pipe (2" - 4" threading machine)	0,050	162470
Cutting wheel for Zinc coated and stainless steel pipes (2" – 4" threading machine)	0,050	162471
Carbon brushes (set of 2) for 2" threading machine	0,030	753066
Set of 3 jaws for 2" threading machine	0,600	753068
Set of 3 pawls for 2" threading machine	0,600	753069
Set of 3 jaws for 4" threading machine	0,900	753070
Set of 3 pawls for 4" threading machine	0,900	753071



1624 : Stand for 2" Threading Machine

For machine 162120.

The machine can be loaded and unloaded from a utility vehicle by one person.

The stand includes pistons for raising and lowering the machine.

Folding stand for easily transporting the threading machine.

System for emptying the machine without dismantling.

Legs provide support under load.

Tool tray.

Supplied with:

1 Oil emptying system,

1 Set of fastening screws.

Kg	Ref.
24,500	162460









1624: Stand for 4" Threading Machine

For 162140 machine.

Fitted with four wheels and handles for easy transport.

Rides kerbs and other obstacles easily.

Tool tray.

Supplied with:

Fastening screws.

Kg	Ref.
31,500	162461







1624 : Grooving machine

It fits most machines currently on the market.

Designed for on site applications.

Fast and easy grooving to be carried out.

Quick, simple adjustment system ensuring a constant groove depth.

Turn with a ratchet wrench (1/2" ref. 220410) or handle for reduced effort.



Steel pipes: NF EN 10208.2/10255W/10217.1/10255S/10216.1.

Max thickness 5.5 mm.

Supplied with:

- 1 connecting shaft,
- 1 set of rollers 2 to 6".

Adaptor optional.

Description	Capacity "	Kg	Ref.
Grooving machine	1 - 6	11,000	162400
Set of rollers	1	2,300	162431
Set of rollers	1.1/4 - 1.1/2	2,400	162432
Set of rollers	2 - 6	2,500	162433





1624: Adaptor for the VIRAX Grooving Machine

These adaptors allow the Virax grooving machine to be mounted on most threading machines currently available.

For machine	Kg	Ref.
Virax 162120	1,150	162420
Virax 162140	1,500	162430
Virax 1620	1,500	162424
Ridgid 300	1,500	162421
Ridgid 300C	1,500	162422
Ridgid 535	1,500	162423
Rems Tornado and Magnum	1,500	162425
Rothenberger Supertronic 2SE	1,150	162420







GROOVER

1626: Groover GR2-12

Advantages

Grooving up to 12", with accurate depth setting.

Hydraulic jack for fast grooving.

Powerful and silent motor on sturdy frame.

Electrohydraulic groover, produces grooves by cold knurling on standard steel and thin wall pipes \emptyset 2" – 12". For installing piping, spraying systems, large-size heating and industrial installations

Compact and highly stable designed for work on worksites and in workshops.

Powerful motor 240 V, 50 / 60 Hz, 1500 W, 23 rpm.

Frame mounted on 4 feet for safe man-height work.

Sturdy hydraulic pump with ergonomic control grip; max. pressure: 8,000 kg.

Pressure valve for fast pipe change.

Lower roller storage compartment.

Grooving rollers designed and tempered specifically for minimum wear, with anti-skid surface for more effective tube feed.

Accurate groove depth adjustment with a nut / locknut system, ideal for repetitive work.

Safety pedal for operation control and instant stopping of machine rotation.

Stabilizer for large diameters to prevent tube slipping.

Roller holder for tubes up to \emptyset 12", fitted with 4 knobs; 2 tempered steel side guides with fast locking system.

Weight (machine only): 129 kg.

Machine dimensions on feet: 770 x 550 x 1400 mm.

Description	Capacity "	Kg	Ref.
Groover GR2-12	2 - 12	170,000	162600
Upper roller 2"-6" for steel / stainless steel pipe	2 - 6	0,780	162610
Upper roller 8"-12" for steel / stainless steel pipe	8 - 12	0,810	162611
Lower roller 2"-2.1/2" for steel pipe	2 - 2.1/2	0,550	162612
Lower roller 3"-6" for steel pipe	3 - 6	1,250	162613

Description	Capacity "	Kg	Ref.
Lower roller 8"-12" for steel pipe	8 - 12	1,420	162614
Lower roller 2"-2.1/2" for stainless steel pipe	2 - 2.1/2	0,550	162616
Lower roller 3"-6" for stainless steel pipe	3 - 6	1,250	162617
Lower roller 8"-12" for stainless steel pipe	8 - 12	1,420	162618
Pipe holder for grooving machine	2 - 12	29,000	162615

Capacities

For steel or stainless steel pipes \emptyset 2" – 12" (60 – 325 mm).

Pipe wall thickness: $3.5-10\ \text{mm}$ (steel) $/\ 1.6-6.5\ \text{mm}$ (stainless steel).

Delivered with

- 4 frame feet.
- Safety pedal.
- Large diameter stabilizer.
- Roller holder. (162615)
- Grooving control tape measure.
- 3 lower rollers for steel pipe (2" 2.1/2"; 3" 6"; 8" 12").
- 2 upper rollers for steel and stainless steel pipe (2"-6"; 8"-12").
- Installation tool set.

Tips

When grooving stainless steel pipes, use the optional specific lower rollers.



PERCUSSION FLANGING TOOL

2504 : Copper Forming Set

For annealed copper pipes.

The holes in the die have a 90° chamfer on one side for forming tapered flanges with the turn

The other side may be used for forming flat flanges after first forming a tapered flange. 4 opposing pegs are provided for securing the die in a parallel vice. Phosphate finish. Supplied in a plastic case with turn pin plus single and stepped mandrels.

Composition of set	Kg	Ref.
Die for pipe O.D.: 6 - 8 - 10 - 12 - 14 mm, 90° turn pin for pipe O.D. : 6 to 14 mm, Single size mandrel 10 to 12 mm dia, Stepped mandrels 8 to 14 mm	1,350	250401
Die for pipe O.D.: 10 - 12 - 15 - 16 - 18 - 20 - 22 mm, 90° turn pin for pipe O.D.: 10 to 22 mm, Single size mandrel 16 mm Ø.Stepped mandrels 10 and 18, 12 and 20 and 15 and 22 mm Ø.	3,440	250402
Die for pipe O.D.: 10 - 12 - 14 - 16 - 18 - 20 - 22 mm, 90° turn pin for pipe O.D.: 10 to 22 mm, Single size mandrel 16 mm Ø, Stepped mandrels 10 and 18, 12 and 20 and 14 and 22 mm Ø.	3,400	250403



2504 : Die

The holes in the die have a 90° chamfer on one side for forming tapered flanges with the turn pin. The other side may be used for forming flat flanges after first forming a tapered flange.

Pipe O.D. mm	Kg	Ref.
6 - 8 - 10 - 12 - 14	0,480	250411
10 - 12 - 15 - 16 - 18 - 20 - 22	1,180	250412
10 - 12 - 14 - 16 - 18 - 20 - 22	1,175	250413



2504: Mandrel / Flanging Tool







Description	Type	Pipe O.D. mm	Kg	Ref.
Flanging tool	90°	6 to 14	0,090	250441
Flanging tool	90°	10 to 22	0,270	250442
Flanging tool	90°	6 to 40	0,525	250443
Flanging tool	60°	10 to 22	0,300	250447
Mandrel	Single	10	0,075	250422
Mandrel	Single	12	0,080	250423

Description	Туре	Pipe O.D. mm	Kg	Ref.
Mandrel	Single	16	0,250	250435
Mandrel	2 sizes	8 and 14	0,085	250421
Mandrel	2 sizes	10 and 18	0,265	250431
Mandrel	2 sizes	12 and 20	0,275	250432
Mandrel	2 sizes	14 and 22	0,285	250433
Mandrel	2 sizes	15 and 22	0,290	250434

FRIGOR - FLARING TOOL

2505: Heavy Duty Flanging Tool

Advantages

Eccentric-mounted turn-pin for an impeccable finish and a perfect seal.

End-of-travel "release" system for "smoothing " the flange. Feed screw fitted with a large handle **for minimum effort**.

Capacity on annealed and hard copper pipes: 45° tapered flange: Ø 3/16" to 3/4" OD. Precision tool for forming flanges on copper refrigeration pipes. Supplied in a plastic case containing die and yoke vice.

ovirax o c

Pipe O.D. "	Taper angle	Kg	Ref.
3/16 - 1/4 - 5/16 - 3/8 - 1/2 - 5/8 - 3/4	45°	1,970	250580



2506: Flaring Tool

Chrome finish for the yoke, hard chrome for the tools.

Capacity on annealed copper pipes:

45° tapered flange: Ø 1/8"* to 3/4" OD.


Expanding tools: Ø 3/16" to 3/4" OD.

Combined tool for forming $45\,^\circ$ flares and expansion of refrigeration pipes.

Easy tool change.

Supplied in a plastic case with die and yoke vice.

* Only 45° tapered flange.









Virax a daily player in environmental protection

CITEO

As a member of CiteO, an eco-organization funding the collection and sorting of paper, Virax is committed to preserving natural resources, by using recycled paper within the company and for all its advertising media, and participating in this funding via the eco-contribution.

FLARING PLIERS

2526: Flaring Pliers for Copper

Advantages

Reduced effort ensured by long, rigid handles.

Lightweight pliers (made of forged aluminum) less than 800 gr and very high strength profiled handles.

Quick and easy tool change.

The design of the mechanism of the pliers ensures:

- Use in any position.
- Extraction of the head after flaring, every time.

Ergonomic polypropylene grease and solvent resistant grips.

Supplied in a plastic case.

Description	Kg	Ref.
Ø 12, 14, 16, 18, 22 mm	2,120	252641
Ø 12, 14, 16, 18, 22, 28, 32 mm	2,500	252644
Ø 12, 15, 18, 22, 28 mm	2,200	252679
Ø 3/8, 1/2, 5/8, 3/4, 7/8"	2,300	252637
Ø 3/8, 1/2, 5/8, 3/4, 7/8, 1.1/8"	2,170	252651
Ø 3/8, 1/2, 5/8, 3/4, 7/8, 1, 1.1/8"	2,485	252681
Pliers only	0,710	252600
Pliers + case	1,710	252640







2526: Flaring Tool

High quality expansion tools:

- 6 detachable, self-centring segments.
- Long flaring length.
- Special anti-oxidation treatment providing efficient protection.



Pipe O.D. "	Pipe O.D. mm	Pipe wall thickness mm	Kg	Ref.
-	8	1	0,125	252601
-	10	1	0,130	252602
-	12	1	0,120	252603
-	14	1	0,130	252604
-	15	1	0,130	252605
-	16	1	0,130	252606
-	18	1	0,140	252607
-	20	1	0,145	252608
-	22	1	0,155	252609
-	25	1	0,175	252610
-	28	1	0,190	252611
-	32	1	0,230	252612
-	35	1	0,255	252613
-	36	1	0,265	252614

Pipe O.D. "	Pipe O.D. mm	Pipe wall thickness mm	Kg	Ref.
-	40	1	0,305	252615
-	42	1	0,325	252616
3/8	-	1	0,130	252622
1/2	-	1	0,125	252623
5/8	-	1	0,130	252624
3/4	-	1	0,140	252625
7/8	-	1	0,155	252626
1	-	1	0,175	252627
1.1/8	-	1	0,180	252628
1.1/4	-	1	0,210	252632
1.3/8	-	1	0,210	252633
1.1/2	-	1	0,210	252634
1.5/8	-	1	0,210	252635

EXPANSION PLIERS

2534 : Expansion Pliers PEX series 5

Advantages

Quick tool change.

Effort reducing mechanism.

Ergonomic polypropylene handles.

Capacity Ø 12 to 32 mm. For PEX series 5 pipes.

Expansion head: Ø 12, 16/20, 25 and 32 mm.

For the Alphacan Retube \varnothing 32 mm system, push the pipe onto the coupling as far as the last

Description	Kg	Ref.
Case: Pliers + Expansion tools Ø 16, 20, 25, 32 mm	2,020	253401
Case: Pliers + Expansion tools Ø 12, 16, 20 mm	3,300	253402
Case: Pliers + Expansion tools Ø 12, 16, 20, 25, 32 mm	2,400	253403
Pliers only	0,720	253480
Case only	0,840	253481
Expansion tool Ø 12 mm	0,150	253412
Expansion tool Ø 16/20 mm	0,133	253416
Expansion tool Ø 25 mm	0,156	253425
Expansion tool Ø 32 mm	0,156	253432








Delivered with

In a plastic case.





T-FLANGE

2527: T-Rax T-Flange Tool Set

Ratchet-operated tools for forming extruded T-flanges. Supplied in a metal case.

T-rax with tools	Kg	Ref.
Ø 12, 14, 16, 18, 22 mm	3,930	252730



2527: T-rax Accessories

Special drill bit (adjusted to suit the diameter), to be mounted on a reversible drill to form the hole for inserting the tool prior to extrusion.

Punching Pliers: limit the penetration of the pipe branch into the flange to ensure perfect flow. 11 mm ratchet square drive.

Description	Kg	Ref.
Drill Bit	0,415	252701
Punching Pliers	0,120	252702
Ratchet for T-flanges	0,310	252703







2527: T-Rax Flanging tools

Ø mm	Kg	Ref.
12	0,084	252711
14	0,140	252712
16	0,175	252714
18	0,220	252715
22	0,335	252717
28	0,370	252719



2528: Extrudax® T-Flange Tool Set

Special drill bit (adjusted to suit the diameter), mounted on a reversible drill to make a hole for inserting the tool prior to extrusion The punching pliers limit the penetration of the branch pipe into the flange to ensure perfect flow.

Powered "Extrudax" T-flange tool sets are supplied with a 230 V - 800 W reversible drill. Supplied in a case.

	Description	Motorised	Kg	Ref.
Г	Ø 12, 14, 16, 18, 22 mm	yes	5,750	252830
	Ø 12, 14, 16, 18, 22 mm	-	1,500	252880
	Ø 3/8, 1/2, 5/8, 3/4, 7/8"	-	1,500	252883





2528: Extrudax® Accessories

Special drill bit (adjusted to suit the diameter), to be mounted on a reversible drill to make a hole for inserting the tool prior to extrusion.

Description	Speed rpm	Kg	Ref.
230 V - 701 W reversible drill	0 to 850	3,690	252806
Tool holder	-	0,280	252802
Hexagonal drive	-	0,045	252804
Drill Bit	-	0,080	252801



2528: Extrudax® Flanging Tools



Ø mm	Ø"	Kg	Ref.
10	-	0,060	252810
12	-	0,060	252812
14	-	0,060	252814
15	-	0,060	252815
16	-	0,065	252816
18	-	0,065	252818
20	-	0,065	252820

Ø mm	ø"	Kg	Ref.
22	-	0,068	252822
-	3/8	0,060	252860
-	1/2	0,060	252861
-	5/8	0,060	252862
-	3/4	0,063	252863
-	7/8	0,070	252864

TOOLS FOR LEAD TUBE

2610: Tools for lead tube

261000 : Expanding Pliers

For expanding lead pipes. Pressed sheet steel. Striated surface.

261010 : Plumbers broach

For reshaping the ends of lead pipes. Phosphated steel, bent at 40 $^{\circ}\,.$







Description	A mm	A1 mm	Ø mm	L mm	Kg	Ref.
Expanding Pliers	0 - 8	60	-	290	0,365	261000
Plumbers broach	-	-	16	270	0,375	261010



Virax in France, is also...

The Virax head office, located in Epernay, France, groups all activities: R&D department, Production Centre, Quality pole, Customer service, Purchasing department, After-Sales Service... up to the Storage and Distribution center.

SEALANT

2626: Filetfix® III

Advantages

Quick polymerisation.

Repositionable before drying.

High temperature and pressure resistance.

Consistent with the main European standards for gas, hot water and drinking water.

Sealant for threaded connections in contact with town gas, natural gas, liquid petroleum gas, hot water, drinking water, air and petroleum products.

- Complies with Positive Lists (CLP) for contact with drinking water.
- Complies with the GDF specifications.
- Complies with EN 751-1 Class H / DVGW approval * (sealants for threaded connections in contact with gas and hot water).
- Complies with WRAS drinking water certification.

Easy to apply, thanks to its accurate and transparent spout. Resistant to vibration, corrosion and most solvents. Not to be used on pure oxygen or steam pipes, or on plastics.

For more information, see our Technical data sheet available at www.virax.com, section Documentation > Technical Sheet.

* excluding installation meeting the TRGI 86/96 standard

Packaging	Kg	Ref.
1 bottle of Filetfix® III - 60 ml	0,100	262600







2626: Display of Bottles of Filetfix® III

Display of 15 Bottles of Filetfix® III (262600).

Kg	Ref.
1,680	262601







Virax certified ISO 14001 and OHSAS 18001 since 2009

And in 2016 our Environmental Management System was acknowledged through certification in its new version ISO 14001: 2015.



AXIAL CRIMPING

2533 : Compact Manual Axial Crimping Tool for PEX series 5

Advantages

User-friendly: only one hand to crimp or declutch. Gear units to crimp the coupling, elbow, T, nut and threaded. The range is completed by Expansion Pliers Ø 12-20 mm.

Specific crimping forks design to not damage the coupling during the crimping.

For crimping free nuts Ø 3/8, 1/2, 3/4" and Tees and elbows Ø 12, 16 and 20 mm. (Crimping fork in Ø 20 mm)

Suitable for installation or renovation in a house.

Ergonomic use with Soft Touch® handles.

Effortless handling for an easier work.

Die-cast aluminum design: strong and light weight (only 800g).

Expansion Pliers PEX series 5: Sheathed handles for a better handling; End caps treated with cataphoresis to reduce corrosion risk and to make easier the pipe fitting.

Description	Kg	Ref.
Crimping tool box Ø 12 - 16 - 20 mm + expansion pliers Ø 12 - 16 - 20 mm	2,340	253360
Crimping tool box Ø 12 - 16 - 20 mm	2,000	253350
Expansion pliers Ø 12 - 16 - 20 mm	0,380	253355
Crimping tool box Ø 12 - 16 - 20 mm + expansion pliers Ø 12 - 16 - 20 mm + pipe cutter PC 32	2,540	253361
Gear Ø 12 mm	0,080	753568
Gear Ø 16 mm	0,080	753569
Gear V	0,080	753570
Flat double gear	0,080	753571







Capacities

PEX series 5 Ø 12 - 16 - 20 mm

Delivered with

2 gears Ø 12 mm (Réf. 753568), 2 gears Ø 16 mm (Réf. 753569), 1 double gear V (Réf. 753570), 1 flat double gear (Réf. 753571). In a case.

Benefit of VIRAX Soft Touch®



The Soft Touch® coating offers the best possible grip. It reduces fatigue and minimizes the risk of the product slipping when handling it with wet hands.



2533: Manual Axial Crimping Tool for PEX series 5

Advantages

Quick tool change.

Effort reducing mechanism. Quick crimping.

Capacity from Ø 12 to 32 mm.

Ergonomic polypropylene handles.

Reset trigger.

Removable, reversible adaptor to suit the different couplings on the market.

Rapid feed system.

6 reducers and 1 adaptor are available for performing Ø 12, 16, 20, 25 and 32 mm crimps on the following couplings: union, T, 90° elbow, captive or free-turning captive nut.

Description	Kg	Ref.
Ø 16, 20, 25 and 32	3,260	253300
Ø 12, 16, 20 and 32	3,270	253302
Ø 12, 16, 20, 25, and 32	3,310	253303
Machine only	1,250	253380
Case	0,840	253381







Capacities

Ø 12 to 32 mm.

Delivered with

In a plastic case.

2533: Reducer and adaptor for Axial Crimping Tools 2533

For Axial Crimping Tools ref. 253300, 253302, 253303, 253380.

Description	Kg	Ref.
Reducer Ø 12 mm	0,060	253312
Reducer Ø 16 mm	0,055	253316
Reducer Ø 20 mm	0,045	253320
Reducer Ø 25 mm	0,035	253325
Reducer Ø 32 mm	0,150	253332
"V" Adaptor Ø 12, 16, 20, 25, 32 mm	0,050	253333
Adaptor for Ø 1/2, 3/4, 1" nut	0,050	253334
Adaptor for Ø 3/8" nut	0,100	253335







Go to www.virax.com

To find a product sheet, a safety data sheet or exploded views, Go to our web site.

RADIAL CRIMPING

2529: Viper® i26 Manual Hydraulic Press-Fitting **Machine**

Advantages

Multi-material press-fitting, up to Ø 26 mm in multiple layers.

Ergonomic and space-saving

Sound indicator at end of crimping.

Manual hydraulic press-fitting machine for use with insert sets.

Easy feed by a high performance staged piston hydraulic device.

Crimping end indicator: sound signal when reaching maximum pressure.

Minimized weight (only 2.5 Kg): one-handed use thanks to its ergonomic design, slim format and compact head for access to confined spaces.

Head swivels at 180° for easy use in all situations; Fast head opening / closing.

High quality steel hydraulic dispenser, jaw in anticorrosion treated hardened steel.

Machine protected by overpressure valve.

Non-slip Soft Touch® handle for perfect control.

Wide choice of inserts: Virax has inserts for the majority of crimping systems available on the

Size: 366 x 63 x 88mm.


Supplied in a case VIRABOX

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.

Non-contractual photo



Multilayer: Ø 12 - 26 mm. Except inserts HA26 and V15.











Discover our YouTube channel

and its product demonstration videos! /VIRAX

2535 : Viper® M21+ Electro-mechanical Press Fitting **Machine**

Advantages

The lightest in its category: only 2.2 kg battery included: weight minimized to improve user comfort.

Secured cycle: electronic control of the crimping cycle with automatic adaptation of the load applied.

Modular: to work with inserts or mini crimping jaws.

Electromechanical crimper 20 kN on battery, with automatic piston return.

One Machine for 2 solutions:

Use with mini crimping jaws: compact and light, for crimping in confined spaces and between manifolds.

Use with the mother jaws and inserts: compact, they are practical to store, transport and very light to use.

Inserts in offset version for certain profiles, allowing crimping as close as possible to an obstacle (e.g. along a wall).

Designed for user comfort:

Ergonomic use: Soft Touch® anti-slip grip, highly compact 360° pivoting head (only 33 cm long with mini crimping jaws).

Minimized weight (only 2.2 kg with battery / 3.4 kg with mini crimping jaws) and fast cycle to guarantee effective work.

Centre of gravity placed ideally, allowing to place it on its foot between two crimping operations, and improve user comfort.

Smart for increased safety:

Electronic card control of proper crimping performance with light and sound indicators.

Calculation of the exact force to apply according to the coupling: extended lifetime.

Secured crimping jaw locking, simple and fast changing.

Crimping starts only when the battery is charged sufficiently.

The user can stop crimping at any time by releasing pressure on the trigger.

Automatic machine shutdown to save batteries.

Communicates:

Battery charge indicator.

Maintenance indicator at 20 000 cycles with early warning at 19 000 and 19 500.

The machine connects to a PC to check the number of crimping operations performed and anticipate servicing.

Li-Ion 18V battery:

Battery available in 1.5 Ah version (ref. 253506), or 3 Ah version (ref. 253505) for twice the

Battery platform common with the Viper® P25+ press fitting machine.

Wired adapter 230V - 18 V (ref. 253508) as an option or according to set reference for continuous mains operation.

M21+ supplied in standard with 2 1.5 Ah batteries.

Size (with battery): 340 x 240 x 85 mm.

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.







Composition	Size mm	Crimping force kN	Kg	Ref.
Viper® M21+ 18 V - 1,5 Ah Li-Ion - Without mother jaw		20	6,900	253500
Viper® M21+ 230V wire adapter – Without mother jaw	590 x 390 x 140	20	6,300	253501
Viper® M21+ 18 V - 1,5 Ah Li-Ion - Mother jaw	590 x 390 x 140	20	8,000	253502
Viper® M21+ 18 V - 1,5 Ah Li-lon - Mother jaw - Inserts HA16 / HA20 / HA26	590 x 390 x 140	20	8,900	253510
Viper® M21+ 18 V - 1,5 Ah Li-lon - Mother jaw - Inserts TH16 / TH20 / TH26	590 x 390 x 140	20	8,500	253511
Viper® M21+ 18 V - 1,5 Ah Li-lon - Mother jaw - Inserts RFP12 / RFP16 / RFP20	590 x 390 x 140	20	8,500	253512

Composition	Size mm	Crimping force kN	Kg	Ref.
Viper® M21+ 18 V - 1,5 Ah Li-Ion - Mother jaw - Inserts V12 / V14 / V16 / V18 / V22	590 x 390 x 140	20	8,700	253513
Viper® M21+ 18 V - 1,5 Ah Li-lon - Mother jaw - Inserts U16 / U20 / U25	590 x 390 x 140	20	8,500	253514
Viper® M21+ 18 V - 1,5 Ah Li-Ion - Mother jaw - Inserts V12 / V15 / V18 / V22 / V28	590 x 390 x 140	20	8,700	253516
UViper® M21+ 18 V - 1,5 Ah Li-lon - Mother jaw - Inserts TH16 / TH20 / TH25 / TH32	590 x 390 x 140	20	8,700	253517
Viper® M21+ 18 V - 1,5 Ah Li-Ion - Mother jaw - Inserts RFP16 / RFP20 / RFP25	590 x 390 x 140	20	8,500	253518
Viper® M21+ 18 V - 1,5 Ah Li-lon - Mother jaw - Inserts RFP16 / RFP20 / RFP25 / RFP32	590 x 390 x 140	□20	8,700	253519

Capacities

Copper: \emptyset 12 – 28 mm. Stainless steel: \emptyset 12 – 28 mm.

PER, PEX: Ø 12 – 32 mm (inserts) / 40 mm (mini crimping jaws TH-U). Multilayer: Ø 12 – 32 mm (inserts) / 40 mm (mini crimping jaws TH-U).

Electro-zinc steel (or carbon steel): Ø 12 – 28 mm.

Delivered with

- 2 Li-lon 18 V 1.5 Ah batteries, 1 fast charger (except ref. 253501).
- 1 mother jaw (except ref. 253500 and 253501).
- In box.



Virax encourages WorldSkills France

As an official supplier of the national finals of Plumbing, Heating and Metallic Roofing professionals, our objective is to support apprenticeship and professional training of young adults before the age of 23. Apprentices are able to express all their talent and invest in their future while promoting their trade.



2535 : Viper® ML21+ Electro-Mechanical Press Fitting **Machine**

Advantages

Slim format: for use in confined spaces.

Proven product: all the technical benefits of the M21+ gun

Modular: to work with inserts or mini crimping jaws.

Electro-mechanical 20 kN press fitting machine with automatic piston return.

Slim format for easier access in confined spaces: only 12 cm wide.

Minimized weight (only 3.4 kg with mini crimping jaws).

Centre of gravity located on the gripping zone for less user fatigue.

Can be placed on its foot between two crimping operations, and improves user comfort.

Control by easily accessible push button.

All the technical benefits of the Viper® M21+ press fitting machine (ref. 253502), visible on the previous page.

Dimensions (battery included): 314 x 119 x 79 mm.

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.







Description	Size mm	Crimping force kN	Kg	Ref.
Viper® ML21+ 18V - Mother jaw	390 x 390 x 140	20	6,575	253521
Viper® ML21+ 18V – Without mother jaw	390 x 390 x 140	20	5,472	253520
Viper® ML21+ 18V - Mother jaw - Inserts TH16-20-26	390 x 390 x 140	20	7,070	253522
Viper® ML21+ 18V - Mother jaw - Inserts RFP12-16-20	390 x 390 x 140	20	7,070	253523
Viper® ML21+ 18 V - Mother jaw - Inserts V12-14-16-18-22	390 x 390 x 140	20	7,270	253524
Viper® ML21+ 18 V - Mother jaw - Inserts U16-20-25	390 x 390 x 140	20	7,070	253525

Capacities

Copper: Ø 12 – 28 mm. Stainless steel: Ø 12 – 28 mm.

PER, PEX: Ø 12 – 32 mm (inserts) / 40 mm (mini crimping jaws TH-U). Multilayer: Ø 12 – 32 mm (inserts) / 40 mm (mini crimping jaws TH-U).

Electro-zinc steel (or carbon steel): Ø 12 – 28 mm.

Delivered with

- 2 Li-lon 18 V
- 1.5 Ah batteries, 1 fast charger.
- 1 mother jaw (except ref. 253520).
- In box.



Virax has been certified ISO 9001 since 1997

And in 2016 our Quality Management System was acknowledged through certification in its new 2015 version.

2532 : Viper® P25+ Battery-Powered Hydraulic Press Fitting Machine

Advantages

Light: Only 4 kg with the battery.

Quick: very short press fitting cycle (about 5 sec.), with

automatic piston return.

Practical: 2 frontal lights to light the part to press.

Handy and effective:

Hydraulic press fitting machine 32 kN, with 360° pivoting head and automatic piston return. Lightweight and fast cycle guaranteeing effective and easy work for the user in all working conditions.

Anti-slip Soft Touch® ergonomic handle.

Temperature of use between -10° C and +60° C.

Smart with its electronic card:

Crimping cycle end or interruption indicator

Battery charge indicator

Cycle service indicator at 20 000 cycles with early warning at 19 500.

Automatic machine shutdown to save batteries.

Safety focus:

Crimping clamps locked by a lever at 180° to prevent untimely locking Press fitting machine locked when battery charge insufficient to make a complete cycle The user may stop crimping at any time with the emergency stop button

Li-Ion 18V / 3 Ah battery: increased crimping time, resists to cold (down to -10 °C), Soft Touch® protection reinforcements, minimum auto-discharge and no memory effect. Battery platform common with the VIPER® M21+ press fitting machine. Wired adapter 230V - 18 V (ref. 253508) as an option or according to set reference for continuous mains operation.

Size (with battery): 411 x 249 x 93 mm.

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.







Description	Size mm	Crimping force kN	Kg	Ref.
Viper® P25+ 18V – 2 Li-Ion batteries 3Ah	590 x 390 x 140	32-34	8,700	253261
Viper® P25+ Mains adaptor 230V	590 x 390 x 140	32-34	7,560	253262
Viper® P25+ 18V – 1 Li-lon batterie 3Ah	590 x 390 x 140	32-34	8,050	253263

Capacities

Copper: Ø 12 - 54 mm. Stainless steel: Ø 12 - 54 mm. PER/PEX: Ø 12 - 32 mm. Multilayer: Ø 12 - 110 mm.

Electro-zinc steel (or carbon steel): Ø 12 – 54 mm.

Delivered with

Ref. 253261:

- 2 Li-Ion batteries 18 V - 3 Ah. - 1 fast 85 min. charger. - Without crimping jaws. - In a case.

Ref. 253262

- 1 mains adapter 230 V 18 V. Without crimping laws. In a case.
- 1 Li-Ion batterie 18 V 3 Ah. 1 fast 85 min. charger. Without crimping jaws. In a case.

CONNECTION / ASSEMBLY

2536: Viper® P30+ Electro-Mechanical Press Fitting **Machine**

Advantages

One the lightest machine in its category: 4,5kg without jaw. Crimping control by micro-processor:

Systematic crimping control with LED display (green or red). Automatic return of the piston.

USB/PC connection: Read numbers of cycles to anticipate maintenance (18 000 cycles).

180° pivoting head.

Maintenance indicator with preventive alert at 15 000 cycles before machine shutdown at 18

Checks temperature and only works in optimum conditions (-10° +50°) in order to avoid wrong crimping.

230V - 50Hz power supply.

Ergonomic Soft Touch® handle for a perfect grip and comfort in use.


Optimum user safety: crimping control by electronic board. Systematic crimping control with LED display (green or red).

No-load cycle impossible to minimize risks of injury: a sensor detects the clamp when mounted on the Viper P30+.

The exact force required for crimping is calculated by the machine's internal program: moderate wear of mechanical components.

Size: 315 x 230 x 85 mm.

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.



Capacities

Copper: Ø 12 - 54 mm. Stainless steel: Ø 12 - 54 mm. PER/PEX: Ø 12 - 32 mm. Multilayer: Ø 12 - 110 mm.

Electro-zinc steel (or carbon steel): Ø 12 – 54 mm.

Delivered with

- Without crimping laws. - In a case.



Much more than just quality, here's the Virax commitment!

Virax commits to total, permanent and durable satisfaction of users and therefore applies a process based on:

A proactive product plan.

A constant innovation process.

A focus on permanent improvement.

Improved customer services.

An assurance of optimum availability rate.

Customer satisfaction, the heart of our commitments.







2532 - 2535 : Accessories for Press Fitting Machines

For	Description	Kg	Ref.
Viper® M21+ / Viper® ML21+ / Viper® P25+	Battery 18 V - 3 Ah Li-ion	0,790	253505
Viper® M21+ / Viper® ML21+	Battery 18 V - 1,5 Ah - Li-ion	0,450	253506
Viper® M21+ / Viper® ML21+ / Viper® P25+	240 V Charger - for 18 V - Li-ion battery	0,800	253507
Viper® M20+ / P22+	Battery 14,4 V - 2,4 Ah Li-Ion	0,645	253244
Viper® M20+ / P22+	230 V Charger - for 14,4 V battery - 2,4 Ah Li-lon	0,740	251844
Viper® M20+ / P22+	Mains adaptor 230V - 14,4V	0,980	252938
Viper® M21+ / Viper® ML21+ / Viper® P25+	Mains adaptor 230V - 18V	0,900	253508
Viper® M21+ / Viper® ML21+	Mother jaw	1,150	753497







2529 - 2532 : Inserts for Models i10 / i26 / M20+ / M21+ / ML21+

Lightweight. Compact. Very good value for money. Very high strength steel (33 HRC). Very precise crimping.

Inserts in offset version for certain profiles, allowing crimping as close as possible to an obstacle (e.g. along a wall).

5 year guarantee (except profile).

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.







Profile	Ø	Туре	i10	i26	M20+	M21+/ML21+	Kg	Ref.
М	12	Off centred	-	-	ok	ok	0,220	252951
М	15	Off centred	-	-	ok	ok	0,205	252952
М	18	Off centred	-	-	ok	ok	0,185	252953
М	22	Standard	-	-	ok	ok	0,185	252954
М	15-18-22	-	-	-	ok	ok	0,850	990156
М	28	Standard	-	-	-	ok	0,140	252955
G	16	Standard	-	ok	-	ok	0,270	252981
G	20	Standard	-	ok	-	ok	0,240	252982
G	26	Standard	-	ok	-	ok	0,190	252983
G	32	Standard	-	-	-	ok	0,160	252984
HA	16	Standard	ok	ok	ok	ok	0,410	252986
HA	20	Standard	ok	ok	ok	ok	0,360	252987
HA	26	Standard	-	-	ok	ok	0,290	252988
HA	16-20-26	Standard	-	-	ok	ok	1,300	990010
HA	32	Standard	-	-	ok	ok	0,180	252989
H-ML	14	Standard	ok	ok	ok	ok	0,190	252942
H-ML	16	Standard	ok	ok	ok	ok	0,180	252943
H-ML	18	Standard	ok	ok	ok	ok	0,170	252945
H-ML	20	Standard	ok	ok	ok	ok	0,160	252946
H-ML	26	Standard	-	ok	ok	ok	0,130	252948
H-ML	16-20-26	Standard	-	ok	ok	ok	0,770	990066
H-ML	32	Standard	-	ok	ok	ok	0,080	252949
RF-P	12	Standard	ok	-	ok	ok	0,220	253251
RF-P	16	Standard	ok	ok	ok	ok	0,190	253252
RF-P	18	Standard	ok	ok	ok	ok	0,190	253257
RF-P	20	Standard	ok	ok	ok	ok	0,170	253253

^{*} Viper® i10 with TH26 Profile: only for Barbi, Comap, Frankische, Giacomini, Idrosanitaria Bonomi, Industrial Blansol, Ipalpex, Somatherm, Tiemme, Valsir.

4 CONNECTION / ASSEMBLY

Profile	Ø	Туре	i10	i26	M20+	M21+/ML21+	Kg	Ref.
RF-P	12-16-20	Standard	ok	ok	ok	ok	0,850	990020
RF-P	25	Standard	-	ok	ok	ok	0,150	253254
RF-P	16-20-25	Standard	-	ok	ok	ok	0,780	990058
RF-P	32	Standard	-	ok	ok	ok	0,130	253255
TH	14	Standard	ok	ok	ok	ok	0,290	252902
TH	14	Off centred	-	-	ok	ok	0,290	253266
TH	15	Standard	ok	ok	ok	ok	0,285	252903
TH	16	Standard	ok	ok	ok	ok	0,280	252904
TH	16	Off centred	-	-	ok	ok	0,280	253268
TH	17	Standard	ok	ok	ok	ok	0,270	252905
TH	18	Standard	ok	ok	ok	ok	0,260	252906
TH	20	Standard	ok	ok	ok	ok	0,240	252907
TH	20	Off centred	-	-	ok	ok	0,240	253271
TH	25	Standard	-	ok	ok	ok	0,200	252908
TH	26	Standard	ok*	ok	ok	ok	0,190	252909
TH	16-20-26	Standard	ok*	ok	ok	ok	0,850	990019
TH	32	Standard	-	-	ok	ok	0,110	252911
U	14	Off centred	-	-	ok	ok	0,200	253281
U	16	Standard	ok	ok	ok	ok	0,180	252915
U	16	Off centred	-	-	ok	ok	0,170	253272
U	18	Standard	ok	ok	ok	ok	0,170	252916
U	20	Standard	ok	ok	ok	ok	0,160	252917
U	20	Off centred	-	-	ok	ok	0,160	253273
U	25	Standard	-	ok	ok	ok	0,130	252918
U	16-20-25	Standard	-	ok	ok	ok	0,770	990063
U	32	Standard	-	-	ok	ok	0,080	252919
V	12	Standard	-	ok	ok	ok	0,180	252961
V	12	Off centred	-	-	ok	ok	0,170	253274
V	14	Standard	-	ok	ok	ok	0,170	252966
V	14	Off centred	-	-	ok	ok	0,170	253275
V	15	Standard	-	-	ok	ok	0,165	252962
V	15	Off centred	-	-	ok	ok	0,170	253276
V	16	Standard	-	ok	ok	ok	0,160	252967
V	16	Off centred	-	-	ok	ok	0,170	253277
V	18	Standard	-	-	ok	ok	0,160	252963
V	18	Off centred	-	-	ok	ok	0,170	253278
V	22	Standard	-	-	ok	ok	0,130	252964
V	12-15-18-22	Standard	-	-	ok	ok	0,940	990059
V	12-14-16-18-22	Standard	-	-	ok	ok	1,100	990034
V	28	Standard	-	-	ok	ok	0,090	252965



Virax, French manufacturing

Located in Epernay, the Capital of the Champagne region, the Virax company was formed about a century ago with the famous "Virax threader" that « Turns around the Axis ». The production centre now extends over more than 25 000 sqm.

2525: Mini crimping jaws for M21+/ML21+

Dedicated to the Viper® M21+/ML21+ press fitting machine.

Extremely compact and light, allows for crimping in narrow places and between collectors. Made in tempered steel, resistant to heavy-stress and corrosion.

5 year guarantee (except profile).

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.





Ø mm	Profile	Kg	Ref.
16	G	1,800	252529
20	G	1,800	252530
26	G	1,800	252531
32	G	1,800	252532
40	G	1,800	252556
12	М	1,800	252507
15	M	1,800	252508
18	M	1,800	252509
22	M	1,800	252510
12-15-18-22	М	8,800	252595
12	RF	1,800	252545
16	RF	1,800	252546
18	RF	1,800	252547
20	RF	1,800	252548
12-16-20	RF	5,500	252590
25	RF	1,800	252549
32	RF	1,800	252550
14	TH	1,800	252512
16	TH	1,800	252514
18	TH	1,800	252516
20	TH	1,800	252517

Ø mm	Profile	Kg	Ref.
25	TH	1,800	252518
26	TH	1,800	252519
16-20-26	TH	5,500	252591
32	TH	1,800	252520
40	TH	1,800	252521
16	U	1,800	252523
18	U	1,800	252524
20	U	1,800	252525
25	U	1,800	252526
16-20-25	U	5,500	252592
32	U	1,800	252527
40	U	1,800	252528
12	V	1,800	252500
14	V	1,800	252501
15	V	1,800	252502
16	V	1,800	252503
18	V	1,800	252504
22	V	1,800	252505
12-14-16-18-22	V	8,800	252593
12-15-18-22-28	V	8,800	252594
28	V	1,800	252506

2530 - 2531 : Crimping Jaws for Models P10 / P22+ / P25+ / P30+

Adaptable to all currently available machines. 20 % harder than traditional jaws.

Very high strength steel (33 HRC). Strength tests performed with a pressure of between 12T and 15T applied 10,000 times. 5 year guarantee (except profile).

View all systems compatible with VIRAX inserts and clamps at the end of the catalogue.

- * Original Uponor. Crimping ring must be used with the activator jaw 253110. ** Activator jaw for ref. 253126, 253127, 253128, 253129.





4 CONNECTION / ASSEMBLY

Ø mm	Profile	Kg	Ref.
16	G (Geberit Original)	1,900	253130
20	G (Geberit Original)	1,900	253131
26	G (Geberit Original)	1,900	253132
32	G (Geberit Original)	1,900	253133
40	G (Geberit Original)	1,900	253134
50	G (Geberit Original)	1,900	253135
12	Н	1,900	253090
14	Н	1,900	253091
16	Н	1,900	253092
20	Н	1,900	253095
12-16-20	Н	7,000	990113
25	Н	1,900	253096
26	Н	1,900	253097
32	Н	1,900	253098
12	HA	1,900	253102
16	HA	1,900	253104
20	HA	1,900	253105
26	HA	1,900	253106
16-20-26	HA	7,400	990062
32	HA	1,900	253107
40	HA	1,900	253108
12	M	1,900	253051
14	M	1,900	253050
15	M	1,900	253052
16	M	1,900	253059
18	M	1,900	253053
22	M	1,900	253054
28	M	1,900	253055
12-15-18-22-28	M	10,200	990056
35	M	1,900	253056
42	M	1,900	253057
54	M	1,900	253058
12	TH	1,900	253001
14	TH	1,900	253002
15	TH	1,900	253003
16	TH	1,900	253004

Ø mm	Profile	Kg	Ref.
17	TH	1,900	253005
18	TH	2,040	253006
20	TH	1,980	253007
25	TH	1,900	253008
26	TH	1,900	253009
16-20-26	TH	6,900	990035
32	TH	1,900	253011
40	TH	1,900	253012
50	TH	1,900	253013
63	TH	4,856	253017
14	U	1,900	253111
16	U	1,900	253112
18	U	1,900	253113
20	U	1,900	253114
25	U	1,900	253115
16-20-25	U	6,300	990057
32	U	1,900	253116
40	U	1,900	253117
50	U	1,900	253118
63	U	5,030	253119
63	U*	2,300	253126
75	U*	2,640	253127
90	U*	3,310	253128
110	U*	3,890	253129
63-110	U**	2,430	253110
12	V	1,900	253060
14	V	1,900	253061
15	V	1,900	253062
16	V	1,900	253063
18	V	1,900	253064
22	V	1,900	253065
12-14-16-18-22	V	10,500	990036
28	V	1,900	253066
35	V	1,900	253067
42	V	1,900	253068
54	V	1,900	253069




www.virax.com


Simple, quick and easy to use. Browse and download our online catalogue, Discover the new products, Find a point of sale, Subscribe to our newsletter, Ask for an appointment, In just a few clicks!



For heating floors and pipe networks installation in PEX series 5 pipe, in all situations.







PIEZO TORCH

5200 : Piezo Propane Torch

Advantages


Piezo-electric ignition. Ergonomic, comfortable handle. Gas flow control knob.

Threaded nipple for attaching straight and swivel couplings. M 16 x 1.5 left thread for France, 3/8" left for other countries.

Range of eight interchangeable burners.

Nickel-plated steel burner provides excellent wind resistance.

Brass burner body, nickel finish.







5205: HM Piezo Propane Torch

Piezo-electric ignition, torch shuts off automatically when the handle is released. Handle directly controls the gas supply and ignition of the flame and is designed to avoid any risk of accidental ignition. Nickel-plated steel burner. Range of eight interchangeable burners. Ergonomic, comfortable HM handle. Brass burner body, nickel finish. Gas flow control knob.

Composition	Connection "	Kg	Ref.
Swivel coupling, Piezo HM Handle	M 16 x 1,5	0,480	520500
Swivel coupling, Piezo HM Handle, Turbojet Burner Ø 18 mm	M 16 x 1,5	0,590	520501
Adjustable pressure regulator 1,5 à 4 bar, swivel hose 4 m, Piezo HM Handle, Turbojet Burner Ø 18 mm	M 16 x 1,5	1,400	520504
Swivel coupling, Piezo HM Handle	Left 3/8 "	0,470	520510
Swivel coupling, Piezo HM Handle, Turbojet Burner Ø 18 mm	3/8" Left	0,720	520511





5200 : Piezo Needlepoint Burner for Piezo Torches 5200/5205

Pointed flame.

TIP: Propane gas is to be preferred to butane because at 0 °C:

- Butane produces no pressure,
- Propane provides a pressure of 4 bar.



Nozzle Ø int. Mm	Flow rate kg/h 3 bar	Type of gas	Pipe Ø mm tin solder	Pipe Ø mm P or Ag solder	Energy supplied kJ/h at 4 bar	Kg	Ref.
11	0,120	Butane or Propane	22	-	5500	0,300	520011
14	0,180	Butane or Propane	32	16	8200	0,305	520012
18	0,410	Butane or Propane	35	22	18800	0,240	520013
22	0,560	Propane	42	32	25700	0,300	520014

5200 : Piezo Turbojet® Burner for Piezo Torches 5200 / 5205

Wrap-around flame.

TIP: Propane gas is to be preferred to butane because at 0 °C:

- Butane produces no pressure,
- Propane provides a pressure of 4 bar.



Nozzle Ø int. Mm	Flow rate kg/h 4 bar	Type of gas	Pipe Ø mm tin solder	Pipe Ø mm P or Ag solder	Energy supplied kJ/h at 4 bar	Kg	Ref.
13	0,210	Propane	32	16	9600	0,290	520020
18	0,460	Propane	35	22	21100	0,240	520021
22	0,710	Propane	>42	42	32300	0,315	520022

5200: Piezo Gyroflam® Burner for Piezo Torches 5200/5205

Produces a flame that fully wraps around a pipe. Ideal for quick brazing.

TIP: Propane gas is to be preferred to butane because at 0 °C:

- Butane produces no pressure.
- Propane provides a pressure of 4 bar without any difficulty.



Description	Type of gas	For Ø max. mm	Kg	Ref.
Gyroflam brazer for Piezo torch	Propane	22	0,270	520025



Safety, one of the top concerns of Virax

Safety throughout the site is at the heart of Virax's concerns:

Emergency situations, incidents and accidents are avoided through a prevention process. The target is zero accident.

Mitigate, and whenever possible eliminate, nuisances and risks in terms of occupational health and safety for all staff and interveners.

Focus on safety equipment.

STANDARD TORCH

5210 : Standard Propane Torch X 200

Operates at full capacity when the trigger is pressed, reducing to a simple (adjustable) pilot flame when released. Threaded nipple for connecting straight or swivel couplings.

Range of seven interchangeable burners.

Smooth, easy to operate on/off trigger.

General control valve. Air ring for soft flame.

Composition	Connection "	Kg	Ref.
Swivel coupling, X 200 Handle	M 16 x 1,5	0,490	521000
Swivel coupling, X 200 Handle, Turbo 007 Burner	M 16 x 1,5	0,830	521050
1,5 to 4 bar adjustable pressure regulator, 4 m swivel hose, X200 handle, Turbo burner 007	M 16 x 1,5	1,460	521060
Swivel coupling, X 200 Handle	Left 3/8 "	0,500	521001



5210 : Needlepoint Burner for Standard Torch with handle X 200

Pointed flame.

TIP: Propane gas is to be preferred to butane because at $0 \,^{\circ}$ C:

- Butane produces no pressure,
- Propane provides a pressure of 4 bar without any difficulty.





Description	Nozzle Ø int. Mm	Flow rate kg/h 3 bar	Type of gas	Pipe Ø mm tin solder	Pipe Ø mm P or Ag solder	Energy supplied kJ/h at 4 bar	Kg	Ref.
Dard 81	9	0,060	Butane or Propane	16	-	2700	0,115	521010
Dard 82	17	0,290	Butane or Propane	22	16	13300	0,150	521011
Dard 87	18	0,420	Propane	35	22	19300	0,186	521012

5210: Turbojet® Burner for Standard Torch with Handle X 200

Wrap-around flame.

TIP: Propane gas is to be preferred to butane because at 0 °C:

- Butane produces no pressure,
- Propane provides a pressure of 4 bar without any difficulty.





Description	Nozzle Ø int. Mm	Flow rate kg/h 3 bar	Type of gas	Pipe Ø mm tin solder	Pipe Ø mm P or Ag solder	Energy supplied kJ/h at 4 bar	Kg	Ref.
Turbo burner 007	18	0,480	Propane	42	32	22000	0,195	521020
Turbo burner 008	22	0,740	Propane	> 42	42	34000	0,275	521021




5210 : Gyroflam® Brazer for Standard Torch with Handle X 200

Produces a flame that fully wraps around the pipe. Ideal for quick brazing.

WARNING: Never attach this accessoy to a Piezo handle, or you may destroy the flint.

TIP: Propane gas is to be differnet to butane because at 0 °C:

- Butane produces no pressure.
- Propane provides a pressure of 4 bar without any difficulty.



Description	Burner	Type of gas	Pipe Ø max. mm	Kg	Ref.
990	87 or 007	Propane	25	0,090	521030
997	008	Propane	54	0,150	521031

GP TORCH

5212: GP Standard Torch

Soft soldering up to Ø 42 mm. Hard soldering (40% silver) up to Ø 28 mm.

Needlepoint burner Ø 18 mm. Ergonomic handle.

Description	Kg	Ref.
GP air-propane torch	0,400	521200



XB III

5215: Autonomous Propane/Butane Torch XB III

Advantages

Can be used at very low temperatures (approx. -15°C). Gas supply: 90 min. Works in any position.

Immediately usable in any position, for soft and hard soldering (Ø 14 mm), bending and shrinking plastic, annealing pipes, loosening rusted nuts and unfreezing pipes.




Soft soldering : Ø 54 mm.

Hard soldering (40% -Ag) : Ø 14 mm.



Description	Type of ignition	Capacity gas	Autonomy	Kg	Ref.
Torch + cardridge	Piezo	210g - 380ml	1h30	0,610	521560
Torch only	Piezo	-	-	0,190	521562
Cardridge	-	210g - 380ml	1h30	0,360	521516



5215: Autonomous Torch XB III Display

Display containing 8 Piezo ignition XB III torches.





Description	Type of ignition	Capacity gas	Autonomy	Kg	Ref.
8 x Torch + cardridge	Piézo	210g - 380ml	1h30	5,700	521565

MAPP® TORCH

5217: MAPP® Gas Torch

Advantages

Easy and fast use in all positions. Long operating time up to 2.50 hrs. Very broad range of operating temperatures: -20°C to 49°C.

Torch running on MAPP® gas for higher performance, reaching temperatures up to 2400°C, allowing to work in ambient temperatures from -20°C to 49°C.

Easy to use with its ergonomic handle, light weight, Piezo lighting and can be used in all positions.

Safe work with its on/off trigger protected in case of shock, its accurate flow adjustment and safety valve for safe cartridge changing.

Interchangeable tip, with anti-tripping for launching loose. Connection 1 "(US)

Gas torch available alone or in a kit with gas cartridge.

Also offered in case with 2 gas cartridges (ref. 521740) and 2 additional tips (ref. 521741).







Description	Capacity gas	Autonomy	Soft brazing	Hard brazing	Supplied with	Kg	Ref.
MAPP® Pro kit	399,7g - 788ml	2.5 hrs	Ø 54mm max	Ø 18mm max	MAPP® extra-wide Turbojet® burner	1,180	521735
MAPP® Pro gas torch alone	-	-	Ø 54mm max	Ø 18mm max	MAPP® extra-wide Turbojet® burner	0,330	521720
MAPP® gas cartridge	399,7g - 788ml	2.5 hrs	-	-	-	0,850	521700
Brazing MAPP® Pro case	2 x 399,7g - 788ml	2 x 2h30	Ø 54mm maxi	Ø 18mm maxi	MAPP® extra-wide Turbojet® burner	3,475	521740
Multifunction MAPP® Pro case	2 x 399,7g - 788ml	2 x 2h30	Ø 54mm maxi	Ø 18mm maxi	MAPP® extra-wide Turbojet® burner, MAPP® extra-thin needle-point burner, MAPP® hot air burner	3,765	521741

5217: Tip for MAPP® Pro Torch

Broad range of interchangeable tips for the MAPP® Pro torch.

Extra-thin needle-point burner: Soft welding, precise and stable flame.

Extra wide Turbojet® burner: Strong welding, cyclone effect for even and fast heating. Hot air burner head: Stripping and shrinking work, powerful hot air flow and resists to wind. Soft flame burner head: Shrinking and heating work (soft welding Ø 22 mm), soft and powerful wind-proof flame.







Description	Soft brazing	Hard brazing	Kg	Ref.
MAPP® extra-thin needle-point burner	Ø 10 mm max	-	0,090	521721
MAPP® extra-wide Turbojet® burner	Ø 50 mm max	Ø 18 mm max	0,105	521724
MAPP® hot air burner	-	-	0,210	521725
MAPP® soft flame burner	Ø 22 mm max	-	0,120	521726

SOLDERING IRON

5240 : Soldering Iron - X 100 Handle

Gradual flame control.

Threaded nipple for connecting straight or swivel couplings.

Malleable cast iron combustion chamber.

Optimum conservation of heat. Ergonomic handle.

3 types of electrolytic copper swivel tips providing 360 $^{\circ}$ adjustment.

Stainless steel burner.

Nipple for Ø int. 6 mm hose.

Composition	Connection "	Kg	Ref.
Swivel coupling, X 100 handle	M 16 x 1,5	0,340	524000
Swivel coupling, X 100 handle, Burner and tip 300	M 16 x 1,5	1,040	524054
Fixed 2 bar pressure regulator, 4 m swivel hose, X 100 handle, Burner and Tip 300	M 16 x 1,5	1,950	524070





5240 : Burner and Tip for X 100 Handle Soldering Iron

 * fits the Piezo soldering iron, the new model X 300 handle soldering iron (5241) and the new model X 100 handle soldering iron (5240).

Description	Kg	Ref.
New model burner without tip	0,440	524010
Tip 250 (new model sold in pairs with screws)*	0,530	523020
Tip 300 (new model sold in pairs with screws)*	0,645	523021
Tip 400 (new model sold in pairs with screws)*	0,805	523022





Virax supports future professionals

Virax helps teachers promote the industry to students. Every year, Virax and teachers create a competition to test the skills of future graduates in a fun way. The best students win prizes to help them get started in their new profession.





5230: Display Box of Tips 300

Display box containing 15 tips 300 (523021).

Kg	Ref.
5,610	523029





5218: Autonomous Soldering Iron

Advantages

Handy with its integrated gas cartridge.

Operating time: up to 90 minutes with a single cartridge. Simple to use: piezo lighting and usable in all positions.

Very light, less than 500 g.

Soldering iron to be used everywhere, in all work positions and weather conditions. Autonomous and easy to use with its interchangeable gas cartridge.

Ergonomic **Titanium** / **Aluminium** handle limiting risks of burns while being very sturdy. Accurate, with flame adjustable with a knob, the tip reaching a temperature of 560°C promptly.

Supplied in a case with 2 gas cartridges.







Description	Type of ignition	Capacity gas	Autonomy	Kg	Ref.
Autonomous soldering iron kit	Piezo	2 x 60g - 110ml	2 x 1.5 hrs	2,500	521850
Copper tip	-	-	-	0,250	521855
Cartridge	-	60g - 110ml	1.5 hrs	0,115	521860



Virax and the environment

Virax is committed to environmental protection and sustainable development, as demonstrated by our ISO certification 14001: 2015 for our environmental management system.

Compliance with the REACH Directive no.1907/2006.

Low energy consumption.

Dematerialisation of documentary flows and printing control.

Waste control and reclaiming.

Packaging materials recycled in a partnership with Eco Emballage.

Anticipation of pollution risks.

WATERPROOFER TORCH

5250 : Waterproofer's Torch - X 400 Handle

General shut-off valve. Constant pilot light adjustment.

Heat and bitumen-resistant handle. Threaded nipple for connecting straight or swivel couplings. Rounded handle for a good, easy grip even without gloves. Set of two interchangeable burners fitting onto single connecting tubes. All burners fitted with an adjustable stand. Long trigger for easy operation with or without gloves.

Tip: Use only with propane gas.

Operating pressure: 4 bar.

Composition	Connection "	Kg	Ref.
Swivel coupling, X 400 handle	M 16 x 1,5	0,540	525000
X 400 handle, Connecting tube 240 mm, Jet 3 burner Ø 42 mm	M 16 x 1,5	1,080	525070
X 400 handle, Connecting tube 240 mm, Jet 4 burner Ø 52 mm	M 16 x 1,5	1,080	525072
4 bar fixed pressure regulator, Waterproofer 10m straight hose, X 400 handle	M 16 x 1,5	2,130	525090



5250 : Burner for X 400 Handle Waterproofing Torches

Circular burner.



Description	Nozzle Ø int. Mm	Flame Ø mm	Flame L mm	Flow rate kg/h 4 bar	Energy supplied kJ/h at 4 bar	Kg	Ref.
Jet 3	42	60	600	4,1	179500	0,270	525013
Jet 4	52	90	800	7,9	347000	0,370	525014

$5250: \mbox{Connecting Tubes for Jet Burners 3-4 for X 400 Handle Waterproofing torches}$

Description	L mm	Kg	Ref.
Single 31	240	0,140	525021
Single 33	350	0,190	525022
Single 34	660	0,280	525023





Virax, a French story

Nearly a century ago, in 1920, two Frenchmen established Virax by launching its famous "Virax threader", the threader that "Turns around the Axis". Nowadays, it is still from Epernay, at the heart of the Marne and Champagne country, that Virax manufactures and distributes its professional product ranges in more than 40 countries.

PRESSURE REGULATOR

5260: Propane Pressure Regulator

Stepless pressure adjustment from 1.5 to 4 bar. French version provided with couplings to NF EN 560. 4 different international versions, one of them is in accordance with DIN 4811/1. Supplied with a swivel coupling.



Description	Туре	Type of gas	Cylinder coupling	Male hose coupling	Flow rate kg/h	Kg	Ref.
Adjustable 1,5 to 4 bar	NF (France)	Propane	Left Female 21,7 x 1,814	Left M 16 x 1,5	-	0,410	526000
Adjustable 1,5 to 4 bar	А	Propane	Left Female 21,7 x 1,814	Left 3/8"	-	0,410	526001
Fixed 2 bar	For soldering iron	Propane	Left Female 21,7 x 1,814	Left M 16 x 1,5	8	0,350	526010
Fixed 4 bar	For waterproofer's torch	Propane	Left Female 21,7 x 1,814	Left M 16 x 1,5	15	0,350	526020

ELECTRIC SOLDERING MACHINE

5270: Cobraz® Electric Soldering Machine

Advantages

Electrically operated (230 V): for safe soldering (no flame), without damaging or annealing the copper pipe. Safe and Easy to use: No flame. No gas. Immediately operational.

Easy to carry: comes complete with carrying case with space for storing pliers and cables. Supplied with:

- 2 cylindrical electrodes,
- 1 bottle of Virax Smartflux 250g,
- 1 coil of Ø 2 mm soft braze 250 g,
- 1 wire brush.







Туре	Capacity	Cable m	Secondary voltage V	Current intensity	Power W	Kg	Ref.
Cobraz 28	Soft soldering: Ø 6 - 28 mm	3,00	5,2	10	840	9,930	527022

5270 : Cobraz® Accessories

Description	Туре	Kg	Ref.
Pair of electrodes with holder	Prismatic	0,090	527030
Pair of electrodes with holder	Rod / cylindrical	0,120	527032
Pairs of electrodes without holder	Rod / cylindrical	0,020	527038
5 x Pairs of electrodes without holder	Rod / cylindrical	0,260	527033
Soft soldering Ø 2 mm - 250 g	-	0,250	528346
Smarflux: Brazing paste for preparing the braze of copper pipes	-	0,280	528420



RUBBER HOSE

5280 : Propane/Butane Rubber Hose

In accordance with NF EN 559. Ø 6 X 12 mm.







Packaging	Lm	Connection "	Connection "	Kg	Ref.
PVC box	4,00	Left M 16 x 1,5	Swivel coupling, Straight coupling	0,580	528013
Plastic bag	10,00	Left M 16 x 1,5	2 straight couplings	1,400	528037
Plastic bag	4,00	Left 3/8"	Swivel coupling, Straight coupling	0,570	528012
Dispenser box	40,00	-	Supplied without couplings with 20 hose clamps	6,230	528040
Bulk	20,00	-	Supplied without couplings	2,600	528030

COUPLING

5282 : Swivel Coupling

Swivel nipple coupling. Avoids the hose wrapping around the handle. For fitting bear directly onto the nipple. In accordance with NF EN 560.

Thread size	Kg	Ref.
M 16 x 1,5 Left	0,055	528210
3/8" Left	0,060	528211





Virax is on Facebook!

@viraxofficial

GAS CYLINDER - ACCESSORIES

5282: Gas Cylinder - 1,6 kg

Supplied empty. In accordance with EN 1442. 528265: Purge. Stop valve.

Description	Kg	Ref.
Gas cylinder - 1,6 kg	4,050	528260
Tapered stem valve	0,320	528265
Straight filling connector - NF connexion	0,145	528270





5282: Flint Ignitor

Description	Kg	Ref.
1 x	0,070	528280
20 x	1,415	528282
Box of 6 packs of 6 spare flints	0,065	528285



5282: Flame Shield

50% more efficient.1 side glass fibre (guaranteed asbestos-free), 1 side aluminium. Very good heat resistance: protects ceilings, floors, walls and their finishes during welding. Reduces the risk of fire. For use with commercially available propane and butane torches. Ideal for maximum protection when working in corners. Cuts and folds easily to any shape.



Set of 2	Size mm	E mm	Kg	Ref.
1 x	280 x 200	15	0,290	528290
20 x	280 x 200	15	7,200	528294

5283: Soft Solder

Reel of solder. Good fluidity, good wetting and bonding characteristics. For soft soldering copper hot and cold water supply pipes. Particularly recommended for soft soldering in conjunction with the Cobraz 28 and Cobraz 54 electric soldering machines.

Alloy contains Selenium for excellent capillary attraction. Contains no Nickel, Lead nor antimony. Melting point: 210°C. Heat resistant up to 110°C. Solder strength 52 N/mm².

Ø mm	Kg	Ref.
2	0,250	528346





FLUX

5284: Universal Brazing Flux


Ripoflux: Flux paste for silver and phosphorus-copper brazing. Ensures good wetting of copper and its alloys, when melted, for producing high-quality brazed joints.

Smartflux: For preparing the solder of copper domestic hot and cold water pipes: changes colour when soldering temperature is reached, non flowing, easy brush application. Particularly recommended for use with the Cobraz 28 and Cobraz 54 electric soldering machines.


Description	Capacity	Kg	Ref.
Ripoflux	125 ml	0,240	528400
Smartflux	250 g	0,280	528420











FREEZER

2210 : Siberia® Electric Pipe Freezer 2"

Advantages

Economical: no gas cylinder required.

Easy to carry: thanks to its wheels and folding handle.

Reduced freezing time: for faster intervention.

Simple to use with the thermometer integrated to its freezing

heads.

The Siberia® allows radiators and valves to be replaced without emptying the water from the heating system.

It quickly forms an ice plug in the pipe, without polluting the environment thanks to the effectiveness of R290 gas: environmentally friendlier than R404A refrigerant but without compromising on performance.

A thermometer is integrated to the freezing heads to monitor the freezing process. Head integrated tightening screws for easier fastening.

Technical features:

Motor: 230V ~50Hz

Refrigerating power: 309W at -25°C

Protection rate: IP 20 Coolant: R290 55g







Description	Copper tube ext. Ø mm	Copper tube ext. Ø "	Iron tube ext. Ø ext. "	Kg	Ref.
Siberia® Electric Pipe Freezer	12 - 14/15 - 16 - 18 - 22 - 28 - 35 - 42	1/2 - 5/8 - 7/8 - 1.3/8	1/4 - 3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 2	40,000	221070

Capacities

Copper Tube: Ø 10 mm - 3/4" to Ø 54 mm - 2.1/8".

Iron Tube: Ø 1/8" to Ø 2".

Delivered with

16 adaptors diameter 12 - 14/15 - 16 - 18 - 22 - 28 - 35 - 42 (8 pairs), 1 bottle of thermo-conductive paste (ref. 221069).

2210 : Accessories for Siberia® Pipe Freezer

Thermo-conductive paste: for better cold conduction and improved pipe freezing. Adaptors: sold in pairs.







Description	Standard / Option	Copper tube ext. Ø mm	Copper tube ext. Ø "	Iron tube ext. Ø ext. "	Kg	Ref.
Thermo-conductive paste	Supplied with Siberia®	-	-	-	0,130	221069
2 x Adaptors GR I	Option	10	3/8	1/8	0,385	221025
2 x Adaptors GR II	Supplied with Siberia®	12	1/2	-	0,755	221026



Description	Standard / Option	Copper tube ext. Ø mm	Copper tube ext. Ø "	Iron tube ext. Ø ext. "	Kg	Ref.
2 x Adaptors GR III	Supplied with Siberia®	14 / 15	-	1/4	0,345	221027
2 x Adaptors GR IV	Supplied with Siberia®	16	5/8	-	0,340	221028
2 x Adaptors GR V	Supplied with Siberia®	18	-	3/8	0,335	221029
2 x Adaptors GR VI	Option	20	3/8	-	0,320	221030
2 x Adaptors GR VII	Supplied with Siberia®	22	7/8	1/2	0,290	221031
2 x Adaptors GR VIII	Option	-	1	-	0,280	221032
2 x Adaptors GR A	Supplied with Siberia®	28	-	3/4	0,675	221033
2 x Adaptors GR B	Option	-	1.1/8	-	0,695	221034
2 x Adaptors GR C	Option	32	1.1/4	-	0,645	221035
2 x Adaptors GR D	Supplied with Siberia®	35	1.3/8	1	0,575	221036
2 x Adaptors GR F	Option	-	-	1.1/2	0,315	221038
2 x Adaptors GR E	Supplied with Siberia®	42	-	1.1/4	0,430	221037
2 x Adaptors GR G	Option	54	2.1/8	-	0,190	221039

GAS THIGHTNESS CONTROLLER

2620 : Gas Tightness Controller

Advantages

Very compact: holding in only one hand and being able to be transported easily.

Strong: very resistant composite material.

Ergonomic: easily transportable in its storage bag.

Modern design.

Checks the tightness seal of a gas installation in a pressure less than 50 mbar. its automatic limiting device of pressure avoids any risk of error.

Dimensions mm: 165 x 80 x 80.

Light: 1.280 kg. Supplied with: - 1 coupling hose,

- brass couplings:1/2 G female, 7/8 G male, propan 20/150 male,
- box of seals,
- 1,5 V battery (LR6/AA),
- protective carrying bag.







Pression mbar	Coupling "	Resolution mbar	Kg	Ref.
0 to 60	1 fitting for gas cooker, 1/2 G female, 7/8 G male gasmeter outlet connection, 1 male propan fitting 20/150	1	1,280	262080



Virax, French manufacturer

In its Production Centre extending over more than 25,000 m² situated in Epernay, France, Virax manufactures tools and machines designed by its R&D Center to meet the requirements of professionals. Plasturgy, machining, milling, grinding, assembly and painting, all these activities are performed on site for manufacturing control and quality.

2626: Leak Detector

For testing all gas or compressed air circuits. Replaces soapy water for detecting leaks in gas installations. Will show up even the smallest leaks when sprayed on the surface to be checked.

Packaging		Ref.
1 spray can - 400 ml	0,480	262630



TEST PUMP

2620 : Manual Test Pump

Advantages

EA85 anti-limestone patent: to avoid blockages caused by over-hard water.

Easy to use: for pumping, testing and bleeding with a single button.

Small size for the tightest of locations.

3 pump models for your seal tests (for leak testing on water installations- plumbing, individual central heating, etc.).

Virax EA85 anti-limestone patented system: Prevents blockages due to hard water, or other deposits, on the ball in the piston (50 bar models only).

Plastic tank: light and shock resistant (max.: 4.3 kg).

Accurate result with a 1.6 class manometer. Easier reading with 1 bar grading.

High pressure hydraulic hose (1.5 m). Practical implementation.

Nylon strainer (filter) on intake to block particles exceeding 0.1 mm diameter to protect the pump mechanism and the customer's installation against dirt.

Soft Touch® ergonomic lever for working comfortably.

Easy to carry thanks to a lever locking mechanism.

Fluids accepted: water, Glycol (requires rinsing after use), oil (requires rinsing after use).







Description	Presssure bar	Coupling "	Tank capacity L	Kg	Ref.
Manual test pump	50	1/2 - 3/8	5	4,200	262035
High volume test pump	50	1/2 - 3/8	10	4,100	262015
High pressure test pump	100	1/2 - 3/8	10	4,290	262005



Virax Experts

Would you like technical assistance?

Our team of experts is at your disposal to provide you with tips and recommendations on how to get the most out of your Virax products.

From 8.00 am to 12.15 pm and from 1.45 pm to 5.00 pm, Monday to Friday (4.30 pm): +33 (0) 3.26.59.56.82

Exploded views and manuals: www.virax.com, Documentation section.



2620 : Electric Test Pump

Advantages

Sturdy: Structure and handle in lightweight ABS.

Powerful: 6 l/min - 40 bar.

Autonomous: Can suck fluid from a tank.

For leak testing on water installations (plumbing, individual central heating...).

Fast and effective work.

Accurate results with its glycerine manometer with 1 bar grading.

Easy to carry thanks to its compact design and carry handle.

Shock and corrosion resistant.

Self-extracting up to 1 m if no water intake available.

Fluids accepted: water, Glycol (requires rinsing after use).







Description	Presssure bar	Coupling "	Self-extracting capacity m	Kg	Ref.
Electric test pump	40	1/2	1	18,000	262070

GRINDING TOOL

2621: Rodor® Tap Reamer

Tap seat grinding tool. Spring holds cutter in contact with the tap seating. Cutter with serrated underside, screws on to cutter-holder.

M7 thread. Taper ensures a correct fit on the head of the tape.

Cutter-holder no.1: internally and externally threaded tapered cone.

Cutter-holder no.2: triple cone: for servicing of bath, basin, kitchen and bib taps.

Characteristic	Kg	Ref.
Cutter-holder no.1 and cutters Ø 11 - 13 - 14 - 15 - 16 - 18 - 20 - 22 mm	0,305	262191
Cutter-holder no.1	0,235	262181
Cutter-holder no.2	0,390	262182





2621 : Cutter For Rodor Tap Reamer

Cutter with serrated underside, screws on to cutter-holder. M7 thread for cutter-holders n° 1 & 2.



Cutter-holder	Ø mm	Kg	Ref.
no. 1, 2, 3 or 5	11	0,005	262111
no. 1, 2, 3 or 5	12	0,005	262112
no. 1, 2, 3 or 5	13	0,005	262113
no. 1, 2, 3 or 5	14	0,010	262114
no. 1, 2, 3 or 5	15	0,010	262115
no. 1, 2, 3 or 5	16	0,010	262116
no. 1, 2, 3 or 5	18	0,010	262118
no. 1, 2, 3 or 5	20	0,015	262120

Cutter-holder	Ø mm	Kg	Ref.
no. 1, 2, 3 or 5	22	0,020	262122
no. 1, 2, 3 or 5	23	0,020	262123
no. 1, 2, 3 or 5	26	0,025	262126
no. 1, 2, 3 or 5	30	0,040	262130
no. 1, 2, 3 or 5	17	0,010	262117
no. 1, 2, 3 or 5	24	0,025	262124
no. 1, 2, 3 or 5	32	0,040	262132

2645 : Recti 9® Tap Reamer Tool Set

Tap seat refacing tool. Cutter produces a high quality ground finish. M8 thread. Brass components. Micrometric feed control. Permanent, precise grinding control.

Characteristic	Kg	Ref.
Flat cutters: Ø 15 - 16 - 24 mm - Tapered cutter: Ø 15 mm - 3 Adaptors (264501, 264502, 264503)	2,100	264550
Flat cutters: Ø 15 - 16 - 18 - 19 - 21 - 24 mm - Tapered cutter: Ø 15 mm - 9 Adaptors (264501 to 264509) - 3 Extensions (264540, 264542, 264544)	3,600	264560
without accessories	0,450	264500





2645 : Accessories for Recti 9® Tap Reamer Tool

Ref. 264510, Ref. 264511, Ref. 264513, Ref. 264514 for fitting onto Porcher single hole tap.



Description	Ø mm	L mm	Kg	Ref.
Adaptor	3/8" - 17/150	-	0,210	264501
Adaptor	1/2" - 18/150	-	0,215	264502
Adaptor	3/4" - 20/150	-	0,225	264503
Adaptor	19/150 - 21/150	-	0,220	264504
Adaptor	23/150 - 26/150	-	0,225	264505
Adaptor	18/125 - 19/125	-	0,215	264506
Adaptor	20/125 - 21/125	-	0,220	264507
Adaptor	23/125 - 25/100	-	0,230	264508
Adaptor	20/100 - 22/100	-	0,220	264509
Adaptor	□18/125	-	0,170	264510
□Adaptor	□18/150	-	0,165	264511
Extension	-	10	0,015	264540

		-		
Description	Ø mm	L mm	Kg	Ref.
Extension	-	20	0,020	264542
Extension	-	40	0,035	264544
Cutter	13	-	0,010	264513
Cutter	14	-	0,010	264514
Cutter	15	-	0,010	264515
Cutter	16	-	0,007	264516
Cutter	18	-	0,008	264518
Cutter	19	-	0,010	264519
Cutter	21	-	0,012	264521
Cutter	24	-	0,015	264524
Tapered cutter	15	-	0,011	264535

BOILER & RADIATOR LIFTS

2636: Radiator Lift

Advantages

Self-braking winch for loads up to 150 kg. An extension to adapt to vertical radiators. Folding handle and winch, practical for storage.

Integrated extension ideal for installing vertical radiators (does not require any tools for mounting).

Integrated telescopic radiator lock for more safety and stability during movement.

Deep tray (22 cm) to accommodate most radiators.

Folding arm and winch to save space during storage.

New self-braking winch for more safety and less effort during handling operations.

Numerous protective rubber strips.

- Lifting Height: 0.57 m,
- Overall Width: 0.68 m.

Description	Kg	Ref.
Radiator lift	40,000	263605







2636 : Cylinder / Water Heater Lift

Advantages

Safe and effortless thanks to the self-braking winch.

Strong: load up to 150 kg.

Space saving thanks to the folding arms.

Strong belt to hold the water heater.

Folding arm and winch to save space during storage.

New self-braking winch for more safety and less effort during handling operations.

Integrated extensionfor installation in high location (does not require any tools for mounting). Accurate: 4 balls under the forks for accurate positioning.

Integrated extension for installation in high location (does not require any tools for mounting). Numerous protective rubber strips.

- Overall width: 0.65 m.

Specific boiler lift accessories:

- Horizontal Cradle*.
- Radiator adaptor*: enables a radiator to be installed from a water heater lift.

Built for safety and stability when moving blocks-telescopic radiator.

Deep tray (19 cm) to accommodate the majority of radiators.

*Compatible only with the cylinder/ water heater lift ref. 263620








Description	Max load kg	Max lifting height without / with extension m	Kg	Ref.
Cylinder / water heater lift	150	1,17 / 1,90	42,000	263620
Horizontal cradle*	150	1,87 / 2,32	4,000	263625
Radiator adaptor*	150	1,18 / 1,91	11,000	263626

SNAKE PIPE CLEANER

2901 : Furet Auger Pipe Cleaner

Simple, economical pipe cleaner for everyday use.

Auger Pipe Cleaner No. 4: Hot-galvanised close wound steel wire cable: very flexible able to follow very tight radius bends (less than 3 times tool diameter). Sleeve to facilitate rotation.



cable Ø mm	L cable m	Pipe Ø mm	Brush type	Kg	Ref.
no. 2 : 8	1,50	30	Steel	0,320	290120
no. 4 : 15	5,00	80	Claw 42 mm	5,900	290140

2901 : Accessories for Furet Auger







Description	For	Use	Ø mm	L m	Kg	Ref.
Extension	Furet no. 2	-	8	1,50	0,330	290121
Extension	Furet no. 4	-	15	5,00	5,400	290141
Steel brush	Furet no. 2	Finishing tool for scraping	30	-	0,015	290122
Steel brush	Furet no. 3	Finishing tool for scraping	50	-	0,035	290132
Steel brush	Furet no. 4	Finishing tool for scraping	80	-	0,300	290142
Claw	Furet no. 4	To drill through blockages	42	-	0,070	290145
Corkscrew head	Furet no. 4	To retrieve lost objects: cloths, etc	80	-	0,250	290146



Virax committed to WEEE management

As a producer, Virax has implemented a process for collecting Waste from Electrical and Electronic Equipment (WEEE) in compliance with the European Directive 2012/19/UE. In compliance with its environmental commitment, Virax organizes the management and recycling of WEEE at end of life.

PRESSURE PIPE CLEANER

2902: Pump-Action Pipe Cleaner

Advantages

2 robust non-slip Soft Touch® handles.

Single body, resistant to impact and domestic pipe cleaning products.

2 end pieces for all types of pipe cleaning, easy to put on and take off.

Professional pump-action pipe cleaner for wash hand basins, sinks, showers toilets, etc.. **Works in both pressure and suction.**

Back and forward movement facilitated by the seal protected by water resistant marine grease.

Interior seal perfectly waterproof to guarantee maximum pressure during difficult pipe cleaning operations.

Specially designed end pieces to facilitate introduction and limit flow back.

Body and end pieces resistant to domestic pipe cleaning products (caustic soda or 20% diluted hydrogen chloride based).

Co	ontents	Kg	Ref.
	1	2,100	290210
	6	12,600	290215







2900: Pair of Gloves

Designed to protect your hands against mechanical risks. 100% polyamide / Polyurethane coating. Complies with EN420 and EN388 standards (classification 4131). Size 10.

	Kg	Ref.
Ī	0,130	290000





Customer Service

For information on our products, promotions, stocks, record your orders or follow a delivery? From 8.00 am to 12.15 pm and from 1.45 pm to 5.30 pm, Monday to Friday (5 pm):

FRANCE

Phone: 03.26.59.56.78 Fax: 03.26.59.56.20 Email: client.fr@virax.com

EXPORT

Phone: +33 3.26.59.56.57 Fax: +33 3 26.59.56.70 Email: export@virax.com

Exploded views and manuals: www.virax.com, Documentation section.

2901: Pipe Cleaner Gun

Advantages

Pressure:

up to 6 bars for pipes up to Ø 100 mm.

Efficiency:

98% of energy is directed forward to free blocked pipes.

only 2% of released energy acts on the pipe walls.

Ideal for blockages far away from the siphon.

This cleaner uses the kinetic energy stored in the cylindrical body (max. 6 bar) to remove blockages formed by grease, soap, wash water, hair, paper, cloth, etc.

For cleaning domestic drainage pipes of max. internal Ø 100mm (sinks, wash hand basins, urinals, bath-thubs, etc.), as well as toilet if fitted with the optional extension (290151). Integrated manometer to measure the pressure to be applied.

Supplied in a case.

Kg	Ref.
2,800	290150







2901: Toilet Extension for Pipe Cleaner Gun

Enables toilets to be unblocked by applying the handle directly into the bowl.

Kg	Ref.
0,740	290151



MANUAL CABLE PIPE CLEANER

2905 : Closet Auger

Crank for rotation or back-and-forth movement. Plastic elbow to avoid scratching enamel. Scroll shaped jointed head. Articulated auger head. Double turnsover steel core. Carrying hook. Ref.: Telescopic shaft.

Ø mm	Max. reach cm	Kg	Ref.
12,5	85	2,400	290510
12,5	160	2,700	290520









Virax certified ISO 14001 and OHSAS 18001 since 2009

And in 2016 our Environmental Management System was acknowledged through certification in its new version ISO 14001: 2015.

2905 : Swivel Head for Closet Auger

Kg	Ref.
0.115	290512



2906 : Drum-Type Manual Pipe Cleaner

Pipe cleaner. Lacquered metal reel. Fast cable storage. Lock screw. **Adjustable anti-ejection system:** prevents untimely cable exit and loss. **Supplied with a pair of gloves.**





Contents	Pipe Ø mm	cable Ø mm	L cable m	Max. reach m	Kg	Ref.
1	25 - 50	6,40	7,50	7,50	2,075	290600
8	25 - 50	6,40	7,50	7,50	17,270	290602

2906: Accessory for Drum-Type Manual Pipe Cleaner

Tools	Ø mm	Lm	Kg	Ref.
Cable and boring gimlet	6,40	7,50	1,230	290605

2906 : Professional pipe cleaner VAL 26

Advantages

Flexible and strong cleaning cables.

Handy and light.

For use by hand or with a power drill (not supplied).

Manual cable pipe cleaner for piping Ø25-75mm, maximum cable length 10m. Supplied with cleaning cable \emptyset 7 mm, length 7.5 m, for piping Ø 25-50 mm:

- Highly flexible for fast advance in the piping, even in narrow pipe curves and elbows.
- Jointed auger for easy passage in the elbows.
- High strength, special high grade steel, with steel core.

Handy and light, only 2.7kg cable included.

Used manually for easy obstructions easy to remove.

Used with power drill (not supplied) for tough obstructions:

- Crank removable in a few seconds without tools.
- Hew adapter at the centre of the drum.
- Ergonomic Soft Touch® grip for excellent control in rotation.

Adjustable anti-ejection system: **prevents untimely cable exit and loss** inside the piping. Plastic **anti-shock** and **anti-corrosion** drum with large openings for better viewing of the cable and faster drying after cleaning.

Chuck Ø 13 mm to tighten cleaning pipes of different diameters.

Supplied with a pair of gloves.

Optional capacities with cables Ø 10 mm / length 7.5 m and Ø 8 mm / length 10 m.

Pipe Ø mm	Reach m	Kg	Ref.
25 to 50	7,50	3,350	290640







After each intervention: clean the cable and protect it against rust with pipe cleaner oil reference 290400.

2906: Cables for professional pipe cleaner VAL 26







Description	Ø mm	L m	Steel-cored	Pipe Ø mm	Kg	Ref.
Cable and articulated gimlet	7	7,50	Yes	25 to 50	1,650	290645
Cable and articulated gimlet	10	7,50	Yes	50 to 75	3,450	290646
Cable and articulated gimlet	8	10,00	No	50 to 75	2,500	290647

2904 : Pipe Cleaner Oil

Specially formulated for maintaining and cleaning pipe cleaning tools. Avoids oxidation, lubricates, disinfects and deodorises. To be applied after each pipe cleaning operation.

L	Kg	Ref.
1	1,000	290400





Customer Service

For information on our products, promotions, stocks, record your orders or follow a delivery? From 8.00 am to 12.15 pm and from 1.45 pm to 5.30 pm, Monday to Friday (5 pm):

FRANCE

Phone: 03.26.59.56.78 Fax: 03.26.59.56.20 Email: client.fr@virax.com

EXPORT

Phone: +33 3.26.59.56.57 Fax: +33 3 26.59.56.70 Email: export@virax.com

Exploded views and manuals: www.virax.com, Documentation section.

ELECTRIC CABLE PIPE CLEANER

2910 : Portable Electric Drum Type Pipe Cleaner VAL 35 / VAL 35E

Advantages

For pipes Ø 30 to 75 mm.

Highly effective thanks to its articulated gimlet (VAL 35E) on steel core cable.

Variable speed control.

VAL 35: manual cable feed and return.

VAL 35E: less effort thanks to automatic cable feed and return.

Cable: Ø 8 mm (also exists in Ø 6.3 and 9.5 mm).

Length 7.5 m (also exists in 10.5 and 15 m, depending on diameters).

Composed of a robust steel wire rolled around a 49-strand thermally treated metal core. Light alloy casing. Cable feed adjustment knob and handle to lock the cable. Simple cartridge change thanks to its specially designed chuck to adapt to different cable diameters. Motor: 230 V / 275 W / 50 Hz, Reversible right/left, 0 to 400 rpm.

VAL 35 : cable included as standard \emptyset 8 mm Lg 7,5 m ref. 291013 (non-replacable fixed auger).

VAL 35E : cable included as standard Ø 8 mm Lg 7,5 m ref. 291014 (replacable hinger auger, ref. 291026 only).





Туре	Pipe Ø mm	cable Ø mm	Feed / Return	Reach m	Kg	Ref.
VAL 35	40 - 50	8	Manual	7,50	11,300	291000
VAL 35E	40 - 50	8	Automatic	7,50	11,920	291001



2912 : Electric Drum Type Pipe Cleaner VAL 80 / VAL 80E

Advantages

Essential for any clearing on drain Ø 30 mm to 100 mm. Effective thanks to its steel-cored cable of 22,5 m, for an optimal ratio resistance/flexibility.

Powerful motor, reverse switch up to 165 trs/min.

VAL 80: manual cable feed and return.

VAL 80E: Electric cable feed and return. Clutching by automatic cable advance. Electric cable roller. Folding transportable trolley.

Electric rotation with pneumatic pedal.

Ø 9.5 mm cable composed of a robust steel wire rolled around a 49-strand thermally treated metal core. Distribution tube inside the drum to insert or remove the cable quickly.

Metal drum with opening for cleaning and lubrication, removable for transport or for changing

Can receive cables of 7.5 or 15 m, or a drum and a cable of Ø 6.3 or Ø 8 mm to work in small pipes (wash hand basin, etc.).

Motor: 230V / 50 Hz / 250W, Reversible right/left, 0 to 165 rpm.

Supplied with:

- 1 pair of gloves,
- 1 cable Ø 9,5 mm, Lg 22,50 m ref. 291214,
- 1 gimlet ref. 291213,
- 1 smooth knife Ø 38 mm ref. 291211,
- 1 toothed blade Ø 50 mm ref. 291212,
- 1 arrow head ref. 291217.







Туре	Pipe Ø mm	cable Ø mm	Feed / Return	Reach m	Kg	Ref.
VAL 80	50 - 75	9,50	Manual	22,5	36,000	291200
VAL 80E	50 - 75	9,50	Automatic	22,5	48,200	291201

2912: Pipe Cleaner Accessories VAL 80 / VAL 80E

Ref. 291223: For clearing basins, sinks, showers, etc. Adapt on VAL 80 / VAL 80E with cables ref. 291011, 291012, 291014.

Description	For	Kg	Ref.
Drum	VAL 80 / VAL 80E	6,770	291223
Troley	VAL 80	7,150	291221





Virax a daily player in environmental protection

CITEO

As a member of Citeo, an eco-organization funding the collection and sorting of paper, Virax is committed to preserving natural resources, by using recycled paper within the company and for all its advertising media, and participating in this funding via the eco-contribution.

2920 : Electric Drum Type Pipe Cleaner: VAL 90

Advantages

Specially designed for large diameter pipes, 75 to 250 mm. Effortless movement: loading wheel, tracks for going up and down stairs, ball bearing \emptyset 25 cm wheels.

Perfect result thanks to the 8 tools supplied and its steel core cable for an optimum resistance/flexibility ratio.

 \varnothing 16 mm (also exists in \varnothing 19 mm) 30 m long cable (extendible to 60 m) composed of a robust steel wire rolled around a 49-strand thermally treated metal core.

Clutching for automatic cable feed and return with motorised variable speed mechanism to facilitate cable insertion and removal.

Pneumatic pedal to activate the motor and the safety circuit breaker. Open cage drum with distributor tube to avoid knots and see the quantity of cable remaining. Integrated toolkit. Supplied with:

- 1 pair of gloves.
- 1 cable Ø 16 mm, Lg 30 m ref. 292028.
- 1 84 cm long flexible head to intervene in tight bends, siphons ref. 292015.
- 2 toothed blades to cut and scrape walls in Ø 75 or 100 mm ref. 292027.
- 1 harpoon head to start pipe cleaning and drill through deposits ref. 292011.
- 1 large corkscrew to recover objects ref. 292014.
- 1 toothed blade to cut and scrape walls in Ø 50 mm ref. 292032.
- 1 rotating saw blade for crushing branches and other materials, in Ø 100 mm ref. 292016.
- 1 spiral saw blade for crushing roots, branches and other materials, in \varnothing 75 mm ref. 292021.



Motor	Pipe Ø mm	Max. reach m	cable Ø mm	Kg	Ref.
230V / 0 to 170 rpm - 50Hz / 375 W - Reversible right/left	75 - 150	60,00	16	107,500	292030
•				•	



2931 : Cable segment pipe cleaner VAL 96QC

Advantages

'Quick Change' system: instant swapping of Ø 16 mm and Ø 22 mm cables, without tools.

Easily transportable: easy to store in a chest, cable sections are supplied in independent cages.

Continuous drive shaft: excellent protection against used water flow on the motor, as well as electrical and mechanical parts.

For Ø 50 to 150 mm piping, maximum length 70 m.

Electrical motor 750 W, right / left reversible, 690 rpm, 24 kg, IP44, maintenance-free, delivering high torque for effective pipe cleaning.

Timed belt for smooth motor power transmission. High wear resistance.

Electrical connection cable with built-in differential circuit breaker (PRCD) providing optimum protection of the pipe cleaner but also the user.

External drive jaws allowing instant cable changing; sealed, life lubricated, maintenance free

Sheathed grip for clutch and transport.

Manual cable feed for fast and accurate approach of the tool towards the plug.

Guide pipe to prevent waste water projections in the work environment.

Fastening pin securing the cable to the pipe cleaner when adding or removing a section (prevents untimely loss of the section engaged in the piping).

Feet with rubber anti-slip protection for better operating stability.


Cable sections with tempering optimized to guarantee flexibility allowing several elbows to

Metallic cable section storage and transport cage.

Simple and fast section connection / separation, T coupler for secured holding.

According to the model, special cable sections with plastic core, ideal to avoid inner cable fouling, easier to clean.

Cable sections and tools compatible with most cable segment cleaner in the market.



Capacities

Cable section \emptyset 16 mm / 2.30 m: for \emptyset 50 – \emptyset 100 mm piping, max length 40 m. Cable section \emptyset 22 mm / 4.50 m: for \emptyset 70 – \emptyset 150 mm piping, max length 70 m.







Delivered with

Guide pipe, pair of gloves, user manual.

Cable sections according to model:

- Ø 16 mm: 5 sections Ø 16 mm / 2.3 m + transport cage.
- Ø 16 mm with plastic core: 5 sections Ø 16 mm / 2.3 m + transport cage.
- Ø 22 mm: 5 sections Ø 22 mm / 4.5 m + transport cage.
- Ø 22 mm with plastic core: 5 sections Ø 22 mm / 4.5 m + transport cage.

Tool sets according to model (supplied in a case VIRABOX):

- Set of 3 tools for Ø 16 mm sections: straight spiral head Ø 16 mm (293158), bulb spiral head Ø 28 mm (293159), arrow blade head Ø 25 mm (293160), 1 uncoupling wrench Ø 16 mm (293162).
- Set of 5 tools for Ø 22 mm sections: straight spiral head Ø 22 mm (293163), bulb spiral head Ø 40 mm (293164), conical spiral head Ø 55 mm (293165), toothed knife head Ø 76 mm (293166), toothed mill head Ø 65 mm 4 blades (293168), 1 uncoupling wrench Ø 22 mm (293169).

Tips

The cable sections and tools are compatible with most pipe cleaners with a cable section Ø 16 mm / Ø 22 mm.

HIGH PRESSURE PIPE CLEANER

2932: Pro HP Cleaner-Clearer

Advantages

Mobile and complete for semi-intensive use.

Quickly wash your sites, frontage using the low pressure / high pressure lances.

Strip the toughest surfaces deep down thanks to the rotating nozzle lance.

Clean blocked pipes effectively with the 3 retro-jet nozzle.

A professional quality assembly:

- 2800 rpm motor for semi-intensive use.
- Brass axial pump and stainless steel pistons for maximum endurance.
- Automatic shut off function to preserve the motor and reduce electricity consumption.
- Non-deforming, shock-resistant PE injected hood.
- Large diameter moulded hub wheels to cross any obstacle.

High pressure washing function:

- Gun with lockable trigger.
- Sheathed HP/LP multi-jet lance.
- Rotating nozzle lance: cleaning power doubled.
- 1 pro HP hose (12 m) on roller with brake.
- 2 removable 0.6 l. detergent tanks that can be controlled separately.

Pipe cleaning function:

Cleans and unblocks all types of pipe obstructed by grease or friable materials such as grease, silt, soap, sand and clay.

- 3 retro-jet nozzle (1/8"): simply guide the hose which moves forward thanks to the pressure.
- 20 m pipe cleaning hose.

Power supply: 230V - 50Hz







Presssure bar	Pump flowrate I/min	Drilling speeds rpm	Motor rating kW	Max. reach m	Pipe Ø mm	Kg	Ref.
160	10	2800	3	12 (HP hose) - 20 (pipe cleaning hose)	40 - 100	24,000	293230

Capacities

Ø 40 mm to 100 mm.

Continuous usage time per day: 1h30

Delivered with

- 1 gun,
- 1 HP/LP multi-jet lance,
- 1 rotating nozzle lance,
- 1 Pro HP hose (12 m),
- 1 3 retro-jet nozzle ((1/8"),
- 20 m pipe cleaning hose.

2932 : Electric High Pressure Pipe Cleaner

Advantages

Hard-wearing and high performing, for intensive use. Cleans and unblocks all types of pipe: Ø 50-150 mm. Rotating nozzle lance: cleaning power doubled.

A professional quality assembly:

- 1400 rpm low speed motor for semi-intensive use: allows it to run continuously for several hours at a time (4 hours) without the risk of overheating.
- Ceramic tie-rod and piston radial pump for greater longevity.
- Automatic shut off function to preserve

the motor and reduce electricity consumption.

- Non-deforming, shock-resistant PE injected hood. Aluminium cradle frame.
- Large diameter moulded hub wheels to cross any obstacle.


High pressure cleaning function:

- Rotating connector gun: anti-twist.
- 2 channel HP/LP lance with pressure adjustment.
- Rotating nozzle lance: cleaning power doubled.
- 2 pro HP hoses (10 m + 15 m) and a safety pedal allow the cleaner to be used in places that are inaccessible to the machine (stairs, confined spaces, etc.).
- 1 large capacity detergent tank (7.5 L).

Pipe cleaning function:

Cleans and unblocks all types of pipe Ø 50-150 mm obstructed by grease or friable materials such as silt, soap, sand and clay.

- 3 retro-jet nozzle: simply guide the hose which moves forward thanks to the pressure.
- 40 m pipe cleaning hose on roller.



Capacities

Ø 50-150 mm

Continuous usage time per day: 4h00

Delivered with

- 1 Rotating connector gun,
- 2 Channel HP/LP lance with pressure adjustment.
- 1 Rotating nozzle lance,
- 2 pro HP hoses (10 m + 15 m),
- 1 safety pedal.
- 1 3 retro-jet nozzle (1/4"),
- 40 m pipe cleaning hose.







2932 : Accessories for High Pressure Pipe Cleaner


- A complete range of accessories:
 Telescopic lance: frontage cleaning up to 5 m.
- Harness for telescopic lance: lance hold assistance.
- Gutter elbow lance: gutter cleaning, only operates with the telescopic lance Ref. 293233.
- Suction filter screen: filters water from an external tank (3 m hose).
- 4 1/8" jet nozzle: 3 retro-jets + 1 front jet to attack the plug.
- 1/8" rotating nozzle: rotating jets for pipes with heavy dirt build up, moss, etc.
 4 1/4" jet nozzle: 3 retro-jets + 1 front jet to attack the plug.
- 1/4" rotating nozzle: rotating jets for pipes with heavy dirt build up, moss, etc.







Description	293230	293280	Kg	Ref.
Telescopic lance	ok	ok	3,000	293233
Harness for telescopic lance	ok	ok	0,900	293234
Gutter elbow lance	ok	ok	1,200	293235
Suction filter screen	-	ok	5,200	293236
4 1/8" jet nozzle	ok	-	0,030	293272
1/8" rotating nozzle	ok	-	0,060	293273
4 1/4" jet nozzle	-	ok	0,035	293277
1/4" rotating nozzle	-	ok	0,065	293278



PIPE INSPECTION

2941: Colour Digital Inspection Mini Camera Visioval®

Advantages

Image always horizontal thanks to the self-levelling head. Colour touch screen for intuitive use.

Application on Smartphone or tablet to view / transfer the

Possible head localisation on the 16-metre cable version.

Colour CCD camera head:

Self-levelling image to maintain it horizontal whatever the position of the camera head. Watertight head IP 68 down to 9 m deep. 4 built-in LEDs (power 100 Lux). Head Ø 17 mm on 1.2 m semi-rigid cable: for inspections of Ø 20 - 75 mm / 3/4" - 3" in confined areas (ref. 294110).

3,5" (9 cm) colour touch screen:

Touch screen with intuitive browsing in the many settings: zoom x2, adjustable brightness, black & white image function, time stamping.

Live viewing during inspection possible on Smartphone and tablet via the Mini Visioval® app (under los only).

Power supply / Battery life:

Internal rechargeable lithium battery 3.7 V/ 4.2 Ah, battery life several hours.

Photo / video / voice recording:

Resolution: Photos 720 x 480 (jpeg) / Videos 640 x 480 (avi)

later add annotations to the image, send by email or SMS.


Built-in microphone to record voice comments on real-time videos or photos. 3 transfer modes: via SD card, USB port (cable supplied), or built-in Wifi transmitter for Smartphone or tablet transfer using the Mini Visioval® app (with synchronisation function), to

Cable 16 m (ref. 294121): to be used with the Mini Visioval® ref. 294110:

Head Ø 25 mm to inspect the Ø 40 - 100 mm / 1.1/2" - 4" up to 16 metres distance (can negotiate 90° bends in 50 mm internal diameter pipes)

4 built-in LEDs (power 125 Lux).

Head fitted with a 512 Hz transmitter to be detected by the Virax localizer ref. 294130. Other characteristics of the head equivalent to those of the Mini Visioval® ref. 294110. Cable in turret open with guide for easy storage an cleaning. Base with anti-slip and









Description	Camera head	For pipes internal Ø mm	Built-in record function	Possibility of localisation	Autonomy	Kg	Ref.
Mini Visioval® 1,2 m	Fixed self-tilting	20 - 75	Yes	No	3-5hrs	3,000	294110
Mini Visioval® kit 1,2 m + cable 16 m	Fixed self-tilting	20 - 75 / 40 (50) - 100	Yes	Yes	3-5hrs	12,000	294120
Cable 16 m	Fixed self-tilting	40 (50) - 100	Yes	Yes	3-5hrs	9,000	294121

Ref. 294110: Head Ø 17 mm on 1.2 m semi-rigid cable: for inspections of Ø 20 - 75 mm / 3/4" - 3" in confined areas (ref. 294110). Ref. 294121: Head Ø 25 mm to inspect the Ø 40 - 100 mm / 1.1/2" - 4" up to 16 metres distance (can negotiate 90° bends in 50 mm internal diameter pipes).

Delivered with

Ref. 294110:

- -1 cable 1.2m.
- -1 USB mini-cable.
- -1 SD card.
- -1 charger for internal battery.
- -In plastic case.

Ref. 294121:

- -1 cable 16 m.
- -2 AA batteries to supply the 512 Hz transmitter.
- -In plastic case.

Ref. 294120:

- -1 Mini Visioval camera ref. 294110.
- -1 cable 16 m ref. 294121.
- -In plastic case.

2941: Locator for Mini Visioval®

Advantages

Allows to locate the 16 m cable head of the Mini Visioval®. Localisation up to **2.45 m deep**.

Intuitive search with **visual and sound indications** of the Mini Visioval®.

Locator ref. 294130:

Used to find the exact position of the 512 Hz transmitter of the Mini Visioval® 16 m cable head

Easy and intuitive search with direction display on 3.5" screen of the Mini Visioval® and sound indications.

Two search models:

- A geolocalisation mode to find and move above the probe.
- A depth mode to determine the distance between the probe and the locator.

Also allows to detect the 640 Hz, 33 Khz active, 50/60 Hz passive frequencies.

Telescopic design for easy storage.

Operates only with the Mini Visioval® camera (ref. 294110) associated with the 16 m cable (ref. 294121).

Supplied in a plastic shock-proof case.

Description	Kg	Ref.
Locator	4,500	294130
Complete Mini Visioval® kit + 16 m cable + Locator	16,500	294135









Virax in France, is also...

The Virax head office, located in Epernay, France, groups all activities: R&D department, Production Centre, Quality pole, Customer service, Purchasing department, After-Sales Service... up to the Storage and Distribution center.

2941: Thermal camera Mini Visioval®

Advantages

Allows to view thermal anomalies in heating circuits. Detects temperatures between -20°C and 220°C. Intuitive use thanks to the touch screen of the Mini Visioval®.

Easy and fast detection of a leak, clogged or faulty radiator/heating floor, bad insulation or fluid flow by measuring temperature differences.

Easy and intuitive thermography with settings adjustable directly on the wide 3.5" screen of the Mini Visioval®: hot and cold spot automatic viewing in a zone and display of a specific point's temperature.

Temperature range measured between -20°C and 220°C with selectable colour contrast. Many adjustments on the touch screen. Emissivity adjustable according to the material. High resolution image, with saving Photos 720 x 480 (jpeg) / Videos 640 x 480 (avi). Smartphone (iOS) or tablet transmission thanks to the Mini Visioval® app (with synchronisation function), to add annotations to the image. Transmission possible via email or SMS.

Operates only with the Mini Visioval® camera (ref. 294110). Supplied in a plastic shock-proof case.

Description	Kg	Ref.
Thermal module for Mini Visioval®	1,000	294140
Mini Visioval® camera + Thermal module kit	4,000	294145
Complete Mini Visioval® kit + Cable 16 m + Localizer + Thermal	17,500	294150









2940 : Colour digital inspection camera Visioval® VX

Advantages

Camera heads with transmitter for localisation. 30 m hose with distance indication. Detachable and interchangeable camera heads (Switch version).

Portable video inspection system with localisable camera heads in a plastic case with double reinforced walls. Vertical or horizontal inspections of piping with an inner diameter of 40 mm, exhaust pipes, ventilation ducts, flue linings, false ceilings, industrial installations, miscellaneous cavities, etc.

Visioval® VX-26 and VX-40 with non-interchangeable camera heads. Visioval® VX-SWITCH with interchangeable camera heads for complete inspection amplitude.

Colour CCD camera.

With built-in 8.9 kHz transmitter, for exact localisation of the head in the piping (requires localizer Ref. 294054).

Head Ø 26 mm watertight 3bar/IP68 for inspections of inner Ø 40 à 125 mm.

Head Ø 40 mm watertight 1bar/IP67 turns 360° and tilts 180° for inspections of inner int. 50 to 200 mm

Digital display of head position (precision 4 cm) and tilting on screen.

'Home' function to recenter the camera head in the straight position (on \varnothing 40 mm head only).

Wide 115° viewing angle and 0.5 lux sensitivity: precise image event in dark areas.

12 LEDs protected from shock and dirt, with adjustable lighting level.

7" TFT colour screen (18 cm):

Light and excellent quality images thanks to the 800 x 480 pixel resolution.

The screen can either be fixed inside the case or held in the hand thanks to its 2 m long cable.

The brightness and contrast can be adjusted.

Solar protection option (Ref. 294034) to reduce glare when working outdoors.

Power supply / Battery life.

Runs on mains or battery supply (supplied with 2 batteries).

Battery level indicated on screen, up to 2 hours per battery.

Battery charge level indicator.

Photo / video recording:

Photo and video recording on 2 GB SD card (supplied), up to 2 hours video.

Play Fast forward and rewind / Pause / Delete Functions from Visioval®.


Mini USB port to transfer photos or videos onto PC.

Visioval® VX locator: Fast and accurate localisation of the Visioval® VX \varnothing 26 mm and \varnothing 40 mm camera head by radiofrequency (8.9 kHz) in the damaged or clogged zone down to a depth of 3 metres underground.

Intuitive search with direction display on colour screen and sound indications.

Telescopic design for easy work.

Li-Ion 3.7V battery.









Capacities

Camera head Ø 26 mm: for pipes inner Ø 40 to 125 mm. Passage of 90° elbows in inner Ø 50 mm. Camera head Ø 40 mm: for pipes inner Ø 50 to 200 mm. Passage of 90° elbows in inner Ø 80 mm.

Delivered with

Visioval® VX camera:

- 2 batteries: 12 V, 2.6 Ah, Ni-MH.
- Mains power supply
- Anti-slip mat: avoids the case slipping on tiled floors.
- 2 GB SD card.
- USB cable.
- 5 Plexiglas cups (VX-40 / VX-SWITCH)

Visioval® VX locator:

- 1 headphone set with sound signal adjustment.
- 1 charger with micro USB cable
- 12 pencils
- 1 telescopic rod
- 1 case

Tips

Different accessories complete the use of the camera to make it more effective and handy: elbow head, guide ring, roller centring piece, weight for chimney inspection, etc.

2940 - 2941 : Accessories for Mini Visioval® and Visioval®

Guide ball:

(ref. 294112) allows for centring of the camera Mini Visioval® cable (ref. 294121) in pipes of section Ø 70 mm to Ø 100 mm.

Centre guide:

(ref. 294021) for pipe diameters 70 mm (min) to 150 mm (max). For centring the camera in larger diameter pipes.

24 spare brushes:

(ref. 294022) for creating 4 sets of 6 brushes, by cutting them to the most frequently inspected diameters and changing them on the centre guide 294021 (min. 70 mm, max. 150 mm).

Extension for centre guide:

(ref. 294033) composed of a 7 cm tube and a 2nd 150 mm centre guide with brushes. Enables the head to be stabilised and improved guidance in pipes with diameters of over 120 mm. *Only works in conjunction with camera heads Ø26 mm and with the centre guide ref. 294021.

Guide ring with protection:

(ref. 294031) enables the 26 mm Ø head to be protected from impact and acts as a centre guide 50 mm Ø.

7" screen solar protection:

(ref. 294034) reduces glare on the VISIOVAL's 7" monitor. For optimum visibility event outdoors.

(ref. 294041) protects the plastic dome of the 40 mm Ø head against shock and scratches.

Centring device with rollers:

(ref. 294042) improved 40 mm Ø centring and guiding for inspections in 100-150 mm Ø.

Kit of 10 plastic domes:

(ref. 294043) allows replacing the plastic dome of the 40 mm Ø head when scratched or damaged.







Description	Mini Visioval®	Visioval®	Kg	Ref.
Guide ball for 16m cable Mini Visioval®	ok	-	0,090	294112
Ø 150 mm 6" centre guide	-	ok	0,120	294021
24 Spare brushes for 294021	-	ok	0,050	294022
Elbow guide	-	ok	0,020	294023
Battery for Visioval®	-	ok	0,550	294027
Weights for chimney	-	ok	0,720	294028

Description	Mini Visioval®	Visioval®	Kg	Ref.
Guide ring with protection	-	ok	0,020	294031
Extension for centre guide *	-	ok	0,150	294033
Protection cage	-	ok	0,100	294041
Protection solaire d'écran 7"	-	ok	0,100	294034
Centering device with rollers	-	ok	0,075	294042
Kit of 10 plastic domes	-	ok	0,150	294043

CLEANING PUMP

2950 : Sludge Removal Pump / Descaling Pump

Advantages

Sludge removal pump: 3 functions in 1:

- Sludge removal from radiators and heated floors to eliminate cold zones.
- Algae elimination (sources of blockages) in heated floors.
- Descaling of boiler heating elements (copper and steel only).

Descaling pump: compact and effective to descale boiler heating elements (copper and steel only).

Translucent, anti-impact plastic tank to view the fluid level.

Manual flow reverser (ref. 295020: electric - ref. 295000: mechanical) to attack deposits in both directions: quicker and more effective action.

IP54 protected motor for maximum lifetime.

Robust and practical transport handle.

Max usage temperature: 50°C.

Virax additives must be added to optimise the action of the sludge removal pump and descaling pump. These additives are specific to the cleaning to be carried out. Their objective is to re-establish the ideal circulation in the installation for better effectiveness.

Accessory available for the sludge removal pump only: 20 m transparent pipe extension (ref. 295022) to connect to the water inlet, drains, etc.







Description	Pump flowrate I/min	Motor rating kW	Tank capacity L	Elevation height m	Use	Kg	Ref.
Sludge removal pump	30	0,330	24	15	Boiler / Radiator / Heated floor	12,000	295020
Descaling pump	28	0,130	15	10	Boiler	8,700	295000

Delivered with

Two 2 m long transparent pipes and 1 set of 8 connectors included to adapt to all configurations.

Tips

Using a neutralizer is indispensable to complete descaling, to preserve the boiler, the descaling pump and environment.

2950 : Virafal® High Flow Sludge Removal Pump / **Descaling Pump**

Advantages

1 standard version, 1 connected version in compliance with European Directive EN 806.

Mechanical cleaning 2 in 1:

Air/Water pulses to separate the sludge. Air/Water continuous flows to expel the sludge.

Chemical cleaning 4 in 1:

Sludge removal from radiators.

Sludge removal and sanitization of heating floors.

Protection against scale and corrosion.

Disinfection of drinking water pipes.

Easy installation with its roller trolley and fastening suction cups. Connectors and pipes supplied for immediate use.

High performance action: Maximum flow rate 80L/min and maximum pressure 8 bar. Effective and robust compressor: Self-lubricated, power 1.5 kW and evacuates 200L/min. Maximum temperature of use: 30°C.

For easy transport of your Virafal® or Virafal® Connect, models 295053 and 295059 are delivered with an extra raised handle. Tool-free assembly, quick height adjustment. Handle also available alone (ref. 753778).

Additional features of the VIRAFAL® Connect:

Connects with a SmartPhone, a tablet under Android or a PC via a Bluetooth connection to print an intervention report in compliance with European Directive EN 806 on drinking water

Intervention report written and transferred using the Virafal application available on Android and PC

The use of Virax additives (sold separately) requires using the fitting ref. 295052 and injector ref. 295051. These additives allow chemical use for all types of installations. They can be rejected to the sewers without detrimental effect on the environment.



Delivered with

Two 1.5 m long transparent pipes (3/4")







2950 : Additive and Accessory for Cleaning Pump

A complete range of additives that are vital to optimise the action of the VIRAFAL® sludge removal pump, descaling pump and sludge removal unit. These additives are specific to the cleaning to be carried out.

Their objective is to re-establish the ideal circulation in the installation for better effectiveness.

Descaling fluid:

(ref. 295010) to descale boilers with heating elements in copper or steel only. A mix of acids, anti-foaming agents and corrosion inhibitors to avoid damaging pipes. Colour

indicator to see whether the acid is powerful enough or not.

Neutralising agent:

(ref. 295015) for neutralising the acidity remaining in the heating element after descaling. Neutralises the descaling fluid remaining in the pump before disposal.

Sludge remover:

(ref. 295025) for radiators and heated floors. Sludge elimination to re-establish the heating system's effectiveness; non-acidic. Compatible with all metals.

VIRAFAL® sludge remover for radiators:

(ref. 295055) for radiators only. Sanitizes and removes sludge and deposits in radiators. Compatible with all metals.

VIRAFAL® sludge remover for heated floors:

(ref. 295056) for heated floors only. Eliminates both sludge and algae present in heated floors. Compatible with all metals.

Sanitizer:

(ref. 295026) for heated floors. Algae and bacteria destruction to optimise thermal performance. Compatible with all metals.

Protector:

(ref. 295027) for radiators and heated floors. Improves the installation's lifetime by slowing down sludge and corrosion return. Compatible with all metals.

VIRAFAL® protector:

(ref. 295057) for radiators and heated floors. Improves the installation's lifetime by slowing down sludge and corrosion return.

VIRAFAL® disinfectant:

(ref. 295058) for drinking water pipes. Eliminates germs from drinking water pipes.

20 m transparent pipe extension:

(ref. 295022): for easier access to water inlets and outlets.

Injector for VIRAFAL® additives:

(ref. 295051) indispensable for chemical actions with the VIRAFAL®, this injector allows for continuous and even product dispensing in the water flow. *

Reducer for VIRAFAL® additives:

(ref. 295052) this reducer, ideal for chemical actions with the VIRAFAL®, allows to reduce the flow to apply the chemical in the entire piping. **

- * Ref. 295052 only.
- ** Ref. 295052 only.

Description	Use	Packaging	295000	295020	295050	Kg	Ref.
Descaling fluid for steel, copper	Boiler	10 L Container	ok	ok	-	10,700	295010
Neutralising agent	Boiler	1 kg Box	ok	ok	-	1,050	295015
Sludge remover	Radiator / Heated floor	1 L Container	-	ok	-	1,200	295025
VIRAFAL® sludge remover for radiators	Radiator	1 L Container	-	-	ok	1,400	295055
VIRAFAL® sludge remover for heated floors	Heated floor	1 L Container	-	-	ok	1,400	295056
Sanitizer	Heated floor	1 L Container	-	ok	-	1,200	295026







Description	Use	Packaging	295000	295020	295050	Kg	Ref.
Protector	Radiator / Heated floor	1 L Container	-	ok	-	1,200	295027
VIRAFAL® protector	Radiator / Heated floor	1 L Container	-	-	ok	1,400	295057
VIRAFAL® disinfectant	Drinking water pipe	1 L Container	-	-	ok	1,400	295058
Flexible pipe extension	-	20 m	-	ok	-	3,500	295022
Injector for VIRAFAL® additives *	-	-	-	-	ok	0,600	295051
Reducer for VIRAFAL® additives **	-	-	-	-	ok	0,400	295052
Enhanced handle set for VIRAFAL®	-	-	-	-	ok	2,000	753778

HYGIENE

3600 : Towels

Very high degreasing power thanks to the combination of a very high quality liquid detergent with an abrasive, non-scratching, towel.

Easy, fast and efficient cleaning, without water.

No rinsing or drying is required. Leaves no residue.

Removes greases, lubricants, adhesives, oils, tar, bitumen, paint, ink, waxes, coal, graphite, grass stains and other stubborn stains.

Applications: plumbing, industry, storage, mechanical, DIY, gardening, painting, printing, etc. Softens and treats the skin thanks to a mild emollient added to the cleaning agent.

Dermatologically tested.

Pleasant smell (lemon).

Contents	Kg	Ref.
Box of 70 towels	0,710	360000

3600 : Gel with natural micro granulates

High performance cleansing gel for the hands, with natural micro granulates, for perfect, rapid

Very easy to use, on dry hands and without water. No rinsing required.

Removes greases, lubricants, adhesives, oils, tar, bitumen, paint, ink, waxes, coal, graphite, grass stains and other stubborn stains.

Applications: plumbing, industry, storage, mechanical, DIY, gardening, painting, printing... Practical non-screw lid.

Dermatologically tested, without petroleum solvents, biodegradable and non-toxic.

Pleasant smell (orange).

500 ml bottle, handy, for taking everywhere with you.

L	Packaging	Kg	Ref.
500 ml	Container	0,530	360020















Three pumps to descale, clean, flush and rinse all your installations.






MAKE THE MOST OF YOUR TALENT AS PER JORIS

Silver medallist from Worldskills France 2017

"Working with VIRAX tools on a daily basis and during the tests is reassuring."



workstation



WORKSTATION

FIXTUB

2000: Fixtub®

Adjustable pipe holder for accurately and rigidly positioning two pipes (or profiled sections) at a given angle during assembly. Allows complete freedom of movement during welding or brazing. Wing-nut tightening. Galvanized parts.

Pipe Ø mm	Max. arm length mm	Kg	Ref.
8 - 30	60	0,220	200010
20 - 60	100	0,830	200020





VICE

2002 : Etaugriff® Pipe Vice

Trapezoidal thread screw. High yield malleable cast iron vice. Reversible frame for obtaining the best working position on workbench, tripod or table. Hardened steel jaws. V-shaped pipe holder.



No.	Ø"	Ø mm	Kg	Ref.
0	1/8 - 2	10 - 60	3,720	200200
1	1/4 - 3	13 - 90	6,340	200210
2	1/2 - 4.1/2	21 - 127	10,500	200220
3	3/4 - 6	27 - 168	17,000	200230

2003: Chain Vice

Presetting screw. V-shaped pipe holder. Forged cam locking handle for immediate clamping. High-strength hardened steel chain. High yield malleable cast iron vice.

Α"	A mm	Kg	Ref.
1/8 - 4	10 - 114	4,300	200340





2003: Double Chain Vice

For use in boiler shops, petroleum and chemical industries, shipyards, water and gas supply services, etc. High-strength hardened steel chain. High yield malleable cast iron vice.

Α"	A mm	Kg	Ref.
2.1/2 - 12	76 - 325	34,000	200350





2004 : Parallel Vice

This vice is three tools in one: a parallel vice, a pipe vice and an anvil. Steel housing providing long guide length.

4 brass adjusting screws for centring and taking-up play in the moving jaw.





L mm	A1 mm	A2 "	H mm	Kg	Ref.
105	135	1/2 - 1.1/4	125	5,650	200410
125	155	1/2 - 1.1/2	140	8,800	200412
150	180	3/4 - 2	180	13,850	200415

2004: Swivel Base for Parallel Vice

Adjustable swivel base allowing 360° rotation of vice.

For	Kg	Ref.
200410	0,600	200411
200412	1,000	200413
200415	1,500	200416



WORKBENCH

2005 : Folding Portable Stand

Very sturdy angle-section legs.





H mm	P mm	Equipment	Kg	Ref.
925	835	No vice	15,000	200500



Go to www.virax.com

To find a product sheet, a safety data sheet or exploded views, **Go to our web site.**

WORKSTATION

FITTERS TABLE

2009: Professional Fitter's Table

Very sturdy construction, able to support heavy loads. Highly stable.

Easy to set-up, take-down and carry.

Very thick beechwood top. 3 reinforcing tie-bars for increased rigidity. 40 mm angle section legs. Max load: 500 kg.

Version with wheels + handle set available for easy travel. Screws included, quick assembly

The wheels + handle set is only available for users with an existing table.



Working dimensions mm	E mm	H mm	Kg	Ref.
1200 x 540 - No wheels / handle	50	820	43,000	200900
1200 x 540 - With wheels / handle	50	820	44,500	200901

2009: Standard Fitter's Table

Advantages

Stability: thanks to its wide base.

Easy to carry: lockable folding legs, lightweight design.

Easy vice attachment: no shoulder between the worktop and the

angle section.

Multi-ply wooden worktop with steel angle section frame.

Ø 40 mm tubular legs. Easy to install and dismantle.


Max load: 300 kg.

Version with wheels + handle set available for easy travel. Screws included, quick assembly

The wheels + handle set is only available for users with an existing table.







Working dimensions mm	E mm	H mm	Kg	Ref.
1080 x 610 - No wheels / handle	32	840	25,000	200910
1080 x 610 - With wheels / handle	32	840	26,500	200911



Discover our YouTube channel

and its product demonstration videos! /VIRAX

PLUMBER'S TABLE

2012: Professional Plumber's Table

Beechwood worktop. With lower tray. Tubular legs. Max load: 200 kg.





Working dimensions mm	E mm	H mm	Kg	Ref.
700 x 500	30	830	19,000	201202

LIGHTING

2628 : Flexible, multi-angle lamp

Advantages

Innovative: Ultra-thin and flexible body for turning the light in multiple ways.

Functional: bend, fold or wrap the lamp on or around objects to

position it.

Powerful: 16 LEDs with high angle of diffusion, up to 200 lumens.

Silicone body makes it possible to transform the lamp into a headlight to illuminate a specific place or into a lantern for shining the light over a wide perimeter.

Practical: 2 powerful magnets and 1 loop provide even more ways to position the lamp.

4 lighting modes: economical - intermediate - powerful - warning.

Maximum autonomy of 70 hours.

Splash-resistant (IP52).

3 AA batteries included.

Size mm	Kg	Ref.
293 x 144 x 20	0,250	262801







2628 : Flexible multi-angle lamps display

Display of 6 flexible multi-angle lamps (262801).

_		
	Kg	Ref.
Γ	0,250	262800







Virax is on Facebook!

@viraxofficial

WORKSTATION

FITTER'S TOOL-BAG & CHEST

3826: Textile backpack with rollers

Advantages

Double use: Back pack or trolley.

Thick and strong fabric: 1200 x 1200 deniers.

Multiple storages and high capacity: adapts to your needs.

High mobility: telescopic handle integrated to the back of the bag, wheels fitted on metal

Many compartments ensuring easy tool access: wide opening main compartment with 2 internal pockets and removable internal tool holder, 2 external compartments with zipper, and 2 side pockets with adjustable strap for long tools.

Reflective strip for high visibility in the dark.


Comfortable use: reinforced padded back and adjustable padded straps (straps stored in the back when pack used as trolley), ergonomic and strong upper handle.

Tools sold separately.





Description	Max load kg	Internal dimensions mm	External dimensions mm	Kg	Ref.
Textile backpack with rollers	15	450 x 350 x 200	500 x 420 x 250	3,000	382653



3826: Textile Tool Bag

Advantages

Multiple, practical storage compartments. Can hold up to 15 kg of tools and accessories (depending on model).

Soft protective cover. (According to model) Thick, sturdy fabric: 1200x1200 stitch.

Functional and hard-wearing textile bag.

Padded shoulder strap.

Leather grip.

Stiff, water resistant base compartment.

Special screwdriver compartment.

Mini textile bag (ref. 382650) and textile bag (ref. 382660):

- -Aluminium carry bar.
- -Interior elastic straps to hold tools in place.

Textile bag (ref. 382660):

-Metal saw storage.

Bucket bag (ref. 382655):

- -Removable tool holder spacer.
- -Metal holder for tape measure.

Tools sold separately.







Description	Max load kg	Internal dimensions mm	External dimensions mm	Kg	Ref.
Mini textile bag	12	340 x 200 x 200	380 x 320 x 320	2,300	382650
Textile bag	15	480 x 220 x 340	560 x 320 x 370	2,800	382660
Textile bucket bag	15	270 x 270 x 260	300 x 300 x 410	2,000	382655

3826: Mini textile back pack

Textile back pack with adjustable strap, ideal for easy carrying of small tooling. Thick and strong 1200 x 1200 denier fabric, with lined back. Large main compartment with zipper. Inside compartment with elastic closing.



Description	Max load kg	Internal dimensions mm	External dimensions mm	Kg	Ref.
Mini textile back pack	5	445 x 355 x 115	450 x 360 x 120	0,350	382651



Much more than just quality, here's the Virax commitment!

Virax commits to total, permanent and durable satisfaction of users and therefore applies a process based on:

A proactive product plan.

A constant innovation process.

A focus on permanent improvement.

Improved customer services.

An assurance of optimum availability rate.

Customer satisfaction, the heart of our commitments.

WORKSTATION

3826: HQ worksite box

Sealed to rain and water projections thanks to the cover engaging in the tray.

High rigidity: triple folding tray angle piece, angle piece of the double folding cover.

Strong: 10/10th thick metal sheet and reinforced hinges.

Lid opening locking strap.

2 round carry handles with horizontal locking.

Locking possible with padlock (not supplied).

Volume: 104 litres.

Removable tool tray in option.

Tools sold separately.

Description	External dimensions mm	Kg	Ref.
HQ worksite box	850 x 350 x 350	13,000	382620
Removable tray for HQ worksite box	450 x 290 x 80	0,800	382621



Smart: 1 large removable storage tray.

Tough: chock resistant and bad weather proof material.

Ergonomic handle with metal fasteners, retracts into the cover for stacking chests.

Closes with a padlockable metal-hinged clasp.

Tools sold separately.

Internal dimensions mm	External dimensions mm	Kg	Ref.
420 x 170 x 160	500 x 240 x 230	2,000	382640
560 x 180 x 200	650 x 280 x 255	4,250	382641

3826: Leather Fitter's Tool Bag

Top quality tan leather, waterproofed. Reinforced stitching. Buckle fasteners. 3 double leather studs on the underside of the bag. Inside pocket.

Tools sold separately.

Internal dimensions mm	External dimensions mm	Kg	Ref.
470 x 140 x 140	530 x 180 x 170	1,800	382670

3826: Metal Fitter's Tool Bag

Painted sheet metal. Replaceable strap. Lid with closing flaps.

Internal dimensions mm	External dimensions mm	Kg	Ref.
545 x 175 x 245	570 x 180 x 270	3,920	382685





















VACUUM CLEANER

0501: Water and Dust Vacuum Cleaner

Advantages

Anti-clogging system thanks to its 2 filters.

Vacuums everywhere thanks to its 5 m hose.

Used alone or with Virax core drills.

To vacuum water, dust, small gravel, plaster, soot and so on during maintenance or repair work (water leaks, sanitary system installation, masonry, etc.).

Anti-clogging system to remove very fine dust with no loss of suction: 1 washable, anti-bacteria filter and 1 nylon filter.

Can be moved easily thanks to 2 fixed wheels and 2 swivel wheels.

Powerful, graded speed 1500 W motor with ceramic collector for a longer lifetime.

Adapted to Virax V150+ core drills and water retrievers for V150+, V250 and V350 stands. Delivered with an accessory and storage kit.

Description	Capacity L	Kg	Ref.
Water and dust vacuum cleaner	37	10,000	050157
Pack of 10 dust paper bags	30	0,150	050164









A	Ref.	Cat.	Page
A	nei.	oat.	rage
Accessories	2402	3	72
Accessories - Portable Electric Threader	1375	4	90
Accessories for Mini Visioval® and Visioval®	2940	6	156
Accessories for Eurostem® II	2518	3	81
Accessories for Furet Auger Accessories for High Pressure Pipe Cleaner	2901 2932	6	140 151
Accessories for Hole Saws	2209	2	59
Accessories for Press Fitting Machines	2532	4	113
Accessories for Recti 9® Tap Reamer Tool	2645	6	138
Accessories for Siberia® Pipe Freezer	2210	6	134
Accessory for Drum-Type Manual Pipe Cleaner	2906	6	143
Adaptor for the VIRAX Grooving Machine	1624	4	96
Additive and Accessory for Cleaning Pump	2950	6	159
Adjustable Manual Threader	1265	4	85
Adjustable Wrench	0170	1	23
Adjustable wrench with reversible jaw	0170	1	22
Autonomous Propane/Butane Torch XB III	5215	5	123
Autonomous Soldering Iron	5218	5	126
Autonomous Torch XB III Display	5215	5	124
В	Ref.	Cat.	Page
Basin Wrench	2614	1	26
Bending 2.1/2-4" Option for Ram No. 2	2402	3	
Bending Pliers	2511		<u>71</u> 76
Bending Spring - For Copper Pipe	2510	3	75
Bending pliers	2514	3	76
Blade - Corrugated Conduit Cutter	2116	2	57
Blade - Guillotine Pipe Cutter	2115	2	56
Blade - Plastic-composite Tube Cutter	2114	2	55
Blade and Counter-Blade	2215	2	62
Burner and Tip for X 100 Handle Soldering Iron	5240	5	125
IIOII		3	123
Burner for X 400 Handle Waterproofing Torches	5250	5	127
Burner for X 400 Handle Waterproofing Torches	5250	5	127
Burner for X 400 Handle Waterproofing			
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC	5250 Ref. 2931	5 Cat.	127
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26	5250 Ref.	5 Cat.	127 Page
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm	5250 Ref. 2931 2906 2212	5 Cat. 6 6 2	127 Page 148 144 62
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil	5250 Ref. 2931 2906 2212 2627	5 Cat. 6 6 2 1	127 Page 148 144 62 27
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice	5250 Ref. 2931 2906 2212 2627 2003	5 Cat. 6 6 2 1 7	127 Page 148 144 62 27 164
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench	5250 Ref. 2931 2906 2212 2627 2003 0142	5 Cat. 6 6 2 1 7	127 Page 148 144 62 27 164 21
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503	5250 Ref. 2931 2906 2212 2627 2003 0142 2215	5 Cat. 6 6 2 1 7 1 2	127 Page 148 144 62 27 164 21 62
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500	5 Cat. 6 6 2 1 7	127 Page 148 144 62 27 164 21
Burner for X 400 Handle Waterproofing Torches Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2"	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402	5 Cat. 6 6 2 1 7 1 2 3	127 Page 148 144 62 27 164 21 62 74
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402	5 Cat. 6 6 2 1 7 1 2 3 3 3	127 Page 148 144 62 27 164 21 62 74 69
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501	5 Cat. 6 6 2 1 7 1 2 3 3 3 3	127 Page 148 144 62 27 164 21 62 74 69 69 75
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501	5 Cat. 6 6 2 1 7 1 2 3 3 3 6	127 Page 148 144 62 27 164 21 62 74 69 69 75
Burner for X 400 Handle Waterproofing Torches C Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger Cobraz® Accessories	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501 2905 5270	5 Cat. 6 6 2 1 7 1 2 3 3 3 6 5	127 Page 148 144 62 27 164 21 62 74 69 69 75 142 129
Burner for X 400 Handle Waterproofing Torches Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger Cobraz® Accessories Cobraz® Electric Soldering Machine	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501	5 Cat. 6 6 2 1 7 1 2 3 3 3 6	127 Page 148 144 62 27 164 21 62 74 69 69 75
Burner for X 400 Handle Waterproofing Torches Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger Cobraz® Accessories Cobraz® Electric Soldering Machine Colour Digital Inspection Mini Camera Visioval®	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501 2905 5270	5 Cat. 6 6 2 1 7 1 2 3 3 3 6 5	127 Page 148 144 62 27 164 21 62 74 69 69 75 142 129
Burner for X 400 Handle Waterproofing Torches Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger Cobraz® Accessories Cobraz® Accessories Cobraz® Electric Soldering Machine Colour Digital Inspection Mini Camera Visioval® Colour digital inspection camera Visioval® VX	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501 2905 5270 5270	5 Cat. 6 6 2 1 7 1 2 3 3 3 6 5 5	127 Page 148 144 62 27 164 21 62 74 69 69 75 142 129 128
Burner for X 400 Handle Waterproofing Torches Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger Cobraz® Accessories Cobraz® Electric Soldering Machine Colour Digital Inspection Mini Camera Visioval® Colour digital inspection camera Visioval®	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501 2905 5270 2941	5 Cat. 6 6 2 1 7 1 2 3 3 3 6 5 6	127 Page 148 144 62 27 164 21 62 74 69 69 75 142 129 128 152
Burner for X 400 Handle Waterproofing Torches Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger Cobraz® Accessories Cobraz® Accessories Cobraz® Electric Soldering Machine Colour Digital Inspection Mini Camera Visioval® Colour digital inspection camera Visioval® VX Compact Manual Axial Crimping Tool for PEX series 5	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501 2905 5270 2941 2940	5 Cat. 6 6 2 1 7 1 2 3 3 3 6 5 6 6	127 Page 148 144 62 27 164 21 62 74 69 69 75 142 129 128 152
Burner for X 400 Handle Waterproofing Torches Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger Cobraz® Accessories Cobraz® Electric Soldering Machine Colour Digital Inspection Mini Camera Visioval® Colour digital inspection camera Visioval® VX Compact Manual Axial Crimping Tool for	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501 2905 5270 5270 2941 2940 2533	5 Cat. 6 6 2 1 7 1 2 3 3 3 6 5 6 6 4	127 Page 148 144 62 27 164 21 62 74 69 69 75 142 129 128 152 155 105
Burner for X 400 Handle Waterproofing Torches Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger Cobraz® Accessories Cobraz® Electric Soldering Machine Colour Digital Inspection Mini Camera Visioval® Colour digital inspection camera Visioval® VX Compact Manual Axial Crimping Tool for PEX series 5 Compact Tubular Level Concentric Radius Former for Eurostem® II Connecting Tubes for Jet Burners 3-4 for X	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501 2905 5270 5270 2941 2940 2533 2631 2518	5 Cat. 6 6 7 1 2 3 3 3 6 5 6 4 1 3	127 Page 148 144 62 27 164 21 62 74 69 69 75 142 129 128 152 155 105 27 81
Burner for X 400 Handle Waterproofing Torches Cable segment pipe cleaner VAL 96QC Cables for professional pipe cleaner VAL 26 Calibration Tool 16-63 mm Carpenter's Pencil Chain Vice Chain Wrench Chamfering Tool For Plastic Pipes Cheek and Counter Former for 2500 / 2503 Crossbow Bender Cheeks 2.1/2" Cheeks 4" Cheeks and Counter-Former for 2501 Crossbow Bender Closet Auger Cobraz® Accessories Cobraz® Electric Soldering Machine Colour Digital Inspection Mini Camera Visioval® Colour digital inspection camera Visioval® VX Compact Manual Axial Crimping Tool for PEX series 5 Compact Tubular Level Concentric Radius Former for Eurostem® II	5250 Ref. 2931 2906 2212 2627 2003 0142 2215 2500 2402 2402 2501 2905 5270 5270 2941 2940 2533 2631	5 Cat. 6 6 2 1 7 1 2 3 3 3 6 5 6 4 1	127 Page 148 144 62 27 164 21 62 74 69 69 75 142 129 128 152 155 105

Copper Tube Cutter 14-54 mm	2104	2	50
Copper Tube Cutter 14-34 mm	2104	2	49
Core Drill Accessories	0501	2	43
Corrugated Conduit Cutter Ø 45 mm	2116	2	57
Crimping Jaws for Models P10 / P22+ / P25+	2530		
/ P30+	2531	4	115
Crossbow Bender	2503	3	73
Cutter For Rodor Tap Reamer	2621	6	137
Cutting Wheel - Deburring Spare Blade -	2104	2	
Copper Tube Cutter	2104		51
Cutting Wheel - Deburring Spare Blade -	2104	2	53
Plastic-composite Tube Cutter	2104		
Cutting Wheel - Deburring Spare Blade -	2104	2	48
Stainless Steel Tube Cutter			
Cutting Wheel - Steel and Cast Iron Pipe	2101	2	46
Cutter	0000		400
Cylinder / Water Heater Lift	2636	6	139
D	Ref.	Cat.	Page
Diamond Core Bit	0535	2	42
Die Die	2504	4	98
Die Head for 2" – 4" Threading Machine	1621	4	94
Dies for 2 " – 4 " Threading Machine Die			
Heads	1622	4	94
Display Box of Copper Tube Cutters ZR 35	2104	2	49
Display Box of Extra-Wide Opening	0170	1	22
Adjustable Wrenches	0170	'	
Display Box of PC 32 Pipe Cutters	2150	2	54
Display Box of PC 42 Plastic Tube Cutters	2150	2	55
Display Box of Tips 300	5230	5	126
Display for Extra-Wide Opening Multigrip Pliers	0182	1	18
Display of Bottles of Filetfix® III	2626	4	104
Display of Measuring Tapes	3717	1	32
Display of Nicasaming Tapes Display of Seven-Bit Screwdrivers.	3425	.	31
Display of Six-Bit Mini Screwdrivers	3425	.	31
Double Chain Vice	2003	7	164
Drop Head Threaders	1362	4	90
Drum-Type Manual Pipe Cleaner	2906	6	143
Ductile Cast Iron Pipe Cutter	2102	2	45
F	D-f	0-1	D
E	Ref.	Cat.	Page
Electric Drum Type Pipe Cleaner VAL 80 /	2912	6	146
VAL 80E			
Electric Drum Type Pipe Cleaner: VAL 90	2920	6	147
Electric High Pressure Pipe Cleaner	2932	6	150
Electric Ram Electric Test Pump	2408	3	72
Electrical Water Pump	2620 0500	6 2	137 44
Etaugriff® Pipe Vice	2002	7	164
Expansion Pliers PEX series 5	2534	4	101
Extra-Wide Multigrip Pliers with Fast Locking			
Button	0182	1	17
Extra-Wide Opening Adjustable Wrench	0170	1	21
Extra-Wide Opening Multigrip Pliers			17
			1/
Extrudax® Accessories	0182	1 4	
		1	103
Extrudax® Accessories Extrudax® Flanging Tools Extrudax® T-Flange Tool Set	0182 2528	1 4	103
Extrudax® Flanging Tools Extrudax® T-Flange Tool Set	0182 2528 2528 2528	1 4 4 4	103 103 102
Extrudax® Flanging Tools Extrudax® T-Flange Tool Set	0182 2528 2528 2528 Ref.	1 4 4 4 Cat.	103 103 102 Page
Extrudax® Flanging Tools Extrudax® T-Flange Tool Set F Fast Copper Tube Cutter 6-67 mm	0182 2528 2528 2528 Ref.	1 4 4 4 Cat.	103 103 102 Page 50
Extrudax® Flanging Tools Extrudax® T-Flange Tool Set F Fast Copper Tube Cutter 6-67 mm Fast Stainless Steel Tube Cutter 6-67 mm	0182 2528 2528 2528 2528 Ref. 2104 2104	1 4 4 4 Cat.	103 103 102 Page 50 47
Extrudax® Flanging Tools Extrudax® T-Flange Tool Set Fast Copper Tube Cutter 6-67 mm Fast Stainless Steel Tube Cutter 6-67 mm Fast feed 6-65 mm plastic pipe cutter	0182 2528 2528 2528 2528 Ref. 2104 2104 2104	1 4 4 4 Cat.	103 103 102 Page 50 47 51
Extrudax® Flanging Tools Extrudax® T-Flange Tool Set F Fast Copper Tube Cutter 6-67 mm Fast Stainless Steel Tube Cutter 6-67 mm Fast feed 6-65 mm plastic pipe cutter Filetfix® III	0182 2528 2528 2528 Ref. 2104 2104 2104 2626	1 4 4 4 Cat.	103 103 102 Page 50 47 51 104
Extrudax® Flanging Tools Extrudax® T-Flange Tool Set Fast Copper Tube Cutter 6-67 mm Fast Stainless Steel Tube Cutter 6-67 mm Fast feed 6-65 mm plastic pipe cutter	0182 2528 2528 2528 2528 Ref. 2104 2104 2104	1 4 4 4 Cat.	103 103 102 Page 50 47 51

	5282	5	130	Mandrel / Flanging Tool
Flame Shield Flaring Pliers for Copper	2526	4	100	Manual Axial Crimping Tool
Flaring Tool	2526	4	100	Manual Hydraulic Bender
Flexible Head Ratchet Wrench 8-17 mm	3103	1	24	Manual Hydraulic Bender for
Flexible multi-angle lamps display	2628	7	167	Pipe
Flexible, multi-angle lamp	2628	7	167	Manual Ram
Flint Ignitor	5282	5	130	Manual Test Pump
Folding Portable Stand	2005	7	165	Manual Water Pump
Former	2502	3	78	Measuring Tape
Former and Counter-Former for Eurostem®				Metal Fitter's Tool Bag
	2518	3	80	Mineral Cutting Oil
Former for 2500 / 2503 Crossbow Bender	2500	3	74	Mini Copper Tube Cutter 3-2
Former for 2501 Crossbow Bender	2501	3	74	Mini Six-Bit Screwdriver
Former for Gas Pipes Medium and Heavy	2402			Mini crimping jaws for M21+/
Series (nfa49-115)	2408	3	70	Mini textile back pack
Former for Light Series Pipes	2402	3	70	Multi-Material Internal/Extern
Former for Locksmith's Pipes	2402	3	71	
Former for PEX/AL/PEX Pipe	2402	3	71	N
Furet Auger Pipe Cleaner	2901	6	140	
				Needlepoint Burner for Stand
G	Ref.	Cat.	Page	handle X 200
GP Standard Torch	5212	5	123	0
	5212		130	
Gas Cylinder - 1,6 kg Gas Tightness Controller	2620	6	135	Open Cheeks
	3600	6	160	В
Gel with natural micro granulates Grey Cast Iron Pipe Cutter	2102	2	45	P
	2102	2	45	PC 32 Plastic Tube Cutter up
Grey Cast Iron Pipe Cutter for grey cast iron Groover GR2-12	1626	4	97	PC 42 Plastic Tube Cutter up
	1624	4	96	Pack of 5 HSS Bi-Metal Reci
Grooving machine Guillotine Pipe Cutter	2115	2	56	Blades
Gyroflam® Brazer for Standard Torch with	2113		30	Pair of Gloves
Handle X 200	5210	5	123	Parallel Vice
Tiandle A 200				Pencil Reamer with Interchai
H	Ref.	Cat.	Page	Phenix III Portable Electric T
			<u> </u>	
HM Piezo Propane Torch	5205	5	120	Phenix Mini Portable Electric
HQ worksite box	5205 3826	5 7	120 170	Phenix Mini Portable Electric Machine
HQ worksite box HSS Saw Blade		7 2	120	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for
HQ worksite box HSS Saw Blade Hacksaw frame	3826 0430 0490	7	120 170	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool	3826 0430	7 2 2 4	120 170 36 36 99	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for
HQ worksite box HSS Saw Blade Hacksaw frame	3826 0430 0490	7 2 2	120 170 36 36	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool	3826 0430 0490 2505 2402 2209	7 2 2 4	120 170 36 36 99	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3"	3826 0430 0490 2505 2402	7 2 2 4 3	120 170 36 36 99 69	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set	3826 0430 0490 2505 2402 2209 2402	7 2 2 4 3 2 3	120 170 36 36 99 69 58 67	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set	3826 0430 0490 2505 2402 2209	7 2 2 4 3 2	120 170 36 36 99 69 58	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F 5200 / 5205 Pipe Cleaner Accessories V/ Pipe Cleaner Gun
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws	3826 0430 0490 2505 2402 2209 2402	7 2 2 4 3 2 3	120 170 36 36 99 69 58 67	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Oil
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529	7 2 2 4 3 2 3 Cat.	120 170 36 36 99 69 58 67 Page	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F 5200 / 5205 Pipe Cleaner Accessories V/ Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws	3826 0430 0490 2505 2402 2209 2402 Ref.	7 2 2 4 3 2 3 Cat.	120 170 36 36 99 69 58 67	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Oil
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529	7 2 2 4 3 2 3 Cat.	120 170 36 36 99 69 58 67 Page	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112	7 2 2 4 3 2 3 Cat. 2 4	120 170 36 36 99 69 58 67 Page 59 113	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532	7 2 2 4 3 2 3 Cat. 2 4 1	120 170 36 36 99 69 58 67 Page 59	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX &	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112	7 2 2 4 3 2 3 Cat. 2 4	120 170 36 36 99 69 58 67 Page 59 113	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Beteurostem® II
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510	7 2 2 4 3 2 3 Cat. 2 4 1 3	120 170 36 36 99 69 58 67 Page 59 113 16 75	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Beteurostem® II Portable Electric Drum Type
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510	7 2 2 4 3 2 3 Cat. 2 4 1	120 170 36 36 99 69 58 67 Page 59 113 16	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Beturostem® II Portable Electric Drum Type VAL 35 / VAL 35E
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510	7 2 2 4 3 2 3 Cat. 2 4 1 3	120 170 36 36 99 69 58 67 Page 59 113 16 75	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Eurostem® Euros
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510 2212 Ref.	7 2 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 2	120 170 36 36 99 69 58 67 Page 59 113 16 75 60	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender EuroPowered Hydraulic Bender
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2532 0112 2510 2212	7 2 2 4 3 2 3 Cat. 2 4 1 3 2 Cat.	120 170 36 36 99 69 58 67 Page 59 113 16 75 60	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510 2212 Ref.	7 2 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 2	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender EuroPowered Hydraulic Bender
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2532 0112 2510 2212 Ref. 2211	7 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 2 Cat.	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch L Large-Capacity Plumbing Wrench Leak Detector	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510 2212 Ref. 2211 Ref.	7 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional Plumber's Table
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch Large-Capacity Plumbing Wrench Leak Detector Leather Fitter's Tool Bag	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510 2212 Ref. 2211 Ref.	7 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1 6	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional pipe cleaner VA Propane Pressure Regulator
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch Large-Capacity Plumbing Wrench Leak Detector Leather Fitter's Tool Bag Level with 2 in 1 centre distance	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510 2212 Ref. 2211 Ref. 0113 2626 3826 2631	7 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1 6 7 1	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60 Page 18 136 170 29	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional Plumber's Table Professional pipe cleaner VA Propane Pressure Regulator Propane/Butane Rubber Hos
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch Large-Capacity Plumbing Wrench Leak Detector Leather Fitter's Tool Bag Level with 2 in 1 centre distance Light Alloy Offset Viragrip® Pipe Wrench	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510 2212 Ref. 0113 2626 3826 2631 0136	7 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1 6 7	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60 Page 18 136 170	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Gil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Beteurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional Plumber's Table Professional pipe cleaner VA Propane Pressure Regulator Propane/Butane Rubber Hos Pump-Action Pipe Cleaner
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch Large-Capacity Plumbing Wrench Leak Detector Leather Fitter's Tool Bag Level with 2 in 1 centre distance Light Alloy Offset Viragrip® Pipe Wrench Light Alloy Viragrip® Pipe Wrench	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510 2212 Ref. 2211 Ref. 0113 2626 3826 2631	7 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1 6 7 1 1	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60 Page 18 136 170 29 19	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 50 -110 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional Plumber's Table Professional pipe cleaner VA Propane Pressure Regulator Propane/Butane Rubber Hos
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch Large-Capacity Plumbing Wrench Leak Detector Leather Fitter's Tool Bag Level with 2 in 1 centre distance Light Alloy Offset Viragrip® Pipe Wrench Limit Switch	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510 2212 Ref. 0113 2626 3826 2631 0136 0137	7 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1 6 7 1 1	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60 Page 18 136 170 29	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Gil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 35 - 410 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional Plumber's Table Professional pipe cleaner VA Propane Pressure Regulator Propane/Butane Rubber Hos Pump-Action Pipe Cleaner
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch Large-Capacity Plumbing Wrench Leak Detector Leather Fitter's Tool Bag Level with 2 in 1 centre distance Light Alloy Offset Viragrip® Pipe Wrench Limit Switch Locator for Mini Visioval®	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2532 0112 2510 2212 Ref. 2211 Ref. 0113 2626 3826 2631 0136 0137 2408 2941	7 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1 6 7 1 1 3 6	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60 Page 18 136 170 29 19 19	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 35 - 410 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional Plumber's Table Professional pipe cleaner VA Propane Pressure Regulator Propane/Butane Rubber Hos Pump-Action Pipe Cleaner
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch Large-Capacity Plumbing Wrench Leak Detector Leather Fitter's Tool Bag Level with 2 in 1 centre distance Light Alloy Offset Viragrip® Pipe Wrench Limit Switch	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2529 2532 0112 2510 2212 Ref. 0113 2626 3826 2631 0136 0137 2408	7 2 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1 6 7 1 1 1 3	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60 Page 18 136 170 29 19 19	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 35 - 410 m cutter Plug Wrench Portable Battery-Powered Betwostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional Plumber's Table Professional pipe cleaner VA Propane Pressure Regulator Propane/Butane Rubber Hos Pump-Action Pipe Cleaner R Radiator Key Wrench Radiator Key Wrench
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch Large-Capacity Plumbing Wrench Leak Detector Leather Fitter's Tool Bag Level with 2 in 1 centre distance Light Alloy Offset Viragrip® Pipe Wrench Limit Switch Locator for Mini Visioval®	3826 0430 0490 2505 2402 2209 2402 Ref. 2219 2510 2212 Ref. 2211 Ref. 0113 2626 3826 2631 0137 2408 2941 Ref.	7 2 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1 6 7 1 1 1 3 6 Cat.	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60 Page 18 136 170 29 19 19 67 153 Page	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 35 - 410 m cutter Plug Wrench Portable Battery-Powered Be Eurostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional Plumber's Table Professional Plumber's Table Professional Pipe Cleaner VA Propane Pressure Regulator Propane/Butane Rubber Hos Pump-Action Pipe Cleaner Radiator Key Wrench Radiator Key Wrench With Radiator Lift
HQ worksite box HSS Saw Blade Hacksaw frame Heavy Duty Flanging Tool Hinged cheek 3" Hole Saw Set Hydraulic Ram Oil Individual Hole Saws Inserts for Models i10 / i26 / M20+ / M21+ / ML21+ Insulated Slip-Joint Pliers - Straight Jaws Internal Bending Spring for PEX & Multilayers Pipes Internal-External Reamer K Knockout Punch Large-Capacity Plumbing Wrench Leak Detector Leather Fitter's Tool Bag Level with 2 in 1 centre distance Light Alloy Offset Viragrip® Pipe Wrench Limit Switch Locator for Mini Visioval®	3826 0430 0490 2505 2402 2209 2402 Ref. 2209 2532 0112 2510 2212 Ref. 2211 Ref. 0113 2626 3826 2631 0136 0137 2408 2941	7 2 4 3 2 3 Cat. 2 4 1 3 2 Cat. 1 6 7 1 1 3 6	120 170 36 36 99 69 58 67 Page 59 113 16 75 60 Page 60 Page 18 136 170 29 19 19 67 153	Phenix Mini Portable Electric Machine Piezo Gyroflam® Burner for 5200/5205 Piezo Needlepoint Burner for 5200/5205 Piezo Propane Torch Piezo Turbojet® Burner for F5200 / 5205 Pipe Cleaner Accessories V/Pipe Cleaner Gun Pipe Cleaner Gun Pipe Cleaner Oil Plastic pipe cutter 35 - 40 - 6 Plastic pipe cutter 35 - 410 m cutter Plug Wrench Portable Battery-Powered Betwostem® II Portable Electric Drum Type VAL 35 / VAL 35E Portable Power Bender Euro Powered Hydraulic Bender Pro HP Cleaner-Clearer Professional Fitter's Table Professional Plumber's Table Professional pipe cleaner VA Propane Pressure Regulator Propane/Butane Rubber Hos Pump-Action Pipe Cleaner R Radiator Key Wrench Radiator Key Wrench

Mandrel / Flanging Tool	2504	4	98
Manual Axial Crimping Tool for PEX series 5	2533	4	106
Manual Hydraulic Bender	2402	3	66
Manual Hydraulic Bender for Locksmith's Pipe	2402	3	66
Manual Ram	2402	3	72
Manual Test Pump	2620	6	136
Manual Water Pump	0500	2	44
Measuring Tape	3717	1	32
Metal Fitter's Tool Bag	3826	7	170
Mineral Cutting Oil	1101	4	84
Mini Copper Tube Cutter 3-28 mm	2104	2	48
Mini Six-Bit Screwdriver	3425	4	31 115
Mini crimping jaws for M21+/ML21+ Mini textile back pack	2525 3826	7	169
Multi-Material Internal/External Reamer	2212	2	61
N	Ref.	Cat.	Page
Needlepoint Burner for Standard Torch with handle X 200	5210	5	122
0	Ref.	Cat.	Page
Open Cheeks	2402	3	68
·			
P	Ref.	Cat.	Page
PC 32 Plastic Tube Cutter up to 32 mm	2150	2	54
PC 42 Plastic Tube Cutter up to 42 mm	2150	2	55
Pack of 5 HSS Bi-Metal Reciprocating Saw Blades	0460	2	38
Pair of Gloves	2900	6	141
Parallel Vice	2004	7	165
Pencil Reamer with Interchangeable Blade	2212	2	61
Phenix III Portable Electric Threader	1375	4	89
Phenix Mini Portable Electric Threading	1380	4	88
Machine Piezo Gyroflam® Burner for Piezo Torches			
5200/5205	5200	5	121
Piezo Needlepoint Burner for Piezo Torches 5200/5205	5200	5	121
Piezo Propane Torch	5200	5	120
Piezo Turbojet® Burner for Piezo Torches	5200	5	121
5200 / 5205 Pipe Cleaner Accessories VAL 80 / VAL 80E	2912	6	146
Pipe Cleaner Gun	2901	6	142
Pipe Cleaner Oil	2904	6	144
Plastic pipe cutter 35 - 40 - 63 mm	2114	2	53
Plastic pipe cutter 50 -110 mm plastic pipe	2106	2	51
cutter Diva Wranah			
Plug Wrench Portable Battery-Powered Bender	2616	1	27
Eurostem® II	2518	3	79
Portable Electric Drum Type Pipe Cleaner VAL 35 / VAL 35E	2910	6	145
Portable Power Bender Eurostem® II	2518	3	80
Powered Hydraulic Bender	2408	3	67
Pro HP Cleaner-Clearer	2932	6	149
Professional Fitter's Table Professional Plumber's Table	2009 2012	7	166 167
Professional pipe cleaner VAL 26	2906	6	143
Propane Pressure Regulator	5260	5	128
Propane/Butane Rubber Hose	5280	5	129
Pump-Action Pipe Cleaner	2902	6	141
R	Ref.	Cat.	Page
Radiator Key Wrench	2204	1	23
Radiator Key Wrench With Ratchet	2204	1	23
Radiator Lift	2636	6	139
Ratchet Housing for Manual Threader with	1362	4	87
Interchangeable Heads	1363		

B B		_	
Ratchet Reamer	2212	2	60 37
Reciprocating Saw Reciprocating Saw Vice	0450 0450	2	37
Recti 9® Tap Reamer Tool Set	2645	6	138
Reducer and adaptor for Axial Crimping			100
Tools 2533	2533	4	106
Reducing Pliers	3350	1	29
Reversible Sanicrom® Basin Wrench	2614	1	26
Rodor® Tap Reamer	2621	6	137
Roller Stand	1611	4	94
S	Ref.	Cat.	Page
	2614		<u> </u>
Sanicrom® Basin Wrench Set of Dies	2614 1362	1 4	25 91
Set of Hexagonal Keys	3114	1	29
Seven-Bit Screwdriver	3425	<u> </u>	30
Siberia® Electric Pipe Freezer 2"	2210	6	134
Sliding Cheeks	2402	3	68
Sliding Cheeks - Locksmith's Conduit	2402	3	70
Sludge Removal Pump / Descaling Pump	2950	6	157
Soft Solder	5283	5	130
Soldering Iron - X 100 Handle	5240	5	125
Spare parts for 2" – 4" Threading Machine	1621	4	95
Square	2206	1	31
Stainless Steel Pipe Cutter 10-90 mm	2101	2	47
Stainless Steel Pipe Cutter 14-54 mm	2104	2	48
Stainless Steel Pipe Cutter 6-28 mm	2104	2	46
Stand for 2" Threading Machine	1624	4	95
Stand for 4" Threading Machine	1624	4	96
Standard Fitter's Table	2009	7	166
Standard Propane Torch X 200	5210	5	122
Standard Reamer	2212	2	60
Steel Pipe Cutter	2101	2	45
Stillson Wrench	0125	1	19
Strap Wrench	0116	1	18
Swedish - 45° Pipe Wrench	0105	1	15
	0104	1	14
Swedish Pipe Wrench Swedish key - 90°		1	14
Swedish Pipe Wrench	0104		
Swedish Pipe Wrench Swedish key - 90°	0104 0100	1	14
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice	0104 0100 2004	1 7	14 165
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling	0104 0100 2004 5282	1 7 5	14 165 129
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger	0104 0100 2004 5282 2905	1 7 5 6	14 165 129 143 84
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil	0104 0100 2004 5282 2905 1106	1 7 5 6 4 Cat.	14 165 129 143 84
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools	0104 0100 2004 5282 2905 1106 Ref.	1 7 5 6 4 Cat.	14 165 129 143 84 Page
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set	0104 0100 2004 5282 2905 1106 Ref. 2527 2527	1 7 5 6 4 Cat.	14 165 129 143 84 Page 102
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527	1 7 5 6 4 Cat. 4 4	14 165 129 143 84 Page 102 102
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614	1 7 5 6 4 Cat. 4 4 4	14 165 129 143 84 Page 102 102 102 26
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826	1 7 5 6 4 Cat. 4 4 4 1 7	14 165 129 143 84 Page 102 102 102 26 169
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826	1 7 5 6 4 Cat. 4 4 4 1 7	14 165 129 143 84 Page 102 102 102 26 169 168
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval®	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826 2941	1 7 5 6 4 Cat. 4 4 4 1 7 7 6	14 165 129 143 84 Page 102 102 102 26 169 168 154
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2"	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826 2941 1621	1 7 5 6 4 Cat. 4 4 4 1 7 7 6 4	14 165 129 143 84 Page 102 102 102 26 169 168 154 92
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4"	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826 2941 1621	1 7 5 6 4 Cat. 4 4 4 1 7 7 6 4	14 165 129 143 84 Page 102 102 102 26 169 168 154 92 93
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" -	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826 2941 1621 1621	1 7 5 6 4 Cat. 4 4 4 1 7 7 6 4	14 165 129 143 84 Page 102 102 102 26 169 168 154 92
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826 2941 1621 1362 1364	1 7 5 6 4 Cat. 4 4 4 1 7 7 6 4 4	14 165 129 143 84 Page 102 102 26 169 168 154 92 93
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case -	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826 2941 1621 1362 1364 1362	1 7 5 6 4 Cat. 4 4 4 1 7 7 6 4	14 165 129 143 84 Page 102 102 102 26 169 168 154 92 93
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2527 2614 3826 3826 2941 1621 1362 1364 1362 1363	1 7 5 6 4 4 4 1 7 7 6 4 4 4	14 165 129 143 84 Page 102 102 102 26 169 168 154 92 93 87
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case Tip for MAPP® Pro Torch	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826 2941 1621 1362 1364 1362 1363 5217	1 7 5 6 4 Cat. 4 4 4 1 7 7 6 4 4	14 165 129 143 84 Page 102 102 26 169 168 154 92 93
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826 2941 1621 1362 1364 1362 1363 5217 2901	1 7 5 6 4 4 4 1 7 7 6 4 4 4 4 4 5	14 165 129 143 84 Page 102 102 102 26 169 168 154 92 93 87 86
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case Tip for MAPP® Pro Torch Toilet Extension for Pipe Cleaner Gun Tools Chest	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 3826 2941 1621 1362 1364 1362 1363 5217 2901 3826	1 7 5 6 4 4 4 1 7 7 6 4 4 4 4 4 4 5 6	14 165 129 143 84 Page 102 102 102 26 169 168 154 92 93 87 86 125 142 170
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case Tip for MAPP® Pro Torch Toilet Extension for Pipe Cleaner Gun Tools Chest Tools for lead tube	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 2941 1621 1362 1364 1362 1363 5217 2901 3826 2610	1 7 5 6 4 4 4 1 7 7 6 4 4 4 4 4 5 6	14 165 129 143 84 Page 102 102 26 169 168 154 92 93 87 86 125 142 170 103
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case Tip for MAPP® Pro Torch Toilet Extension for Pipe Cleaner Gun Tools Chest Tools for lead tube Towels	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 2941 1621 1362 1364 1362 1363 5217 2901 3826 2610 3600	1 7 5 6 4 4 4 4 1 7 7 6 4 4 4 4 5 6 7	14 165 129 143 84 Page 102 102 102 26 169 168 154 92 93 87 86 125 142 170
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case Tip for MAPP® Pro Torch Toilet Extension for Pipe Cleaner Gun Tools Chest Tools for lead tube Towels Tripod	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 2941 1621 1362 1364 1362 1363 5217 2901 3826 2610	1 7 5 6 4 4 4 4 1 7 7 6 4 4 4 4 4 5 6 7	14 165 129 143 84 Page 102 102 26 169 168 154 92 93 87 86 125 142 170 103 160
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case Tip for MAPP® Pro Torch Toilet Extension for Pipe Cleaner Gun Tools Chest Tools for lead tube Towels Tripod Tubular Vial Level / Trapezoid Level	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2527 2614 3826 3826 2941 1621 1362 1364 1362 1364 1362 1363 5217 2901 3826 2610 3600 2402 2631	1 7 5 6 4 4 4 1 7 7 6 4 4 4 4 5 6 7 4 4 1	14 165 129 143 84 Page 102 102 102 26 169 168 154 92 93 87 86 125 142 170 103 160 68 28
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case Tip for MAPP® Pro Torch Toilet Extension for Pipe Cleaner Gun Tools Chest Tools for lead tube Towels Tripod	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2614 3826 2941 1621 1362 1364 1362 1363 5217 2901 3826 2610 3600 2402	1 7 5 6 4 4 4 4 1 7 7 6 4 4 4 4 4 5 6 7 4 6 3	14 165 129 143 84 Page 102 102 102 26 169 168 154 92 93 87 86 125 142 170 103 160 68
Swedish Pipe Wrench Swedish key - 90° Swivel Base for Parallel Vice Swivel Coupling Swivel Head for Closet Auger Synthetic Threading Oil T T-Rax Flanging tools T-Rax T-Flange Tool Set T-rax Accessories Telescopic Sanicrom® Basin Wrench Textile Tool Bag Textile backpack with rollers Thermal camera Mini Visioval® Threading Machine 2" Threading Machine 4" Threading Set 3/8" - 2" And 1.1/2" - 2" - Metal Case Threading Set 3/8" - 1 1/4" - Plastic case - Metal case Tip for MAPP® Pro Torch Toilet Extension for Pipe Cleaner Gun Tools Chest Tools for lead tube Towels Tripod Tubular Vial Level / Trapezoid Level Turbojet® Burner for Standard Torch with	0104 0100 2004 5282 2905 1106 Ref. 2527 2527 2527 2527 2614 3826 3826 2941 1621 1362 1364 1362 1364 1362 1363 5217 2901 3826 2610 3600 2402 2631	1 7 5 6 4 4 4 1 7 7 6 4 4 4 4 5 6 7 4 4 1	14 165 129 143 84 Page 102 102 102 26 169 168 154 92 93 87 86 125 142 170 103 160 68 28

U	Ref.	Cat.	Page
Universal Brazing Flux	5284	5	131
Universal Key Wrench	2615	1	25
Universal wrench for toilet lid	2205	1	24
V	Ref.	Cat.	Page
V 150+ Core Drill and Support Stand	0501	2	39
V 250 Core Drill and Support Stand	0501	2	40
V 350 Core Drill and Support Stand	0501	2	41
Vacuum Pump for Core Drill	0500	2	43
Viper® M21+ Electro-mechanical Press Fitting Machine	2535	4	108
Viper® ML21+ Electro-Mechanical Press Fitting Machine	2535	4	110
Viper® P25+ Battery-Powered Hydraulic Press Fitting Machine	2532	4	111
Viper® P30+ Electro-Mechanical Press Fitting Machine	2536	4	112
Viper® i26 Manual Hydraulic Press-Fitting Machine	2529	4	107
Virafal® High Flow Sludge Removal Pump / Descaling Pump	2950	6	158
Viragrip® in Heavy Duty Cast Iron	0138	1	20
W	Ref.	Cat.	Page
Water and Dust Vacuum Cleaner	0501	7	171
Waterproofer's Torch – X 400 Handle	5250	5	127
Workbench Manual Bender	2502	3	77
Workbench Manual Bender Accessories	2502	3	77
Z	Ref.	Cat.	Page
ZR 35 Copper Tube Cutter 3-35 mm	2104	2	49
ZR 35 Plastic Tube Cutter 3-32 mm	2104	2	52
ZR 35 Stainless Steel Tube Cutter 3-35 mm	2104	2	47
ZR 42 6-40 mm plastic pipe cutter	2104	2	52
ZR 42 Copper Tube Cutter 6-42 mm	2104	2	50

			017030	1	22	050147	2	43	136205 4	91
01	Cat.	Page	017031	1	22	050155	2	43	136206 4	91
			017032	1	22	050157	2	43	136207 4	91
010011	1	14	017033	1	22	050157	7	171	136211 4	91
010012	1	14	017045	1	21	050158	2	43	136212 4	91
010013	1	14	017047	1	21	050160	2	43	136213 4	91
010041	1	14	017050	1	21	050164	7	171	136214 4	91
010042	1	14	017052	1	21	050174	2	43	136215 4	91
010043	1	14	017093	1	22	050175	2	43	136215 4	92
010434	1	14	018202	1	17	050175	2	44	136216 4	92
010449	1	14	018208	1	17	053502	2	42	136217 4	92
010460	1	14	018212	1	17	053504	2	42	136221 4	92
010521	1	15	018218	1	17	053506	2	42	136222 4	92
010534	1	15	018222	1	17	053508	2	42	136223 4	92
010549	1	15	018228	1	17	053510	2	42	136224 4	92
010560	1	15	018230	1	18	053512	2	42	136225 4	92
010590	1	15				053514	2	42	136226 4	92
010610	1	15	04	Cat.	Page	053516	2	42	136227 4	92
010611	1	15				053518	2	42	136231 4	90
010613	1	15	043004	2	36	053520	2	42	136232 4	90
010731	1	15	043006	2	36	053522	2	42	136236 4	90
010732	1	15	043008	2	36	053524	2	42	136241 4	90
010733	1	15	043010	2	36	053526	2	42	136242 4	90
010734	1	15	043012	2	36	053528	2	42	136242 4	91
010735	1	15	045001	2	37	053530	2	42	136243 4	91
010823	1	16	045003	2	37	053532	2	42	136244 4	91
010828	1	16	046002	2	38	053534	2	42	136245 4	91
010838	1	16	046004	2	38	053536	2	42	136246 4	91
010917	1	16	046005	2	38	053538	2	42	136247 4	91
010924	1	16	046010	2	38	053540	2	42	136251 4	91
010930	1	16	046011	2	38			_	136252 4	91
011240	1	16	046013	2	38	11	Cat.	Page	136253 4	91
011324	1	18	046014	2	38				136254 4	91
011600	1	18	049000	2	36	110101	4	84	136255 4	91
011610	1	18	049050	2	36	110105	4	84	136256 4	91
011620	1	18	049070	2	36	110112	4	84	136257 4	91
012520	1	19	05	0-4	Dawa	110200	4	84	136263 4	87
012525 012535	1	19	05	Cat.	Page	110202	4	84	136267 4	86 86
012535	1	19	050040	0	40	110505	4	84 84	136270 4 136280 4	
012545	1	19 19	050043 050049	2	43	110605	4	04		87 87
012590	1	19	050049	2	44	12	Cat.	Page	136281 4 136282 4	87
013614	1	19	050033	2	39	12	Cat.	Page	136284 4	87
013618	1	19	050110	2	39	124501	4	85	136290 4	87
013624	1	19	050111	2	43	124502	4	85	136292 4	87
013735	1	19	050112	2	43	124503	4	85	136294 4	87
013745	1	19	050114	2	43	124504	4	85	136295 4	87
013760	1	19	050115	2	43	126500	4	85	136301 4	86
013790	1	19	050116	2	39	126503	4	85	136311 4	86
013806	1	20	050119	2	43	126504	4	85	136341 4	90
013808	1	20	050120	2	40	126505	4	85	136342 4	90
013810	1	20	050121	2	40	126513	4	85	136343 4	90
013812	1	20	050121	2	41	126514	4	85	136345 4	90
013814	1	20	050122	2	43	126520	4	85	136361 4	86
013818	1	20	050123	2	43	126599	4	85	136408 4	91
013824	1	20	050124	2	43	127500	4	85	136418 4	92
013836	1	20	050125	2	43	127505	4	85	136428 4	92
013848	1	20	050126	2	40	127506	4	85	136438 4	90
014100	1	20	050130	2	41	127599	4	85	136439 4	90
014200	1	21	050132	2	43				136448 4	91
014210	1	21	050133	2	43	13	Cat.	Page	136449 4	91
017006	1	23	050136	2	41				136458 4	91
017008	1	23	050139	2	43	136095	4	87	136459 4	91
017010	1	23	050141	2	43	136201	4	91	136460 4	87
017012	1	23	050144	2	43	136202	4	91	136490 4	87
017015	1	23	050145	2	43	136203	4	91	136494 4	87
017018	1	23	050146	2	43	136204	4	91	136495 4	87

			162610	4	97	210437	2	48	220640	1	31
13	Cat.	Page	162611	4	97	210439	2	48	220900	2	59
			162612	4	97	210441	2	49	220901	2	59
137003	4	92	162613	4	97	210443	2	49	220903	2	59
137004	4	92	162614	4	97	210444	2	49	220906	2	58
137005	4	92	162615	4	97	210445	2	50	220907	2	58
137006	4	92	162616	4	97	210447	2	50	220908	2	58
137007	4	92	162617	4	97	210453	2	51	220910	2	59
137043	4	91	162618	4	97	210454	2	51	220911	2	59
137044	4	91				210455	2	50	220912	2	59
137045	4	91	20	Cat.	Page	210469	2	46	220914	2	59
137046	4	91	_•	· · · · · ·	90	210471	2	47	220916	2	59
137047	4	91	200010	7	164	210475	2	48	220917	2	59
137507	4	90	200020	7	164	210481	2	48	220918	2	59
137550	4	90	200200	7	164	210482	2	48	220920	2	59
137552	4	90	200210	7	164	210483	2	47	220921	2	59
137553	4	90	200210	7	164	210487	2	52	220921	2	59
137562	4	89	200220	7	164	210487	2	53	220924	2	59
137563	4	89	200230	7		210489	2	52	220924	2	59
			-	7	164			_			
138020	4	90	200350		164	210495	2	53	220928	2	59
138021	4	88	200410	7	165	210496	2	53	220930	2	59
138022	4	90	200411	7	165	210497	2	51	220932	2	59
	_	_	200412	7	165	210611	2	53	220934	2	59
16	Cat.	Page	200413	7	165	210621	2	53	220936	2	59
			200415	7	165	210630	2	51	220938	2	59
161100	4	94	200416	7	165	211401	2	55	220940	2	59
162120	4	92	200500	7	165	211402	2	55	220942	2	59
162140	4	93	200900	7	166	211403	2	55	220948	2	59
162150	4	94	200901	7	166	211404	2	55	220952	2	59
162151	4	94	200910	7	166	211405	2	55	220956	2	59
162152	4	94	200911	7	166	211406	2	55	220964	2	59
162153	4	94	201202	7	167	211435	2	53	220966	2	59
162201	4	95				211440	2	53	220972	2	59
162202	4	95	21	Cat.	Page	211464	2	53	220980	2	59
162203	4	95				211501	2	56	221025	6	134
162204	4	95	210110	2	44	211502	2	56	221026	6	134
162205	4	95	210110	2	47	211503	2	56	221027	6	134
162207	4	95	210120	2	44	211512	2	56	221027	6	135
162208	4	95	210121	2	46	211522	2	56	221028	6	135
162209	4	95	210122	2	46	211532	2	56	221029	6	135
162220	4	95	210123	2	48	211627	2	57	221030	6	135
162221	4	95	210125	2	47	211640	2	57	221031	6	135
162301	4	95	210130	2	44	214041	2	55	221032	6	135
162302	4	95	210130	2	47	215032	2	54	221033	6	135
162303	4	95	210141	2	46	215035	2	54	221034	6	135
162304	4	95	210142	2	46	215042	2	55	221035	6	135
162305	4	95	210145	2	45	215060	2	55	221036	6	135
162307	4	95	210165	2	45			00	221037	6	135
162308	4	95	210103	2	45	22	Cat.	Page	221037	6	135
162309	4	95	210210	2	46	22	Out.	. age	221039	6	135
162400	4	96	210211			220205	1	30	221039	6	134
	4			2	46	220305	1	32	221069		
162420 162420	4	96 96	210220 210221	2	45 46	220308 220310	1 1	32 32	221070	<u>6</u> 2	134 60
162421	4	96	210221	2	46	220315	1	32	221128	2	60
162422	4	96	210250	2	45	220318	1	32	221132	2	60
162423	4	96	210251	2	46	220320	1	32	221135	2	60
162424	4	96	210260	2	45	220410	1	23	221137	2	60
162425	4	96	210261	2	46	220420	1	23	221220	2	60
162430	4	96	210261	2	46	220425	1	23	221242	2	60
162431	4	96	210265	2	45	220430	1	23	221250	2	60
162432	4	96	210266	2	46	220435	1	23	221251	2	61
162433	4	96	210266	2	46	220460	1	23	221252	2	61
162460	4	95	210350	2	51	220465	1	23	221261	2	61
162461	4	96	210350	2	51	220510	1	24	221265	2	51
162470	4	95	210352	2	51	220610	1	31	221265	2	53
162471	4	95	210360	2	48	220620	1	31	221265	2	61
162600	4	97	210360	2	48	220630	1	31	221266	2	48

22 Cat. Page 240203 3 72 250216 3 77 2510 240210 3 68 250217 3 77 2510 221266 2 61 240211 3 68 250218 3 77 2510 221276 2 62 240217 3 68 250219 3 77 2510 250217 3 68 250221 3 78 2510)42 3	75 75
240211 3 68 250218 3 77 2510 221266 2 61 240216 3 68 250219 3 77 2510		/5
221266 2 61 240216 3 68 250219 3 77 2510		
)44 3	75
001076 0 60 040017 0 60 050001 0 70 0510)46 3	75
221276 2 62 240217 3 68 250221 3 78 2510)48 3	75
221277 2 <mark>62</mark> 240220 3 69 250222 3 78 2510		75
221278 2 62 240221 3 69 250222 3 78 2510		75
<u>221280 2 62 240222 3 69 250224 3 78 2511</u>		76
<u>221281 2 62 240223 3 69 250225 3 78 2511</u>	08 3	76
221500 2 62 240226 3 70 250226 3 78 2511	10 3	76
221501 2 62 240228 3 69 250227 3 78 2511	12 3	76
240233 3 66 250228 3 78 2511		76
24 Cat. Page 240242 3 66 250229 3 78 2511		76
<u>240243</u> 3 66 <u>250232</u> 3 78 <u>2511</u>		76
<u>240101 3 67 240248 3 71 250233 3 78 2511</u>	18 3	76
240102 3 67 240249 3 66 250234 3 78 2511	21 3	76
240103 3 68 240252 3 66 250235 3 78 2511	22 3	76
240105 3 68 240279 3 66 250236 3 78 2511		76
		76
<u>240107 3 68 240803 3 72 250238 3 78 2511</u>		76
<u>240110 3 68 240811 3 67 250239 3 78 2514</u>	108 3	76
240111 3 68 240842 3 67 250241 3 78 2514	10 3	76
240114 3 68 240843 3 67 250242 3 78 2514	12 3	76
240115 3 68 240851 3 67 250243 3 78 2514		76
240116 3 69 240852 3 67 250244 3 78 2514		76
240117 3 69 250245 3 78 2514		76
240119 3 70 25 Cat. Page 250246 3 78 2518	300	79
240120 3 69 250270 3 77 2518	302 3	80
240122 3 70 250001 3 74 250271 3 77 2518		79
240123 3 70 250002 3 74 250272 3 77 2518		79
240124 3 70 250003 3 74 250273 3 77 2518		80
<u>240125</u> 3 <u>70</u> <u>250010</u> 3 <u>74</u> <u>250275</u> 3 <u>77</u> <u>2518</u>	3 3	80
240141 3 70 250012 3 74 250280 3 77 2518	309	81
240142 3 70 250014 3 74 250282 3 77 2518		80
240143 3 70 250015 3 74 250283 3 77 2518		80
<u>240144 3 70 250016 3 74 250285 3 77 2518</u>		80
240145 3 70 250018 3 74 250286 3 77 2518		80
240146 3 70 250020 3 74 250300 3 73 2518	3 3	80
240147 3 70 250022 3 74 250301 3 73 2518	3 3	80
240148 3 70 250026 3 74 250302 3 73 2518	320	80
240149 3 70 250032 3 74 250303 3 73 2518		80
		81
<u>240152 3 70 250053 3 74 250305 3 73 2518</u>		81
240153 3 70 250130 3 75 250306 3 73 2518	326	81
240154 3 70 250131 3 75 250401 4 98 2518	328	81
240155 3 70 250132 3 75 250402 4 98 2518	329 3	81
240156 3 70 250159 3 74 250403 4 98 2518		81
	-	81
<u>240161 3 71 250161 3 74 250412 4 98 2518</u>		81
240162 3 71 250162 3 74 250413 4 98 2518	334 3	81
240163 3 71 250163 3 74 250421 4 98 2518	335 3	81
240164 3 71 250164 3 74 250422 4 98 2518		81
240165 3 71 250165 3 74 250423 4 98 2518		81
<u>240166</u> <u>3</u> <u>71</u> <u>250166</u> <u>3</u> <u>74</u> <u>250431</u> <u>4</u> <u>98</u> <u>2518</u>		81
<u>240167 3 71 250167 3 74 250432 4 98 2518</u>		81
<u>240168</u> 3 <u>71</u> <u>250168</u> 3 <u>74</u> <u>250433</u> 4 <u>98</u> <u>2518</u>	344 3	81
240169 3 71 250170 3 74 250434 4 98 2518	344 4	113
240170 3 71 250171 3 74 250435 4 98 2518		79
240171 3 71 250172 3 74 250441 4 98 2518		79
<u>240172</u> <u>3</u> <u>71</u> <u>250173</u> <u>3</u> <u>74</u> <u>250442</u> <u>4</u> <u>98</u> <u>2518</u>		80
<u>240173</u> 3 <u>71</u> <u>250174</u> 3 <u>74</u> <u>250443</u> 4 <u>98</u> <u>2518</u>	-	80
<u>240174</u> 3 <u>71</u> <u>250200 3 <u>77</u> <u>250447 4 <u>98</u> <u>2518</u></u></u>	3 3	79
240175 3 71 250201 3 77 250580 4 99 2518	352 3	80
240177 3 71 250203 3 77 250620 4 99 2518		79
240178 3 71 250208 3 77 251010 3 75 2518		80
<u>240179 3 71 250210 3 77 251012 3 75 2518</u>		81
<u>240185 3 71 250211 3 77 251014 3 75 2518</u>		81
240200 3 72 250212 3 77 251015 3 75 2518	366	81
240200 3 77 250213 3 77 251016 3 75 2518		81
240201 3 72 250214 3 77 251018 3 75 2518		81
240202 3 <u>72</u> 250215 3 <u>77</u> 251020 3 <u>75</u> 2518	3 3	81

			050040		404	050000		400	050000 4	440
4-			252610	4	101	252862	4	103	253008 4	116
25	Cat.	Page	252611	4	100	252863	4	103	253009 4	115
			252611	4	101	252864	4	103	253009 4	116
251882	3	81	252612	4	100	252880	4	102	253011 4	115
251883	3	81	252612	4	101	252883	4	102	253011 4	116
252500	4	115	252613	4	100	252902	4	114	253012 4	115
252501	4	115	252613	4	101	252903	4	114	253012 4	116
252502	4	115	252614	4	100	252904	4	114	253013 4	115
252502	4	115	252614	4	101	252905	4	114	253013 4	116
252504	4	115	252615	4	100	252906	4	114	253017 4	115
252505	4	115	252615	4	101	252907	4	114	253017 4	116
252506	4	115	252616	4	100	252908	4	114	253050 4	115
252507	4	115	252616	4	101	252909	4	114	253050 4	116
252508	4	115	252622	4	100	252910	4	107	253051 4	115
252509	4	115	252622	4	101	252911	4	114	253051 4	116
252510	4	115	252623	4	100	252912	4	107	253052 4	115
252512	4	115	252623	4	101	252913	4	107	253052 4	116
252514	4	115	252624	4	100	252915	4	114	253053 4	115
252516	4	115	252624	4	101	252916	4	114	253053 4	116
252517	4	115	252625	4	100	252917	4	114	253054 4	115
252518	4	115	252625	4	101	252918	4	114	253054 4	116
252519	4	115	252626	4	100	252919	4	114	253055 4	115
252520	4	115	252626	4	101	252921	4	107	253055 4	116
252521	4	115	252627	4	100	252922	4	107	253056 4	115
252523	4	115	252627	4	101	252938	3	81	253056 4	116
252524	4	115	252628	4	100	252938	4	113	253057 4	115
252525	4	115	252628	4	101	252942	4	113	253057 4	116
252526	4	115	252632	4	100	252943	4	113	253058 4	115
252527	4	115	252632	4	101	252945	4	113	253058 4	116
252528	4	115	252633	4	100	252946	4	113	253059 4	115
							4			
252529	4	115	252633	4	101	252948		113	253059 4	116
252530	4	115	252634	4	100	252949	4	113	253060 4	115
252531	4	115	252634	4	101	252951	4	113	253060 4	116
252532	4	115	252635	4	100	252952	4	113	253061 4	115
252545	4	115	252635	4	101	252953	4	113	253061 4	116
252546	4	115	252637	4	100	252954	4	113	253062 4	115
252547	4	115	252640	4	100	252955	4	113	253062 4	116
252548	4	115	252641	4	100	252961	4	114	253063 4	115
252549	4	115	252644	4	100	252962	4	114	253063 4	116
252550	4	115	252651	4	100	252963	4	114	253064 4	115
252556	4	115	252679	4	100	252964	4	114	253064 4	116
252590	4	115	252681	4	100	252965	4	114	253065 4	115
252591	4	115	252701	4	102	252966	4	114	253065 4	116
252592	4	115	252702	4	102	252967	4	114	253066 4	115
252593	4	115	252703	4	102	252981	4	113	253066 4	116
252594	4	115	252711	4	102	252982	4	113	253067 4	115
252595	4	115	252712	4	102	252983	4	113	253067 4	116
252600	4	100	252714	4	102	252984	4	113	253068 4	115
252601	4	100	252715	4	102	252986	4	113	253068 4	116
252601	4	101	252717	4	102	252987	4	113	253069 4	115
252602	4	100	252719	4	102	252988	4	113	253069 4	116
252602	4	101	252730	4	102	252989	4	113	253090 4	115
252603	4	100	252801	4	103	253001	4	115	253090 4	116
252603	4	101	252802	4	103	253001	4	116	253091 4	115
252604	4	100	252804	4	103	253002	4	115	253091 4	116
252604	4	101	252806	4	103	253002	4	116	253092 4	115
252605	4	100	252810	4	103	253003	4	115	253092 4	116
252605	4	101	252812	4	103	253003	4	116	253095 4	115
252606	4	100	252814	4	103	253004	4	115	253095 4	116
252606	4	101	252815	4	103	253004	4	116	253096 4	115
252607	4	100	252816	4	103	253005	4	115	253096 4	116
252607	4	101	252818	4	103	253005	4	116	253097 4	115
252608	4	100	252820	4	103	253006	4	115	253097 4	116
252608	4	101	252822	4	103	253006	4	116	253097 4	115
252609	4	100	252830	4	102	253007	4	115	253098 4	116
252609	4	101	252860	4	103	253007	4	116	253102 4	115
252610	4	100	252861	4	103	253008	4	115	253102 4	116

			253276	4	114	261410	1	25	264510	6	138
25	Cat.	Page	253277	4	114	261420	1	26	264511	6	138
			253278	4	114	261450	1	26	264513	6	138
253104	4	115	253281	4	114	261460	1	26	264514	6	138
253104	4	116	253300	4	106	261470	1	26	264515	6	138
253105	4	115	253302	4	106	261500	1	25	264516	6	138
253105 253106	4	116 115	253303 253312	4	106 106	261501 261502	1	25 25	264518 264519	6	138 138
253106	4	116	253316	4	106	261620	1	27	264521	6	138
253107	4	115	253320	4	106	262005	6	136	264524	6	138
253107	4	116	253325	4	106	262015	6	136	264535	6	138
253108	4	115	253332	4	106	262035	6	136	264540	6	138
253108	4	116	253333	4	106	262070	6	137	264542	6	138
253110	4	115	253334	4	106	262080	6	135	264544	6	138
253110	4	116	253335	4	106	262111	6	137	264550	6	138
253111	4	115	253350	4	105	262111	6	138	264560	6	138
253111	4	116	253355	4	105	262112	6	137	00	0-4	Dawa
253112 253112	4	115 116	253360 253361	4	105 105	262112 262113	6	138 137	29	Cat.	Page
253112	4	115	253380	4	106	262113	6	138	290000	6	141
253113	4	116	253381	4	106	262114	6	137	290120	6	140
253114	4	115	253401	4	101	262114	6	138	290121	6	140
253114	4	116	253402	4	101	262115	6	137	290122	6	140
253115	4	115	253403	4	101	262115	6	138	290132	6	140
253115	4	116	253412	4	101	262116	6	137	290140	6	140
253116	4	115	253416	4	101	262116	6	138	290141	6	140
253116	4	116	253425	4	101	262117	6	137	290142	6	140
253117	4	115	253432 253480	4	101	262117	6	138	290145	6	140
253117 253118	4	116 115	253480	4	101	262118 262118	6	137 138	290146 290150	6	140 142
253118	4	116	253500	4	108	262120	6	137	290150	6	142
253119	4	115	253500	4	109	262120	6	138	290210	6	141
253119	4	116	253501	4	108	262122	6	137	290215	6	141
253126	4	115	253501	4	109	262122	6	138	290400	6	144
253126	4	116	253502	4	108	262123	6	137	290510	6	142
253127	4	115	253502	4	109	262123	6	138	290512	6	143
253127	4	116	253505	4	113	262124	6	137	290520	6	142
253128	4	115	253506	4	113	262124	6	138	290600	6	143
253128 253129	4	116 115	253507 253508	4	113 113	262126 262126	6	137 138	290602 290605	6	143 143
253129	4	116	253510	4	108	262130	6	137	290640	6	143
253130	4	115	253510	4	109	262130	6	138	290645	6	144
253130	4	116	253511	4	108	262132	6	137	290646	6	144
253131	4	115	253511	4	109	262132	6	138	290647	6	144
253131	4	116	253512	4	108	262181	6	137	291000	6	145
253132	4	115	253512	4	109	262182	6	137	291001	6	145
253132	4	116	253513	4	108	262191	6	137	291200	6	146
253133	4	115	253513	4	109	262600	4	104	291201	6	146
253133 253134	4	116 115	253514 253514	4	108 109	262601 262630	6	104	291221 291223	6	146 146
253134	4	116	253514	4	109	262700	1	136 27	292030	6	147
253135	4	115	253516	4	109	262800	7	167	293130	6	148
253135	4	116	253517	4	108	262801	7	167	293131	6	148
253244	3	81	253517	4	109	263120	1	28	293132	6	148
253244	4	113	253518	4	108	263122	1	28	293133	6	148
253251	4	113	253518	4	109	263125	1	27	293134	6	148
253252	4	113	253519	4	108	263150	1	29	293135	6	148
253253	4	113	253519	4	109	263605	6	139	293140	6	148
253254 253255	4	114	253520 253521	4	110 110	263620 263625	6	139 139	293230 293233	6	149 151
253257	4	113	253521	4	110	263626	6	139	293234	6	151
253261	4	111	253523	4	110	264500	6	138	293235	6	151
253262	4	111	253524	4	110	264501	6	138	293236	6	151
253263	4	111	253525	4	110	264502	6	138	293272	6	151
253266	4	114	253630	4	112	264503	6	138	293273	6	151
253268	4	114				264504	6	138	293277	6	151
253271	4	114	26	Cat.	Page	264505	6	138	293278	6	151
253272 253273	4	114	261000	1	100	264506 264507	6	138	293280 294021	6	150 156
253273	4	114	261000 261010	4	103	264507	6 6	138	294021	6 6	157
253274	4	114	261400	1	25	264509	6	138	294021	6	156
200210	-	11-7	_01400	'	20	_0-000	J	100	_U-ULL	J	100

29	Cat.	Page
	ou	. ago
294022	6	157
294023	6	156
294023	6	157
294027 294027	6	156 157
294027	6	156
294028	6	157
294031	6	156
294031	6	157
294033	6	156
294033	6	157
294034	6	156
294034	6	157
294035	6	155
294041	6	156
294041	6	157
294042	6	156
294042 294043	6	157 156
294043	6	157
294045	6	155
294050	6	155
294051	6	155
294052	6	155
294053	6	155
294054	6	155
294110	6	152
294112	6	156
294112	6	157
294120	6	152
294121	6	152
294130	6	153
294135 294140	6 6	153 154
294145	6	154
294150	6	154
295000	6	157
295010	6	159
295015	6	159
295020	6	157
295022	6	160
295025	6	159
295026	6	159
295027	6	159
295027	6	160
295050	6	158
295051	6	160
295052	6	160
295053 295054	6	158 158
295054	6	159
295056	6	159
295057	6	160
295058	6	160
295059	6	158
31	Cat.	Page
310325	1	24
311458	1	29
33	Cat.	Page
335000	1	29

335010	1	29
34	Cat.	Page
341801	1	30
341802	1	30
341803	1	30
341804	1	30
341805	1	30
341806	1	30
341807		30
341808	1	30
341820 342500	<u>1</u> 1	30
342501	<u>'</u> 1	30
342510	1	31
342511	1	30
342520	1	31
342521	1	31
36	Cat.	Page
360000	6	160
360020	6	160
37	Cat.	Page
371741	1	32
371741	'	32
371744	. 1	32
371745	1	32
38	Cat.	Page
382620	7	170
382621	7	170
382640	7	
	7	170
382641	7	170
382641 382650	7 7	170 169
382641	7	170 169 169
382641 382650 382651 382652	7 7 7	170 169 169 30
382641 382650 382651	7 7 7 1	170 169 169
382641 382650 382651 382652 382653	7 7 7 1 7 7	170 169 169 30 168
382641 382650 382651 382652 382653 382655 382660 382670	7 7 7 1 7 7 7	170 169 169 30 168 169 169
382641 382650 382651 382652 382653 382655 382660	7 7 7 1 7 7	170 169 169 30 168 169
382641 382650 382651 382652 382653 382655 382660 382670	7 7 7 1 7 7 7	170 169 169 30 168 169 169
382641 382650 382651 382652 382653 382655 382660 382670 382685	7 7 7 1 7 7 7 7	170 169 169 30 168 169 169 170
382641 382650 382651 382652 382653 382655 382660 382670 382685	7 7 7 1 7 7 7 7 7 7 7 7 7 Cat.	170 169 169 30 168 169 169 170 170
382641 382650 382651 382652 382653 382655 382660 382670 382685 52	7 7 7 1 7 7 7 7 7 7 7 7 7 5 5 5 5	170 169 169 30 168 169 170 170 170 Page
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012	7 7 7 1 7 7 7 7 7 7 7 7 7 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520013	7 7 7 7 7 7 7 7 7 7 7 7 6 Cat. 5 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520013 520014	7 7 7 1 7 7 7 7 7 7 7 7 7 5 5 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520013 520014 520020	7 7 7 7 7 7 7 7 7 7 7 7 6 Cat. 5 5 5 5 5 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 120 121 121 121 121
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520014 520020 520021	7 7 7 7 7 7 7 7 7 7 7 7 7 5 5 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121 121 121 121
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520014 520020 520021 520022	7 7 7 7 7 7 7 7 7 7 7 7 7 6 6 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121 121 121 121 121
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520014 520020 520021 520022 520025	7 7 7 7 7 7 7 7 7 7 7 7 7 7 5 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121 121 121 121 121 121 12
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520013 520014 520020 520021 520022 520025 520042	7 7 7 7 7 7 7 7 7 7 7 7 7 7 5 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121 121 121 121 121 121 12
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520013 520014 520020 520021 520022 520025 520042 520050	7 7 7 7 7 7 7 7 7 7 7 7 7 7 6 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121 121 121 121 121 121 12
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520013 520014 520020 520021 520022 520025 520042 520050 520051	7 7 7 7 7 7 7 7 7 7 7 7 7 7 6 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121 121 121 121 121 121 12
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520013 520014 520020 520021 520022 520025 520042 520050 520061	7 7 7 7 7 7 7 7 7 7 7 7 7 7 5 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121 121 121 121 121 121 12
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520013 520014 520020 520021 520022 520025 520042 520050 520051	7 7 7 7 7 7 7 7 7 7 7 7 7 7 6 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121 121 121 121 121 121 12
382641 382650 382651 382652 382653 382655 382660 382670 382685 52 520000 520001 520011 520012 520013 520014 520020 520021 520022 520025 520042 520050 520061 520500	7 7 7 7 7 7 7 7 7 7 7 7 7 7 5 5 5 5 5 5	170 169 169 30 168 169 170 170 170 Page 120 121 121 121 121 121 121 121 121 12

520511	5	120
521000	5	122
521001	5	122
521010	5	122
521011	5	122
521012	5	122
521020	5	122
521021	5	122
521030	5	123
521030	5	123
521050	5 5	122
521060		122
521200	5	123
521516	5	123
521560	5	123
521562	5	123
521565	5	124
521700	5	124
521720	5	124
521721	5	125
521724	5	125
521725	5	125
521726	5	125
521735	5	124
521740	5	124
521741	5	124
521850	5	126
521855	5	126
521860	5	126
523020	5	125
523021	5	125
523022	5	125
523029	5	126
524000	5	125
524010	5	125
524054	5	125
524070	5	125
525000	5	127
525013	5	127
525014	5	127
525021	5	127
525022	5	127
525023	5	127
======		
525070	<u>5</u>	127 127
525072	<u>5</u>	
525090		127
526000	5	128
526001	5	128
526010	5	128
526020	5	128
527022	5	128
527030	5	129
527032	5	129
527033	5	129
527038	5	129
528012	5	129
528013	5	129
528030	5	129
528037	5	129
528040	5	129
528210	5	129
528211	5	129
528260	5	130
528265	5	130
528270	5	130
528280	5	130
528282	5	130

75	Cat.	Page
528420	5	131
528420	5	129
528400	5	131
528346	5	130
528346	5	129
528294	5	130
528290	5	130
528285	5	130

Cat.	Page
2	57
4	95
4	95
4	95
4	95
4	95
4	113
4	105
4	105
4	105
4	105
6	160
	2 4 4 4 4 4 4 4 4 4 4 4

99	Cat.	Page
990010	4	113
990019	4	114
990020	4	113
990020	4	114
990034	4	114
990035	4	115
990035	4	116
990036	4	115
990036	4	116
990056	4	115
990056	4	116
990057	4	115
990057	4	116
990058	4	114
990059	4	114
990062	4	115
990062	4	116
990063	4	114
990066	4	113
990113	4	115
990113	4	116
990156	4	113

ALL SYSTEMS COMPATIBLE WITH VIRAX JAWS AND INSERTS.

COPPER

BRASS / BRONZE

STEEL / CARBON STEEL MULTI-LAYER / PE-RT COPPER PEX / PB / PER / PE D SYSTÈME/SYSTEM Ø AC-FIX Press 12-16-20-25-32 RF-P / U H/U RF-P / H-ML / U 16-18-20-32 H/U AC-FIX Press-Multi RF-P / U ACOME MT 12-16-20-25 RF-P М 12-15-18-22-28 M AHLSELL A-press elforzinkad M 12-15-18-22-28 35-42-54 AHLSELL A-press koppar 12-15-18-22-28 М M AHLSELL A-press rostfritt M М 12-15-18-22-28 AIRBEL Pressclim 15-18-22-28 M M AIRBEL Sertinox M 14-16-18-20-32 H-ML/TH/U H/TH/U ALB Sistema multicapa H-ML/TH H/TH ANQUIER Aser RF-P 14-16-18-20-26-32 APE Raccordi a pressare 40-50-63 Ü 14-16-18-20-26-32 TH TH BAMPI Balpex 40-50 TH RF-P / U BARBI Easypress 12-16-20-25-32 H/U RF-P / H-ML / U / TH 16-20-32 TH/H/U H-ML / U H/U BARBI Multipex RF-P / U H/U 26 TH / H-ML TH/H 40-50-63 16-20-25-32 U RF-P BRASELLI Pressfitting PE-X 16-18-20-25-32 U U BRASELLI Pressfitting Multicapa 40-50 M/V BROEN Ballofix Pres 15-18-22 M/V BROSSETTE Eurobasic 12-16-20-25 RF-P 14-16-20-26-32 TH TH BUCCHI tech MP 15-18-22-28 M M CHIBRO Pressfitting M 14-16-18-20-25-32 U COES Coesklima K-Fit 40-50 63-75 COMAP PexPress Altech 12-16-20-25 RF-P 14-16-18-20-26-32 TH TH COMAP SkinPress 40-50-63 12-14-15-16-18-22-28 TH COMAP Sudopress Cu 35-42-54 12-15-18-22-28 М M COMAP XPress 35-42-54 М 15-18-22-28 35-42-54 М COMAP XPress H-ML/TH H/TH 14-16-18-20-26-32 COMISA Evo Press TH 40-50-63 TH U/TH COMPTOIR DE PICARDIE 16-20 U/TH

16-20-32

TH / H-ML / U

TH / H-ML

TH/H/U

TH/H

FRABO Multi-Brass

FRABO Multi-Plus

FRANKISCHE Alpex Duo-Alpex L

FRANKISCHE Alpex Duo XS

FRIATEC Friatherm Uni

FRANKISCHE Turatec System



SYSTÈME/SYSTEM	*	Ø		1
D				
DALPEX Laser Multi Dalpex		14-16-18-20-26-32	TH	TH
<u> </u>		40-50-63 14-16-18-20-26-32	- TH	TH TH
DIWA Flex Systems		40	-	TH
DUOFIL Maximétal		16-20-32 16-20-25-32	RF-P / U U	U
DW VERBUNDROHR Multitubo		40-50-63-75	-	Ü
E		16-18-20-25-32	U	U
EBRILLE Monflex		40-50-63-75	-	Ü
EFFEBI Presstige		15-18-22-28	M/V	M/V
		35 16-18-20-32	- TH / H-ML / U	M/V TH/H/U
EFFEBI Tof Multipinza		25	TH/U	TH/H/U
		26 15-18-22-28	TH / H-ML M	TH/H M
EMCAL C-Stahl		35	-	M
EMCAL Perfect Aqua		16-20-25-32	U	U
		40-50-63 16-20-26-32	- TH	TH
EMCAL Presso		40	-	TH
EMCAL PRESSO Nox		15-18-22-28 35	M -	M M
EMMETI Gerpex-Fivpress		14-16-18-20-26-32	TH	TH
· · ·		40-50 15-18-22-28	- M	TH M
ESTA ROHR Simplesta		35	- IVI	M
EUROTUBI EUROPA Pressfitting System		12-15-18-22-28	M	M
		35 12-15-18-22-28	- M	M
EUROTUBI EUROPA Pressfitting System		35	-	М
F		14-16-18-20-32	H-ML/TH/U	H/TH/U
		25	TH/U	H/TH/U
FAR RUBINETTERIE Pressfar		26 40	H-ML/TH	H/TH H/TH/U
		50-63	-	TH/U
FBQ BARONIO BQ press rame		12-14-15-16-18-22-28	V	V
·		35-42-54 15-18-22-28	- V	V
FBQ BARONIO BQ press carbon steel		35-42-54	-	V
FERCOFLOOR Duo Press Ferco Pex		16-20-25-32 16-20-25-32	RF-P / TH / U RF-P / TH / U	TH/U TH/U
FERCOFLOOR Duo Press Multifer		18	TH/U	TH/U
FG Stainless STEEL		15-18-22-28 35	M	M M
FILTLIDE Instalances		12-15-18-22-28	M	M
FILTUBE Instalpress		35-42-54	-	M
FILTUBE Instalpress		15-18-22-28 35-42-54	M -	M M
FITTINGS ESTANDAR Eco-Press		16-20-25-32	RF-P	-
FITTINGS ESTANDAR MULTICAPA		16-20-25-32 18	RF-P / U U	U
FITTINGS ESTANDAR PEX - A		16-20-25-32	RF-P / U	U
FORNARA SPA		16-20-26-32	TH	TH
FRABO Frabopress C-Steel		15-18-22-28 35-42-54	<u> </u>	V V
FRABO Frabopress H2O		12-15-18-22-28	V	V
<u> </u>		35-42-54 15-18-22-28	- V	V
FRABO Frabopress 316		35-42-54		V

16-20

26-32

16-20-32

16-20-26-32

16-20-26-32

16-20-26-32 16-20-26-32

40

50-63

Multiquick NTM

CONEL Connect Multi

TH/U

TH

H/U

TH

TH

TH Н

Ή

TH

TH/U

TH

H-ML / U

H-ML

TH

H-ML

ALL SYSTEMS COMPATIBLE WITH VIRAX JAWS AND INSERTS.

* MATERIAL STEEL / CARBON STEEL	MULTI-LAYER / PE-RT COI			COPPER BRASS / BRONZE STAIN	LESS STEEL 😾 🗸		
SYSTÈME/SYSTEM	* Ø			SYSTÈME/SYSTEM	* Ø		7
3	12-15-18-22-28	l M	M	K	16-20-25-32	TH/U	TH/U
GEBERIT MAPRESS	35	- 191	M	KAN Kan-Therm	26 40	TH	TH
GEBERIT MAPRESS	14-16 12-15-18-22-28	- M	M M	IVAN Nati Hicilii	40 50-63	-	TH/U TH
ILDENII WAFNEGO	35	-	M	KAN Kan-Therm	15-18-22-28	M	M
EBERIT MAPRESS	12-15-18-22-28 35	M -	M M	NAN NAII-THEITH	35-42-54 16-20-25-32	- TH/U	M TH/U
EBERIT Mepla	16-20-26-32	G	G G	KAN Kan-Therm LBP	26	TH	TH
EDEKIT WEPIA	40-50 14-16-18-20-32	- H-ML/TH/U	G H/TH/U	NAN KAII- IIIBIIII LDP	40 50-63	-	TH/U TH
	25	TH/U	H/TH/U	VAN Van Tharm	15-18-22-28	- M	M
SENERAL FITTINGS Series 5S00	26	H-ML / TH	H/TH	KAN Kan-Therm	35-42-54	-	M
	40 50	-	H/U TH/U	KE KELIT Kelox	16-20-25-32 40-50-63-75	<u>U</u>	U U
	16-20-32	H-ML / TH / U	H/TH/U	KE KELIT Steelfix	15-18-22-28	M	M
GIACOMINI Multistrato/Giacoflex/Giacotherm	26 40-50	H-ML / TH	H/TH U		35-42-54 15-18-22-28	- M	M
SLOBAL PIPING SYSTEM Ac-Fix Press	12-16-20-25-32	RF-P / U	H/U	KE KELIT Steelfix	35-42-54	-	M
SLOBAL PIPING SYSTEM Ac-Fix Press-Multi	16-18-20-32	H-ML / RF-P / U	H/U	KING INDUSTRIAL Press-ID	12-16-20-25-32	RF-P	H
SLOBAL TRADE Aqualpress System	25 16-20-25-32	RF-P / U U	H/U U	KME Q-tec COMAP connector Oventrop connector	14-16-20-26 16-20-26	TH HA	TH HA
OLAN	16-18-20-25-32	Ü	U	KOHLER Inox Pres	15-18-22-28	M	M
00 111	40-50-63	-	U	N	35	-	M
AKA GERODUR Hakathen-L	14-16-18-20-26-32	TH	TH	NICOLL Fluxo	16-20-26-32	TH	TH
AMMEL ROBINETTERIE	12-14-15-16-18-22-28 32-42-54	V	V V	THOOLE TIMO	40-50-63 14-16-18-20-25-32	- TH/U	TH TH/U
IAMMEL ROBINETTERIE	16-20-26	TH	TH	N.T.M Winny-AL	26	TH	TH.
AMMEL ROBINETTERIE	12-16-20-25 16-20-26-32	RF-P	H	IV. I.IVI VVIIIIIY-AL	40-50 63	-	TH/U
EIMA Press-Fittings	40-50	TH -	TH TH	AUDIO AUDIOFOO M. Itimus!	14-16-18-20-32	- U	U
ELIROMA Klimapress	16-18-20-25-32	U	U	NUPI & NUPIGECO Multinupi	40-50-63	-	Ü
ELIROMA Romapress	40-50-63-75 16-20-25-32	- RF-P	U -	0	16-20-26-32	HA	HA
ENCO PE-Xc/AL/PE-Xc	14-16-18-20-26	TH	TH	OVENTROP Cofit P	40	-	HA
EROTEC Tempuss-press	14-16-20-26-32 40	TH -	TH TH	P	63	-	U
ERZ Pipefix	14-16-18-20-25-26-32	TH	TH	PB TUB Sertipress	12-16-20-25	RF-P	Н
-1 IZ T IPOIIX	40-50-63	-	TH	PB TUB Serti-Steel	12-15-18-22-28 35	M	M M
	16-18-20-25-32	U	U	PB TUB Alpex Duo & Turatec	16-20-26-32	TH	TH
BP >B <flex f5<="" td=""><td>40-50-63-75</td><td>-</td><td>U</td><td>PERFILTUBO Perfialupex</td><td>16-18-20-25-32</td><td>U</td><td>U</td></flex>	40-50-63-75	-	U	PERFILTUBO Perfialupex	16-18-20-25-32	U	U
BP >B <flex f9<="" td=""><td>16-20-25-26-32</td><td>TH</td><td>TH</td><td>DEDELITION D. (*</td><td>40-50-63 15-18-22-28</td><td>- M</td><td>U M</td></flex>	16-20-25-26-32	TH	TH	DEDELITION D. (*	40-50-63 15-18-22-28	- M	U M
BP >B <press< td=""><td>12-14-15-16-18-22-28 35-42-54</td><td>V -</td><td>V V</td><td>PERFILTUBO Perfipress</td><td>35-42-54</td><td>-</td><td>M</td></press<>	12-14-15-16-18-22-28 35-42-54	V -	V V	PERFILTUBO Perfipress	35-42-54	-	M
BP >B <press< td=""><td>15-18-22-28</td><td>V</td><td>V</td><td>PEXTUBE Pextube PIETRO RAVANI</td><td>16-20-25-32 16-18-20-26-32</td><td>RF-P TH</td><td>- TH</td></press<>	15-18-22-28	V	V	PEXTUBE Pextube PIETRO RAVANI	16-20-25-32 16-18-20-26-32	RF-P TH	- TH
	35-42-54 15-18-22-28	- V	V	PIPELIFE RADOPRESS	16-18-20-26-32	TH	TH
BP >B <press carbon<="" td=""><td>35-42-54</td><td>-</td><td>Ÿ</td><td>I II LLII L IIMUUFILOO</td><td>40-50-63 16-18-20-25-32</td><td>- U</td><td>TH</td></press>	35-42-54	-	Ÿ	I II LLII L IIMUUFILOO	40-50-63 16-18-20-25-32	- U	TH
ROSANITARIA BONOMI Idropress	16-18-20-26-32	TH	TH	POLYSAN Rainbow	40-50-63	-	U
<u> </u>	40-50-63 15-18-22-28	- M	TH M	PF connectors	16-20-26-32	H-ML	Н
TA INOX Chibro Pressfitting	35	-	M	PRANDELLI Multyrama	40-50 16-20	- H-ML / TH / U	U H/TH/
	14 16-20-32	H-ML U / RF-P / H-ML / TH	H U/H/TH	PFM connectors	26-32	H-ML / TH	H/TH
IDUSTRIAL BLANSOL Multipex	18	U / H-ML	U/H	R	15_10 22 20	M	l M
IDOO MIAL DLANGUL WUUUPEX	25	U / RF-P	U/H	RACCORDERIE METALLICHE (RM) Inoxpres	15-18-22-28 35	IVI -	M
	26 40-50-63	H-ML/TH -	H/TH U	RACCORDERIE METALLICHE (RM) Steelpres	15-18-22-28	M	M
ISTAL PRESS Carbon Steel	12-15-18-22-28	M	M		35 14-16-18-20	TH / H-ML / U	TH/H/
	35 14-16-18-20-26-32	- TH	M TH	RBM Tita-fix	26-32	TH / HM-L	TH/H
'A Ipalpex	40-50-63	-	TH		40-50-63 16-20-25-32	- U	TH U
SOLTUBEX Isolpex	16-20-25-32 16-20-25-32	RF-P RF-P / U	- U	RIFENG Raccords F5	40-50-63-75	-	U
SOLTUBEX	18	KF-P / U	U	RIFENG Raccords F9	16-20-25-26-32	TH	TH
OTUBI Numepress	15-18-22-28	M	M	RIQUIER A sertir RUBINETTERIE BRESCIANE BONOMI	12-16-20-25 15-18-22-28	RF-P M	H M
WD.W. W. D.	16-18-20-32 25	TH/H-ML/U TH/U	TH/H/U TH/H/U	CU-NI turbo	35	-	M
'AR Multi-Press	25 26	TH / H-ML	TH/H	RUBINETTERIE BRESCIANE BONOMI Stainless steel turbo	15-18-22-28 35	M -	M M
	40-50	- TU / U MI / II	TH/U	RUBINETTERIE BRESCIANE BONOMI	15-18-22-28	M	M
'AR Plastic-Multi-Press	16-20-32 25	TH/H-ML/U TH/U	TH/H/U TH/H/U	Steel turbo	35	-	M
	25 26	TH / H-ML	TH/H	RUBINETTERIE BRESCIANE BONOMI	14-16-18-20-32 26	TH / H-ML / U TH / H-ML	TH/H/I
				Press turbo	40-50-63	I III/ H∃WL	1 1117/11

ALL SYSTEMS COMPATIBLE WITH VIRAX JAWS AND INSERTS.

MATERIAL STEEL / CARBON ST	EEL MULTI-LAYER / PE-RT COP	PPER PEX / PB /	PER / PE (COPPER BRASS / BRONZE STAINL	ESS STEEL		
/STÈME/SYSTEM	* Ø	S	7	SYSTÈME/SYSTEM	* Ø		7
			_	V			
	16-20-32	TH/U	TH/U	·	16-20	H-ML/TH/U	H/
ANHA 3 fit-press	26	TH	TH	Valsir Mixal	26	H-ML / TH	H
	40-50 14-16	- V	TH V/M		32 14	H-ML / TH / U H-ML / H	H/
	12-15-18-22-28	V/M	V / M		16-20	H-ML / TH / U	H/
ANHA Pressfittings	35		V / M	Valair Daval (laiter (lavaes)	26	H-ML / TH	
	42-54	- V	V	Valsir Pexal (laiton/brass)	32	H-ML / TH / U	H/
	15-18-22-28	M / V	M/V		40-50-63	-	T
ANHA NiroSan	35	-	M/V		75-90	- 	11.7
	42-54 12-15-18-22-28	- M / V	V M/V	VALSIR (PPSU) Bravopress	16-20-32 26	H-ML/TH/U	H/
ANHA Therm	35		M / V	VAN MARCKE Tubipex Alu	16-18-20-26-32	H-ML / TH TH	H
IIIIIIII ATIIII	42-54	- -	V V		12-15-18-22-28	V	+
DUMED A	15-18-22-28	M	M	VIEGA Prestabo	35-42-54	-	
CHWER Aquapress	35-42-54	-	M	VIEGA Profipress	12-14-15-16-18-22-28	V	
ESTA Sistema multistrato	16-20	H-ML/TH/U	H/TH/U	· ·	35-42-54	-	
	18-26-32	TH	TH	VIEGA Sanpress	12-14-15-16-18-22-28	V	
DMATHERM Somex Multi	16-20-32 26	TH / H-ML / U TH / H-ML	TH/H/U TH/H	Bronze connectors for stainless steel pipes	35-42-54 15-18-22-28	- V	-
DMATHERM Somapress	12-16-20-25-32	RF-P / U	H/U	VIEGA Sanpress inox	35-42-54	- V	
TPC Sopalpex Fit	16-20-26	TH	TH	VOLUCIONA	14-16-18-20-26-32	TH	
TELBI Polikraft	14-16-18-20-26-32	TH	TH	VSH Skinpress	40-50-63	-	
	40-50	-	TH	VSH Sudopress	12-15-18-22-28	V	
/STERM Woprex	14-16-20-26-32	HA	HA	Tota Guapasso	35-42-54	-	
	16-20-32	TH/U	TH/U	VSH Xpress Carbon	12-15-18-22-28 35	<u>M</u>	
ERMICALINE Termipex	26	TH	TH		12-15-18-22-28	M	
	14-16	V	V/M	VSH Xpress	35-42-54	- IVI	
HERMADOR	12-15-18-22-28	V / M	V/M	VOLL Versee inne	15-18-22-28	M	
TEKNIADUK	35	-	V/M	VSH Xpress inox	35-42-54	-	
ELIUE O L. D. L. 1700	42-54	-	V	W	40.00.05.00		
EMME Cobra-Pex series 1700	16-20-25-32 14-16-18-20-25-26-32	RF-P TH	- TH	WAVIN Tigris	16-20-25-32 40-50-63	U	
EMME AL-Cobra pex	40-50-63	III	TH	WIEDLAND Cuprotherm CTX	14-16-20	- TH	
	16-20-25-32	U	U	7	14-10-20	III	
RA Multitrapress	40-50-63	-	Ü	ZETAFOOF Furency learney (inculated)	14-16-20	TH/U	T
RA Trapress	12-16-20-25-32	RF-P	Н	ZETAESSE Europex Isopex (insulated)	26-32	TH	
WEETOP	16-18-20-25-32	U	U	ZETAESSE HydroSan / ThermoSan (insulated)	14-16-20	TH/U	I
VLLTOI	40-50-63-75	-	U	ZEWOTHERM	14-16-20-26-32 40-50-63	TH	
	16-20-32	U	U		40-30-03	<u> </u>	
IICAL Max Multipex	26	H-ML	H				
	16-20-32	TH / H-ML / U	TH/H/U				
VIDELTA Deltall	26	TH / H-ML	TH/H				
IIDEEN (DOIRAII	40	-	TH/H/U				
	50-63	-	TH/U				
PONOR Multicouche / Multilayer	16-20-25-32	U	U				









LEGAL NOTICE

THIS CATALOGUE CANCELS AND REPLACES ALL PREVIOUS EDITIONS.

Reproduction rights are reserved in all countries: no reproduction, even partial, may be carried out without the prior written agreement of VIRAX

VIRAX is constantly adapting its products to meet users' requirements and changing techniques; this is why the models presented in this catalogue and their compositions (representations, photographs, characteristics, dimensions and weights) may be modified or removed without notice and without any obligation on us to make modifications to any tools or equipment sold earlier.

The usage and safety instructions in this catalogue do not take the place of trade standards or any legal and statutory provisions that apply in terms of safety.

The performances indicated for the products are those obtained during tests carried out in VIRAX laboratories. They are non contractual.

When a product is no longer marketed, VIRAX promises to provide spare parts for a period of two years. VIRAX will propose a substitute solution if these parts are no longer available before the end of this two-year period.

Our registered trademarks:

Cobraz, Etaugriff, Eurostem, Extrudax, Filetfix, Gyroflam, Lame Scie, Le Furet, Recti 9, Rotax, Sanicrom, Siberia, Soft Touch, Turbojet, Vanadix, Viper, Viraglace, Viragrip, Virafal, Visioval, Elite Virax "rewarding your talent" (avec votre talent récompensé), Virax, the Virax logo virax and the arrow .

Marks owned by third parties:

Hilti by Hilti, Circlips by Nomel, Pozidriv by European Industrial Services.

Design and creation: VIRAX, Agence Fidback, Adexos.

Editing: VIRAX, Fidback agency, SNC agency.


Photo credits: Studio Visuel Impact, Studio CP Création.

Technical drawings, illustrations: T. Lecerf, C. Toussaint

Art purchases: Thinkstock

Publication: 2018







39 QUAI DE MARNE - CS 40197 - 51206 ÉPERNAY, FRANCE

CUSTOMER SERVICE, FRANCETEL.: +33 (0)3 26 59 56 78 - FAX: +33 (0)3 26 59 56 20 - EMAIL: CLIENT.FR@VIRAX.COM

CONTACT A VIRAX EXPERT

TEL.: 03 26 59 56 82

INTERNATIONAL CUSTOMER SERVICE

TEL.: +33 (0)3 26 59 56 97 - FAX: +33 (0)3 26 59 56 70 - EMAIL: EXPORT@VIRAX.COM









